

**Safety Data Sheet**

**PG 300**

Safety Data Sheet dated: 11/11/2022 - version 1

Date of first edition: 11/11/2022

**1. IDENTIFICATION**

**Product identifier**

Mixture identification:

Trade name: PG 300

Trade code: PLY0111

**Recommended use of the chemical and restrictions on use**

Recommended use: Bituminous mastics solvent based

Restrictions on use: Not available

**Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party**

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive

33442 - Deerfield Beach - FL - USA

Phone: +1 866-222-9782

Responsible: info@polyglass.com

**Emergency 24 hour numbers:**

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887 Emergency Transport CANUTEC (Canada) 1-613-996-6666

**2. HAZARD(S) IDENTIFICATION**



**Classification of the chemical**

Flammable Liquids — Category 3

Skin irritation, Category 2

Eye irritation, Category 2A

Germ cell mutagenicity, Category 1B

Carcinogenicity, Category 1A

Specific target organ toxicity following repeated exposure, Category 1

Acute aquatic hazard, category 3

Chronic (long term) aquatic hazard, category 3

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause genetic defects if inhaled, in contact with skin and if swallowed.

May cause cancer if inhaled, in contact with skin and if swallowed.

Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Harmful to aquatic life

Harmful to aquatic life with long lasting effects.

**Label elements**

**Pictograms and Signal Words**



Danger

**Hazard statements:**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects if inhaled, in contact with skin and if swallowed.

H350 May cause cancer if inhaled, in contact with skin and if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

H402 Harmful to aquatic life

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements:**

|                |  |
|----------------|--|
| P201           | Obtain special instructions before use.  |
| P202           | Do not handle until all safety precautions have been read and understood.  |
| P210           | Keep away from heat/sparks/open flames/hot surfaces. — No smoking.   |
| P233           | Keep container tightly closed.   |
| P240           | Ground/bond container and receiving equipment.   |
| P241           | Use explosion-proof electrical/ventilating/lighting equipment.   |
| P242           | Use only non-sparking tools.   |
| P243           | Take precautionary measures against static discharge.  |
| P260           | Do not breathe mist/vapours/spray.   |
| P264           | Wash skin thoroughly after handling.   |
| P270           | Do not eat, drink or smoke when using this product.  |
| P273           | Avoid release to the environment.  |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P314           | Get medical advice/attention if you feel unwell.   |
| P321           | Specific treatment (see supplementary instructions on this label)  |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P370+P378      | In case of fire, use a dry powder fire extinguisher to extinguish.   |
| P403+P235      | Store in a well-ventilated place. Keep cool.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container in accordance with applicable regulations.   |

**Ingredient(s) with unknown acute toxicity:**

None

**Hazards not otherwise classified identified during the classification process:**

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

**3. COMPOSITION/INFORMATION ON INGREDIENTS****Substances**

Not Relevant

**Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

**List of components**

| Concentration (% w/w) | Name  | Ident. Numb.  | Classification   | Registration Number |
|-----------------------|---|---|--|---------------------|
| 50-75 %               | petroleum hydrocarbons; Stoddard Solvent  | CAS:8052-41-3<br>EC:232-489-3<br>Index:649-345-00-4 | Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Muta. 1B, H340; Carc. 1B, H350 |                     |
| 20-25 %               | asphalt; bitumen  | CAS:8052-42-4<br>EC:232-490-9                       | Carc. 2, H351  |                     |
| 1-2.5 %               | 1-propanamine, 3-(isodecyloxy)-, acetate; 3-(Isodecyloxy)propylammonium acetate | CAS:28701-67-9<br>EC:249-166-8                      | Acute Tox. 4, H302; Skin Corr. 1B, H314; Aquatic Chronic 1, H410                       |                     |
| 0.49-1 %              | silica sand; quartz   | CAS:14808-60-7<br>EC:238-878-4                      | STOT RE 1, H372; Carc. 1A, H350  |                     |

---

## 4. FIRST AID MEASURES

### Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- If breathing is irregular or stopped, administer artificial respiration.
- In case of inhalation, consult a doctor immediately and show him packing or label.

### Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

### Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

---

## 5. FIRE-FIGHTING MEASURES

### Extinguishing media

Suitable extinguishing media:

### Unsuitable extinguishing media:

None in particular.

### Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: Not available
- Explosive properties: Not available
- Oxidizing properties: Not available

### Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
  - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
  - Move undamaged containers from immediate hazard area if it can be done safely.
- 

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove all sources of ignition.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Provide adequate ventilation.
- Use appropriate respiratory protection.
- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Limit leakages with earth or sand.

### Methods and material for containment and cleaning up

- Suitable material for taking up: absorbing material, organic, sand
  - Retain contaminated washing water and dispose it.
- 

## 7. HANDLING AND STORAGE

### Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Exercise the greatest care when handling or opening the container.
- Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Handle in a well ventilated place.

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Opened containers must be carefully resealed and kept upright to prevent leakage.

Flammable mixtures may accumulate within the headspace of containers at room temperature.

Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.

Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Electrical installations / working materials must comply with the technological safety standards.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### List of components with OEL value

|  | OEL Type | Country     | Long Term mg/m3 | Long Term ppm | Short Term mg/m3 | Short Term ppm | Note   |
|--|----------|-------------|-----------------|---------------|------------------|----------------|--|
| petroleum hydrocarbons; Stoddard Solvent<br>CAS: 8052-41-3 | OSHA     |             | 2900            | 500           |                  |                |  |
|  | ACGIH    |             |                 | 100           |                  |                | CNS impairment;eye, kidney and skin damage;nausea;   |
| asphalt; bitumen<br>CAS: 8052-42-4                         | ACGIH    |             | 0.5             |               |                  |                | A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free);eye and upper respiratory tract irritation (fume); |
|  | MAK      | GERMANY     | 1.5             |               |                  |                |  |
|  | MAK      | SWITZERLAND | 10              |               |                  |                |  |
| silica sand; quartz<br>CAS: 14808-60-7                     | ACGIH    |             | 0.025           |               |                  |                | A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;  |
|  | MAK      | AUSTRIA     | 0.15            |               |                  |                |  |
|  | MAK      | SWITZERLAND | 0.15            |               |                  |                |  |

### Biological Exposure Index

|                                    | Value | UoM  | Medium | Biological Indicator    | Sampling Period                  |
|------------------------------------|-------|------|--------|-------------------------|----------------------------------|
| asphalt; bitumen<br>CAS: 8052-42-4 |       |      | Urine  | 1-Hydroxypyrene         | End of turn; End of working week |
|                                    | 2.5   | µg/L | Urine  | 1-Hydroxypyrene         | End of turn; End of working week |
|                                    |       |      | Urine  | 3-Hydroxybenzo(a)pyrene | End of turn; End of working week |

Appropriate engineering controls: Not available

### Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness  $\geq 0,5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Nitrile rubber - NBR: thickness  $\geq 0,35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Butyl rubber - IIR: thickness  $\geq 0,5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluorinated rubber - FKM: thickness  $\geq 0,4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid Black

Odour: hydrocarbons like

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available

Initial boiling point and boiling range: 179 °C (354 °F)

Flash point: 40.5 °C (104.9 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: 3.55 % w/w

Vapour density: >1

Vapour pressure: No data available

Relative density: 0.95 g/cm<sup>3</sup>

Solubility in water: Insoluble

Solubility in oil: no data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available

Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available

Oxidizing properties: No data available

Solid/gas flammability: data not applicable

### Other information

Substance Groups relevant properties Not normally reactive

Miscibility: No data available

Fat Solubility: No data available

Conductivity: No data available

---

## 10. STABILITY AND REACTIVITY

### Reactivity

Stable

It may generate dangerous reactions (See subsections below)

### Chemical stability

It may generate dangerous reactions (See subsections below)

### Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

### Conditions to avoid

Heat and open flames.

Avoid accumulating electrostatic charge.

## Incompatible materials

Water

Avoid contact with combustible materials. The product could catch fire.

## Hazardous decomposition products

Develop toxic gases when heated to decomposition.

---

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

#### Toxicological information of the mixture:

|                                      |   |
|--------------------------------------|---|
| a) acute toxicity                    | Not classified  |
|                                      | Based on available data, the classification criteria are not met  |
| b) skin corrosion/irritation         | The product is classified: Skin irritation, Category 2(H315)  |
| c) serious eye damage/irritation     | The product is classified: Eye irritation, Category 2A(H319)  |
| d) respiratory or skin sensitisation | Not classified  |
|                                      | Based on available data, the classification criteria are not met  |
| e) germ cell mutagenicity            | The product is classified: Germ cell mutagenicity, Category 1B(H340)                                    |
| f) carcinogenicity                   | The product is classified: Carcinogenicity, Category 1A(H350)   |
| g) reproductive toxicity             | Not classified  |
|                                      | Based on available data, the classification criteria are not met  |
| h) STOT-single exposure              | Not classified  |
|                                      | Based on available data, the classification criteria are not met  |
| i) STOT-repeated exposure            | The product is classified: Specific target organ toxicity following repeated exposure, Category 1(H372) |
| j) aspiration hazard                 | Not classified  |
|                                      | Based on available data, the classification criteria are not met  |

#### Toxicological information on main components of the mixture:

|  |                   |   |
|--|-------------------|---|
| petroleum hydrocarbons;<br>Stoddard Solvent  | a) acute toxicity | LD50 Skin Rabbit > 3000 mg/kg                     |
|  |                   | LC50 Inhalation Rat > 5.5 mg/l 4h                 |
| asphalt; bitumen   | a) acute toxicity | LD50 Skin Rabbit > 2000 mg/kg                     |
|  |                   | LD50 Oral Rat > 5000 mg/kg                        |
|  |                   | LC50 Inhalation Rat > 94.4 mg/m <sup>3</sup> 4.5h |
|  |                   | LD50 Oral Rat > 5000 mg/kg                        |
| 1-propanamine, 3-<br>(isodecyloxy)-, acetate;<br>3-<br>(Isodecyloxy)<br>propylammonium acetate | a) acute toxicity | LD50 Oral Rat = 1216 mg/kg                        |
| silica sand; quartz  | a) acute toxicity | LD50 Oral Rat = 500 mg/kg                         |

#### Substance(s) listed on the IARC Monographs:

|                     |          |
|---------------------|----------|
| asphalt; bitumen    | Group 2B |
| silica sand; quartz | Group 1  |

#### Substance(s) listed as OSHA Carcinogen(s):

asphalt; bitumen  
silica sand; quartz

#### Substance(s) listed as NIOSH Carcinogen(s):

asphalt; bitumen  
silica sand; quartz

#### Substance(s) listed on the NTP report on Carcinogens:

---

## 12. ECOLOGICAL INFORMATION

### Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

### List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 3(H402), Chronic (long term) aquatic hazard, category 3(H412)

### List of components with eco-toxicological properties

| Component           | Ident. Numb.                                | Ecotox Infos   |
|---------------------|---|--|
| silica sand; quartz | CAS: 14808-60-7<br>7 - EINECS:<br>238-878-4 | a) Aquatic acute toxicity : LC50 carp > 10000 mg/L 72h |

### Persistence and degradability

N.A.

### Bioaccumulative potential

N.A.

### Mobility in soil

N.A.

### Other adverse effects

N.A.

---

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

---

## 14. TRANSPORT INFORMATION

### UN number

DOT-UN Number: UN1993

ADR-UN number: 1993

IATA-Un number: 1993

IMDG-Un number: 1993

### UN proper shipping name

DOT-Proper Shipping Name: Flammable liquids, n.o.s. (solvent naphtha - 1,2,4-trimethyl-benzene; pseudocumene)

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - 1,2,4-trimethyl-benzene; pseudocumene)

IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - 1,2,4-trimethyl-benzene; pseudocumene)

IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - 1,2,4-trimethyl-benzene; pseudocumene)

### Transport hazard class(es)

DOT-Hazard Class: 3

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

**Packing group**

DOT-Packing group: III

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

**Environmental hazards**

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: No

**Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not Applicable

**Special precautions**

Department of Transportation (DOT):

DOT-Special Provision(s): B1, B52, IB3, T4, TP1, TP29

DOT-Label(s): 3

DOT-Symbol: N/A

DOT-Cargo Aircraft: N/A

DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A

DOT-Non-Bulk: N/A

Road and Rail ( ADR-RID ) :

ADR-Label: 3

ADR-Hazard identification number: 30

ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air ( IATA ) :

IATA-Passenger Aircraft: 355

IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3

Sea ( IMDG ) :

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 223 274 955

IMDG-Page: N/A

IMDG-Label: N/A

IMDG-EMS: F-E, S-E

IMDG-MFAG: N/A

---

**15. REGULATORY INFORMATION**

**USA - Federal regulations**

**TSCA - Toxic Substances Control Act**

**TSCA inventory:**

All the components are listed on the TSCA inventory

**TSCA listed substances:**

petroleum hydrocarbons; Stoddard is listed in TSCA Section 8b Solvent

asphalt; bitumen is listed in TSCA Section 8b

1-propanamine, 3-(isodecyloxy)-, is listed in TSCA Section 8b

acetate; 3-(Isodecyloxy)propylammonium acetate

silica sand; quartz is listed in TSCA Section 8b



**SARA - Superfund Amendments and Reauthorization Act**

**Section 302 - Extremely Hazardous Substances:**

No substances listed

**Section 304 - Hazardous substances:**

No substances listed

**Section 313 - Toxic chemical list:**

No substances listed

**CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act**

**Substance(s) listed under CERCLA:**

No substances listed

**CAA - Clean Air Act**

**CAA listed substances:**

No substances listed

**CWA - Clean Water Act**

**CWA listed substances:**

No substances listed

**USA - State specific regulations**

**California Proposition 65**

**Substance(s) listed under California Proposition 65:**

silica sand; quartz                      Listed as carcinogen

**Massachusetts Right to know**

**Substance(s) listed under Massachusetts Right to know:**

petroleum hydrocarbons; Stoddard Solvent

asphalt; bitumen

silica sand; quartz

**Pennsylvania Right to know**

**Substance(s) listed under Pennsylvania Right to know:**

petroleum hydrocarbons; Stoddard Solvent

asphalt; bitumen

silica sand; quartz

**New Jersey Right to know**

**Substance(s) listed under New Jersey Right to know:**

petroleum hydrocarbons; Stoddard Solvent

asphalt; bitumen

silica sand; quartz

**Canada - Federal regulations**

**DSL - Domestic Substances List**

**DSL Inventory:**

All the substances are listed in the DSL.

**NDSL - Non Domestic Substances List**

**NDSL Inventory:**

No substances listed

**NPRI - National Pollutant Release Inventory**

**Substances listed in NPRI:**

No substances listed

**16. OTHER INFORMATION**

Safety Data Sheet dated: 11/11/2022 - version 1

**Additional classification information**

NFPA Health: 1 = Slight

NFPA Flammability: 2 = Combustible liquid

NFPA Reactivity: 0 = Minimal

NFPA Special Risk: NONE



NFPA

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to

be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

| <b>Code</b> | <b>Description</b>  |
|-------------|---|
| H226        | Flammable liquid and vapour.                                    |
| H302        | Harmful if swallowed.   |
| H304        | May be fatal if swallowed and enters airways.                   |
| H314        | Causes severe skin burns and eye damage.                        |
| H340        | May cause genetic defects.                                      |
| H350        | May cause cancer.   |
| H351        | Suspected of causing cancer.                                    |
| H372        | Causes damage to organs through prolonged or repeated exposure. |
| H410        | Very toxic to aquatic life with long lasting effects.           |

| <b>Code</b> | <b>Hazard class and hazard category</b> | <b>Description</b>   |
|-------------|---|--|
| A.1/4/Oral  | Acute Tox. 4                            | Acute toxicity (oral), Category 4                                      |
| A.10/1      | Asp. Tox. 1                             | Aspiration hazard, Category 1  |
| A.2/1B      | Skin Corr. 1B                           | Skin corrosion, Category 1B  |
| A.5/1B      | Muta. 1B                                | Germ cell mutagenicity, Category 1B                                    |
| A.6/1A      | Carc. 1A                                | Carcinogenicity, Category 1A   |
| A.6/1B      | Carc. 1B                                | Carcinogenicity, Category 1B   |
| A.6/2       | Carc. 2                                 | Carcinogenicity, Category 2  |
| A.9/1       | STOT RE 1                               | Specific target organ toxicity following repeated exposure, Category 1 |
| B.6/3       | Flam. Liq. 3                            | Flammable Liquids — Category 3   |
| US-HAE/C1   | Aquatic Chronic 1                       | Chronic (long term) aquatic hazard, category 1                         |

**Legend to abbreviations and acronyms used in the safety data sheet:**

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
- IMDG: International Maritime Code for Dangerous Goods.
- IATA: International Air Transport Association.
- IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
- ICAO: International Civil Aviation Organization.
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- CLP: Classification, Labeling, Packaging.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- INCI: International Nomenclature of Cosmetic Ingredients.
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- GefStoffVO: Ordinance on Hazardous Substances, Germany.
- LC50: Lethal concentration, for 50 percent of test population.
- LD50: Lethal dose, for 50 percent of test population.
- DNEL: Derived No Effect Level.
- PNEC: Predicted No Effect Concentration.
- TLV: Threshold Limiting Value.
- TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
- STEL: Short Term Exposure limit.
- STOT: Specific Target Organ Toxicity.
- WGK: German Water Hazard Class.
- KSt: Explosion coefficient.