


POLYGLASS ROOFING SYSTEM DETAIL



DETAIL KEYNOTES


- SURFACE COAT POLYGLASS ELASTOMERIC ROOF COATINGS.
- BASE COAT POLYGLASS ELASTOMERIC ROOF COATINGS.
- FLASHING COMPOUND POLYGLASS FLASHING COMPOUND WHERE REQUIRED. APPLY AT 1/8" THICK AND USE WITH POLYESTER REINFORCEMENT.
- POLYESTER POLYGLASS REINFORCING POLYESTER.
- SURFACE PREPARATION ALL SURFACES SHALL BE CLEAN, DRY, AND FREE OF ANY DIRT, DUST, GRAVEL, OIL, SURFACE CHEMICALS OR OTHER CONTAMINANTS THAT MAY INTERFERE WITH OPTIMUM ADHESION. POLYGLASS RECOMMENDS ADHESION TEST PRIOR TO COATING APPLICATION. IF ADHESION TEST FAILS, ADDITIONAL CLEANING AND/OR PRIMING MAY BE REQUIRED.

TYP. VENT PIPE FLASHING DETAIL

NUMBER:
PG-VPF-010

DATE:
NOVEMBER 2016

ROOFING AND WATERPROOFING SYSTEMS



www.polyglass.com