

## Safety Data Sheet

### POLYBRITE 79

Safety Data Sheet dated: 05/20/2023 - version 5

Date of first edition: 06/16/2022



## 1. IDENTIFICATION

### Product identifier

Mixture identification:

Trade name: POLYBRITE 79

Trade code: PLY0102

### Recommended use of the chemical and restrictions on use

Recommended use: Primer

Restrictions on use: Not available

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive

33442 - Deerfield Beach - FL - USA

Phone: +1 866-222-9782

Responsible: info@polyglass.com

### Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887 Emergency Transport CANUTEC (Canada) 1-613-996-6666

## 2. HAZARD(S) IDENTIFICATION



### Classification of the chemical

Flammable Liquids — Category 3

Skin Sensitization, Category 1

Carcinogenicity, Category 2

Acute aquatic hazard, category 2

Chronic (long term) aquatic hazard, category 2

Flammable liquid and vapour.

May cause an allergic skin reaction.

Suspected of causing cancer if inhaled, in contact with skin and if swallowed.

Toxic to aquatic life

Toxic to aquatic life with long lasting effects.

### Label elements

#### Pictograms and Signal Words



Warning

### Hazard statements

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer if inhaled, in contact with skin and if swallowed.
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects.

### Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist/vapours/spray.

P272	Contaminated work clothing must not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see supplementary instructions on this label)
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.
P391	Collect spillage.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

**Ingredient(s) with unknown acute toxicity:**

None

**Hazards not otherwise classified identified during the classification process:**

None

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substances**

Not Relevant

**Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

**List of components**

Qty	Name	Ident. Numb.	Classification	Registration Number
75-100 %	4-chloro-a,a,a-trifluorotoluene	CAS:98-56-6 EC:202-681-1	Flam. Liq. 3, H226; Carc. 2, H351; Aquatic Acute 2, H401; Aquatic Chronic 2, H411; Skin Sens. 1, H317	N.A.
5-10 %	xylenes; 1,2 dimethylbenzene	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Acute Tox. 4, H332; Acute Tox. 4, H312; Skin Irrit. 2, H315	
2.5-5 %	tetraethyl orthosilicate; tetraethyl silicate	CAS:78-10-4 EC:201-083-8 Index:014-005-00-0	Flam. Liq. 3, H226; Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335	
2.5-5 %	titanium acetylacetonate; Titanium diisopropoxide bis(2,4-pentanedionate)	CAS:17927-72-9 EC:241-866-1	Eye Irrit. 2A, H319	
1-2.5 %	ethyl benzene; aethylbenzol	CAS:100-41-4 EC:202-849-4 Index:601-023-00-4	Flam. Liq. 2, H225; Acute Tox. 4, H332; Asp. Tox. 1, H304	
1-2.5 %	isopropyl alcohol; Isopropanol	CAS:67-63-0 EC:200-661-7 Index:603-117-00-0	Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336	N.A.

**4. FIRST AID MEASURES**

**Description of first aid measures**

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

**Most important symptoms/effects, acute and delayed**

Not available

**Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

---

## 5. FIRE-FIGHTING MEASURES

### Extinguishing media

Suitable extinguishing media:

### Unsuitable extinguishing media:

None in particular.

### Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

### Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

---

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Store above freezing

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Opened containers must be carefully resealed and kept upright to prevent leakage.

Flammable mixtures may accumulate within the headspace of containers at room temperature.

Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.

Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Electrical installations / working materials must comply with the technological safety standards.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
4-chloro-a,a,a-trifluorotoluene CAS: 98-56-6	MAK	GERMANY	Long Term: 1 mg/m <sup>3</sup>
	OSHA		Long Term: 2.5 mg/m <sup>3</sup>
	ACGIH		Long Term: 2.5 mg/m <sup>3</sup> "A4 - Not Classifiable as a Human Carcinogen" As Fluorides [RR-02792-9];"bone damage;fluorosis" As Fluorides [RR-02792-9]
xylenes; 1,2 dimethylbenzene CAS: 1330-20-7	OSHA		Long Term: 435 mg/m <sup>3</sup> - 100 ppm
	ACGIH		Long Term: 100 ppm; Short Term: 150 ppm A4 - Not Classifiable as a Human Carcinogen;CNS impairment;eye and upper respiratory tract irritation;
	EU		Long Term: 221 mg/m <sup>3</sup> - 50 ppm; Short Term: 442 mg/m <sup>3</sup> - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin;
	MAK	GERMANY	Long Term: 220 mg/m <sup>3</sup> - 50 ppm
	ACGIH		Long Term: 100 ppm; Short Term: 150 ppm A4 - Not Classifiable as a Human Carcinogen;CNS impairment;eye and upper respiratory tract irritation
	MAK	AUSTRIA	Long Term: 221 mg/m <sup>3</sup> - 50 ppm; Short Term: 442 mg/m <sup>3</sup> - 100 ppm
	MAK	SWITZERLAND	Long Term: 435 mg/m <sup>3</sup> - 100 ppm
	EU		Long Term: 221 mg/m <sup>3</sup> - 50 ppm; Short Term: 442 mg/m <sup>3</sup> - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin (pure)
	tetraethyl orthosilicate; tetraethyl silicate CAS: 78-10-4	MAK	GERMANY
OSHA			Long Term: 850 mg/m <sup>3</sup> - 100 ppm
ACGIH			Long Term: 10 ppm eye and upper respiratory tract irritation;kidney damage
MAK		AUSTRIA	Long Term: 44 mg/m <sup>3</sup> - 5 ppm; Short Term: 88 mg/m <sup>3</sup> - 10 ppm
MAK		SWITZERLAND	Long Term: 85 mg/m <sup>3</sup> - 10 ppm
EU			Long Term: 442 mg/m <sup>3</sup> - 100 ppm; Short Term: 884 mg/m <sup>3</sup> - 200 ppm Behaviour Indicative
ethyl benzene; aethylbenzol CAS: 100-41-4	OSHA		Long Term: 435 mg/m <sup>3</sup> - 100 ppm
	ACGIH		Long Term: 20 ppm A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans;upper respiratory tract irritation;kidney damage (nephropathy);cochlear impairment;
	EU		Long Term: 442 mg/m <sup>3</sup> - 100 ppm; Short Term: 884 mg/m <sup>3</sup> - 200 ppm Behaviour Indicative

Possibility of significant uptake through the skin;

MAK	GERMANY	Long Term: 88 mg/m <sup>3</sup> - 20 ppm
ACGIH		Long Term: 20 ppm A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans; upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment
MAK	AUSTRIA	Long Term: 440 mg/m <sup>3</sup> - 100 ppm; Short Term: 880 mg/m <sup>3</sup> - 200 ppm
MAK	SWITZERLAND	Long Term: 220 mg/m <sup>3</sup> - 50 ppm
	D	
EU		Long Term: 442 mg/m <sup>3</sup> - 100 ppm; Short Term: 884 mg/m <sup>3</sup> - 200 ppm Behaviour Indicative Possibility of significant uptake through the skin
isopropyl alcohol; Isopropanol CAS: 67-63-0	ACGIH	Long Term: 200 ppm; Short Term: 400 ppm A4
	OSHA	Long Term: 980 mg/m <sup>3</sup> - 400 ppm
	ACGIH	Long Term: 200 ppm; Short Term: 400 ppm A4 - Not Classifiable as a Human Carcinogen; CNS impairment; eye and upper respiratory tract irritation;
	MAK	GERMANY Long Term: 500 mg/m <sup>3</sup> - 200 ppm
	ACGIH	Long Term: 200 ppm; Short Term: 400 ppm A4 - Not Classifiable as a Human Carcinogen; CNS impairment; eye and upper respiratory tract irritation
	MAK	AUSTRIA Long Term: 500 mg/m <sup>3</sup> - 200 ppm; Short Term: 2000 mg/m <sup>3</sup> - 800 ppm
	MAK	SWITZERLAND Long Term: 500 mg/m <sup>3</sup> - 200 ppm
	D	

### Biological limit values

4-chloro-a,a,a-trifluorotoluene  
CAS: 98-56-6

Biological Indicator: Fluoride; Sampling Period: Before turn  
Value: 2 mg/L; Medium: Urine  
Remark: Background; Not Specific

Biological Indicator: Fluoride; Sampling Period: End of turn  
Value: 3 mg/L; Medium: Urine  
Remark: Background; Not Specific

xylenes; 1,2-dimethylbenzene  
CAS: 1330-20-7

Biological Indicator: Methyl uric Acid; Sampling Period: End of turn  
Value: 1.5 GGCREAT; Medium: Urine

ethyl benzene;  
aethylbenzol  
CAS: 100-41-4

Biological Indicator: Mandelic acid and fenilgliossalico; Sampling Period: End of turn; End of working week  
Value: 0.7 GGCREAT; Medium: Urine  
Remark: Not Specific; Semiquantitative

Biological Indicator: Ethylbenzene; Sampling Period: Not critical  
Medium: Air at the end of exhalation  
Remark: Semiquantitative

Biological Indicator: Mandelic acid and fenilgliossalico; Sampling Period: End of turn  
Value: 0.15 GGCREAT; Medium: Urine  
Remark: Not Specific

isopropyl alcohol;  
Isopropanol  
CAS: 67-63-0

Biological Indicator: Acetone; Sampling Period: End of turn; End of working week  
Value: 40 mg/L; Medium: Urine  
Remark: Background; Not Specific

Appropriate engineering controls: Not available

### Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness  $\geq 0,5$ mm; breakthrough time  $\geq 480$ min.

Nitrile rubber - NBR: thickness  $\geq 0,35$ mm; breakthrough time  $\geq 480$ min.

Butyl rubber - IIR: thickness  $\geq 0,5$ mm; breakthrough time  $\geq 480$ min.

Fluorinated rubber - FKM: thickness  $\geq 0,4$ mm; breakthrough time  $\geq 480$ min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state: Liquid  
Appearance and colour: liquid Orange  
Odour: Like: Petroleum  
Odour threshold: Not Relevant  
pH: No data available  
Melting point / freezing point: Not Relevant  
Initial boiling point and boiling range: Not Relevant  
Flash point: 49 °C (120 °F)  
Evaporation rate: Not Relevant  
Upper/lower flammability or explosive limits: Not Relevant  
Vapour density: Not Relevant  
Vapour pressure: Not Relevant  
Relative density: 1.05 g/cm<sup>3</sup>  
Solubility in water: immiscible  
Solubility in oil: no data available  
Partition coefficient (n-octanol/water): No data available  
Auto-ignition temperature: No data available  
Decomposition temperature: No data available  
Viscosity: 5,500.00 cPs  
Explosive properties: Not Relevant  
Oxidizing properties: Not Relevant  
Solid/gas flammability: Not Relevant

### Other information

Substance Groups relevant properties Not Relevant  
Miscibility: Not Relevant  
Fat Solubility: Not Relevant  
Conductivity: Not Relevant

---

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available  
It may generate dangerous reactions (See subsections below)

### Chemical stability

It may generate dangerous reactions (See subsections below)

### Possibility of hazardous reactions

None.

### Conditions to avoid

No data available  
Avoid accumulating electrostatic charge.

### Incompatible materials

Data not available.  
Avoid contact with combustible materials. The product could catch fire.

### Hazardous decomposition products

Data not available.

---

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

#### Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified

	Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	The product is classified: Carcinogenicity, Category 2(H351)
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

**Toxicological information on main components of the mixture:**

4-chloro-a,a,a-trifluorotoluene	a) acute toxicity	LD50 Oral Rat 13000 mg/kg
		LC50 Inhalation Mouse 20 mg/l
		LD50 Skin Rabbit > 2 mg/kg
		LD50 Skin Rabbit > 2 ml/kg
		LC50 Inhalation Rat = 33 mg/l 4h
		LD50 Oral Rat = 13 g/kg
		LD50 Skin Rabbit > 2 ml/kg
		LC50 Inhalation Rat = 33 mg/l 4h
		LD50 Oral Rat = 13 g/kg
	LD50 Skin Rabbit > 3300 mg/kg	
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat > 45
xylenes; 1,2 dimethylbenzene	a) acute toxicity	LC50 Inhalation Rat = 47635 mg/l 4h
		LD50 Oral Rat = 4300 mg/kg
		LD50 Skin Rabbit > 4350 mg/kg
		LC50 Inhalation Rat = 29.08 mg/l 4h
		LD50 Oral Rat = 3500 mg/kg
tetraethyl orthosilicate; tetraethyl silicate	a) acute toxicity	LD50 Skin Rabbit = 5878 mg/kg
		LD50 Oral Rat = 6270 mg/kg
		LD50 Skin Rabbit = 5878 mg/kg
ethyl benzene; aethylbenzol	a) acute toxicity	LD50 Skin Rabbit = 15354 mg/kg
		LC50 Inhalation Rat = 172 mg/l 4h
		LD50 Oral Rat = 3500 mg/kg
		LD50 Skin Rabbit = 15400 mg/kg
		LC50 Inhalation Rat = 17.4 mg/l 4h
	LD50 Oral Rat = 3500 mg/kg	
isopropyl alcohol; Isopropanol	a) acute toxicity	LD50 Oral Rat 5500 mg/kg
		LC50 Inhalation Rat 72.6 mg/l
		LD50 Skin Rabbit 12870 mg/kg
		LC50 Inhalation Rat = 16000 ppm 8h
		LD50 Skin Rabbit = 4059 mg/kg

LC50 Inhalation Rat = 72600 mg/m<sup>3</sup> 4h

LD50 Oral Rat = 1870 mg/kg

g) reproductive toxicity No Observed Adverse Effect Level Oral Rat 1

**Substance(s) listed on the IARC Monographs:**

4-chloro-a,a,a-trifluorotoluene Group 2B  
xylenes; 1,2 dimethylbenzene Group 3  
ethyl benzene; aethylbenzol Group 2B  
isopropyl alcohol; Isopropanol Group 3

**Substance(s) listed as OSHA Carcinogen(s):**

4-chloro-a,a,a-trifluorotoluene  
ethyl benzene; aethylbenzol

**Substance(s) listed as NIOSH Carcinogen(s):**

None

**Substance(s) listed on the NTP report on Carcinogens:**

None

---

**12. ECOLOGICAL INFORMATION**

**Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

**List of Eco-Toxicological properties of the product**

The product is classified: Acute aquatic hazard, category 2(H401), Chronic (long term) aquatic hazard, category 2(H411)

**List of Eco-Toxicological properties of the components**

Component	Ident. Numb.	Ecotox Data
4-chloro-a,a,a-trifluorotoluene	CAS: 98-56-6 - EINECS: 202-681-1	LC50 Fish Lepomis macrochirus = 11.4 mg/L 72h UNION CARBIDE CORP. ENVIRONMENTAL SERVICES-THE ACUTE TOXICITY OF PCBTF TO BLUEGILL SUN FISH UCES PROJECT NÂ° 11506-81-07-1979-N.Y.TARRY TOWN. - ca.11.4 ca.14.1 mg/L  LOEC Fish Pimephales promelas 1.4 mg/L ,,E G & G , BIONOMICS, AQUATIC TOXICOLOGY LABORATORY-THE TOXICITY OF PCBTF TO FATHEAD MINNOW EMBRIOS AND LARVAE - REPORT B W - 81-3-838, 1981, WAREHAM IN EPA DOCUMENT NÂ° 40-8152019.  NOEC Fish Pimephales promelas 0.54 mg/L ,,E G & G , BIONOMICS, AQUATIC TOXICOLOGY LABORATORY-THE TOXICITY OF PCBTF TO FATHEAD MINNOW EMBRIOS AND LARVAE - REPORT B W - 81-3-838, 1981, WAREHAM IN EPA DOCUMENT NÂ° 40-8152019.  EC50 Daphnia Daphnia magna = 0.12 mg/L 4d 1/6 2/6 PRESI DA UNION CARBIDE CORP. ENVIRONMENTAL SERVICES-THE ACUTE TOXICITY OF PCBTF TO THE WATER FLEA DAPHNIA MAGNA STRAUS UCES PROJECT NÂ° 11506-81-06-1979- N.Y. TARRY TOWN IN EPA DOCUMENT NÂ° 40-7952015. 4/6 5/6 PRESI DA PECE P. - DETERMINAZI - ca.0.12 ca.0.222 mg/L  EC100 Daphnia Daphnia magna 4.92 mg/L 48h EC50 Daphnia Daphnia magna = 10.7 mg/L 48h - ca.10.7 ca.14.5 mg/L a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 3.68 mg/L 48h IUCLID  a) Aquatic acute toxicity : LC50 Fish Danio rerio = 3 mg/L 96h ECHA
xylenes; 1,2 dimethylbenzene	CAS: 1330-20-7 - EINECS: 215-535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 780 mg/L 96h EPA  a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 13.4 mg/L 96h EPA  a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 2.661 mg/L 96h EPA



		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 13.5 mg/L 96h IUCLID
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 13.1 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 19 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 7.711 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 23.53 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio > 780 mg/L 96h IUCLID
		a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata 30.26 mg/L 96h EPA
		a) Aquatic acute toxicity : EC50 Daphnia water flea = 3.82 mg/L 48h
		a) Aquatic acute toxicity : LC50 Daphnia Gammarus lacustris = 0.6 mg/L 48h
tetraethyl orthosilicate; tetraethyl silicate	CAS: 78-10-4 - EINECS: 201-083-8 - INDEX: 014-005-00-0	a) Aquatic acute toxicity : LC50 Fish Danio rerio > 245 mg/L 96h ECHA
ethyl benzene; aethylbenzol	CAS: 100-41-4 - EINECS: 202-849-4 - INDEX: 601-023-00-4	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 11 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 32 mg/L 96h EPA
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata > 438 mg/L 96h IUCLID
		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 4.2 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 7.55 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 9.1 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata = 9.6 mg/L 96h EPA
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 1.8 mg/L 48h IUCLID
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 4.6 mg/L 72h IUCLID
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 2.6 mg/L 72h EPA
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 1.7 mg/L 96h EPA
isopropyl alcohol; Isopropanol	CAS: 67-63-0 - EINECS: 200-661-7 - INDEX: 603-117-00-0	LC50 Fish Pimephales promelas 9640 mg/L 96h „Veith, G.D., Call, D.J. & Brooke, L.T., Estimating the Acute Toxicity of Narcotic Industrial Chemicals to Fathead Minnows. In: Bishop, W.E., Cardwell, R.D. & Heidolph, B.B. Eds. Aquatic Toxicology and Hazard Assessment: 6th Symp., ASTM STP 802, Philadelph
		LC100 Fish Leuciscus idus melanotus 9750 mg/L 48h „Juhnke, I. Ludemann, D.: Ergebnisse der Untersuchung von 200 chemischen Verbindungen auf akute Fischtoxizität mit dem Goldorfentest. Z. Wasser-Abwasser-Forschung 11 (1978) 161-164. - 9750 10920 mg/L
		LC50 Fish Leuciscus idus melanotus 8970 mg/L 48h „Juhnke, I. Ludemann, D.: Ergebnisse der Untersuchung von 200 chemischen Verbindungen auf akute Fischtoxizität mit dem Goldorfentest. Z. Wasser-Abwasser-Forschung 11 (1978) 161-164. - 8970 9280 mg/L
		EC0 Daphnia Daphnia magna > 10000 mg/L 24h „Bringmann, G. & Kuehn, R., Results of the Damaging Effect of Water Pollutants on Daphnia magna, Z. Wasser Abwasser Forsch., 10(5), 1977, 161 - 166.
		EC50 Daphnia Daphnia magna 9700 mg/L 24h „Bringmann, G. Kuhn, R.: Ergebnisse der Schadwirkung wassergefährdender Stoffe gegen Daphnia magna in einem weiterentwickelten standardisierten Testverfahren. Z.Wasser-Abwasser-Forschung 15 (1982) 1-6.
		EC100 Daphnia Daphnia magna > 10000 mg/L 24h „Bringmann, G. Kuhn, R.: Ergebnisse der Schadwirkung wassergefährdender Stoffe gegen Daphnia magna in einem weiterentwickelten standardisierten Testverfahren. Z.Wasser-Abwasser-Forschung 15 (1982) 1-6.

EC10 Algae Scenedesmus subspicatus (Desmodesmus subspicatus) > 1000 mg/L 96h „Knacker, T. Lebertz, H. Klopffer, W. Zietz, E. Brodsky, J. Oppelt, B. Hilt, J. Sychala, U. Reifenberg, P. Millhoff, H. Kohl, E.G.: Experimentelle Bestimmung von Stoffdaten zur Einstufung "umweltgefÄhrlich

EC90 Algae Scenedesmus subspicatus (Desmodesmus subspicatus) > 1000 mg/L 96h „Knacker, T. Lebertz, H. Klopffer, W. Zietz, E. Brodsky, J. Oppelt, B. Hilt, J. Sychala, U. Reifenberg, P. Millhoff, H. Kohl, E.G.: Experimentelle Bestimmung von Stoffdaten zur Einstufung "umweltgefÄhrlich

EC50 Algae Scenedesmus subspicatus (Desmodesmus subspicatus) > 1000 mg/L 96h „Knacker, T. Lebertz, H. Klopffer, W. Zietz, E. Brodsky, J. Oppelt, B. Hilt, J. Sychala, U. Reifenberg, P. Millhoff, H. Kohl, E.G.: Experimentelle Bestimmung von Stoffdaten zur Einstufung "umweltgefÄhrlich

LOEC Algae Scenedesmus quadricauda 1800 mg/L 7d „Bringmann, G. & Kuehn, R., Comparison of the Toxicity Thresholds of Water Pollutants to Bacteria, Algae and Protozoa in the Cell Multiplication Inhibition Test, Water Research, 14, 1980, 231 - 241.

a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 9640 mg/L 96h IUCLID

a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus > 1400000 µg/L 96h EPA

a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 13299 mg/L 48h IUCLID

a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus > 1000 mg/L 96h IUCLID

a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus > 1000 mg/L 72h IUCLID

a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 11130 mg/L 96h IUCLID

#### **Persistence and degradability**

N.A.

#### **Bioaccumulative potential**

N.A.

#### **Mobility in soil**

N.A.

#### **Other adverse effects**

N.A.

---

### **13. DISPOSAL CONSIDERATIONS**

#### **Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

---

### **14. TRANSPORT INFORMATION**

#### **UN number**

DOT-UN Number: UN1993  
ADR-UN number: 1993  
IATA-Un number: 1993  
IMDG-Un number: 1993

**UN proper shipping name**

DOT-Proper Shipping Name: Flammable liquids, n.o.s. (chlorobenzotrifluoride - ethylbenzene)  
ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (having a flash-point below 23 °C and viscous according to 2.2.3.1.4) (vapour pressure at 50 °C more than 110 kPa, boiling point of more than 35 °C) (chlorobenzotrifluoride - ethylbenzene)  
IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (chlorobenzotrifluoride - ethylbenzene)  
IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (chlorobenzotrifluoride - ethylbenzene)

**Transport hazard class(es)**

DOT-Hazard Class: 3  
ADR-Class: 3  
IATA-Class: 3  
IMDG-Class: 3

**Packing group**

DOT-Packing group: III  
ADR-Packing Group: III  
IATA-Packing group: III  
IMDG-Packing group: III

**Environmental hazards**

Marine pollutant: Yes  
Environmental Pollutant: Not Applicable  
DOT-RQ: Yes            DOT-RQ - Quantity: 100 lbs

**Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not Applicable

**Special precautions**

Department of Transportation (DOT):

DOT-Special Provision(s): B1, B52, IB3, T4, TP1, TP29  
DOT-Label(s): 3  
DOT-Symbol: N/A  
DOT-Cargo Aircraft: N/A  
DOT-Passenger Aircraft: N/A  
DOT-Bulk: N/A  
DOT-Non-Bulk: N/A

Road and Rail (ADR-RID):

ADR-Label: 3  
ADR-Hazard identification number: -  
ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 355  
IATA-Cargo Aircraft: 366  
IATA-Label: 3  
IATA-Subsidiary hazards: -  
IATA-Erg: 3L  
IATA-Special Provisions: A3

Sea (IMDG):

IMDG-Stowage Code: Category A  
IMDG-Stowage Note: -  
IMDG-Subsidiary hazards: -  
IMDG-Special Provisions: 223 274 955  
IMDG-Page: N/A  
IMDG-Label: N/A  
IMDG-EMS: F-E, S-E  
IMDG-MFAG: N/A

---

**15. REGULATORY INFORMATION**

## USA - Federal regulations

### TSCA - Toxic Substances Control Act

#### TSCA inventory:

All the components are listed on the TSCA inventory

#### TSCA listed substances:

4-chloro-a,a,a-trifluorotoluene is listed in TSCA Section 8b Section 8a - PAIR Section 12b

xylene; 1,2 dimethylbenzene is listed in TSCA Section 8b

tetraethyl orthosilicate; tetraethyl silicate is listed in TSCA Section 8b Section 8a - PAIR

titanium acetylacetonate; Titanium diisopropoxide bis(2,4-pentanedionate) is listed in TSCA Section 8b

ethyl benzene; aethylbenzol is listed in TSCA Section 8b

isopropyl alcohol; Isopropanol is listed in TSCA Section 8b

### SARA - Superfund Amendments and Reauthorization Act

#### Section 302 - Extremely Hazardous Substances:

No substances listed

#### Section 304 - Hazardous substances:

xylene; 1,2 dimethylbenzene

ethyl benzene; aethylbenzol

#### Section 313 - Toxic chemical list:

xylene; 1,2 dimethylbenzene

ethyl benzene; aethylbenzol

isopropyl alcohol; Isopropanol

### CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

#### Substance(s) listed under CERCLA:

xylene; 1,2 dimethylbenzene Reportable quantity: 100 pounds

ethyl benzene; aethylbenzol Reportable quantity: 1000 pounds

### CAA - Clean Air Act

#### CAA listed substances:

xylene; 1,2 dimethylbenzene is listed in CAA Section 112(b) - HAP Section 112(b) - HON

ethyl benzene; aethylbenzol is listed in CAA Section 112(b) - HAP Section 112(b) - HON

### CWA - Clean Water Act

#### CWA listed substances:

xylene; 1,2 dimethylbenzene is listed in CWA Section 311

ethyl benzene; aethylbenzol is listed in CWA Section 307 Section 311

## USA - State specific regulations

### California Proposition 65

#### Substance(s) listed under California Proposition 65:

4-chloro-a,a,a-trifluorotoluene Listed as carcinogen

ethyl benzene; aethylbenzol Listed as carcinogen

### Massachusetts Right to know

#### Substance(s) listed under Massachusetts Right to know:

xylene; 1,2 dimethylbenzene

tetraethyl orthosilicate; tetraethyl silicate

ethyl benzene; aethylbenzol

isopropyl alcohol; Isopropanol

### Pennsylvania Right to know

#### Substance(s) listed under Pennsylvania Right to know:

xylene; 1,2 dimethylbenzene

tetraethyl orthosilicate; tetraethyl silicate

ethyl benzene; aethylbenzol

isopropyl alcohol; Isopropanol

### New Jersey Right to know

#### Substance(s) listed under New Jersey Right to know:

4-chloro-a,a,a-trifluorotoluene  
xylenes; 1,2 dimethylbenzene  
tetraethyl orthosilicate; tetraethyl silicate  
ethyl benzene; aethylbenzol  
isopropyl alcohol; Isopropanol

## Canada - Federal regulations

### DSL - Domestic Substances List

#### DSL (Domestic Substances List)

All the substances are listed in the DSL.

### NDSL - Non Domestic Substances List

#### NDSL (Non Domestic Substances List)

No substances listed

### NPRI - National Pollutant Release Inventory

#### NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

## 16. OTHER INFORMATION

Safety Data Sheet dated: 5/20/2023 - version 5

### Additional classification information

NFPA Health: 1 = Slight  
NFPA Flammability: 2 = Combustible liquid  
NFPA Reactivity: 0 = Minimal  
NFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
B.6/2	Flam. Liq. 2	Flammable Liquids — Category 2
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3

US-HAE/A2	Aquatic Acute 2	Acute aquatic hazard, category 2
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

**Legend to abbreviations and acronyms used in the safety data sheet:**

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
- IMDG: International Maritime Code for Dangerous Goods.
- IATA: International Air Transport Association.
- IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
- ICAO: International Civil Aviation Organization.
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- CLP: Classification, Labeling, Packaging.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- INCI: International Nomenclature of Cosmetic Ingredients.
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- GefStoffVO: Ordinance on Hazardous Substances, Germany.
- LC50: Lethal concentration, for 50 percent of test population.
- LD50: Lethal dose, for 50 percent of test population.
- DNEL: Derived No Effect Level.
- PNEC: Predicted No Effect Concentration.
- TLV: Threshold Limiting Value.
- TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
- STEL: Short Term Exposure limit.
- STOT: Specific Target Organ Toxicity.
- WGK: German Water Hazard Class.
- KSt: Explosion coefficient.

**Paragraphs modified from the previous revision:**

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 4. FIRST AID MEASURES
- 6. ACCIDENTAL RELEASE MEASURES
- 7. HANDLING AND STORAGE
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION