

TECHNICAL BULLETIN

POLYGLASS USA Inc.
Corporate Office
1111 West Newport Center Drive
Deerfield Beach, Florida 33442
Tel. (954) 233-1330 - Fax: (954) 418-4453
Email: technical@polyglass.com
Website: www.polyglass.com

Technical Bulletin #2013-03

TO: All POLYGLASS Users

CC: POLYGLASS Sales & Technical Services

Date: April 12, 2013

Author: Steven C. Wadding RRC, RRO, CDT
National Technical Services Manager

RE: Closed Valley Tile Applications

In response to questions related to Closed Valley tile applications within the State of Florida jurisdiction, the following is being provided as clarification to what is interpreted by some as vague language.

Polystick TU Plus underlayment having a fabric surface, is subject to a UV exposure limited of 180 days. At Closed Valley tile applications, there has been some concern related to the potential of the underlayment surface being exposed to UV sunlight. Therefore, the use of a Polyglass mineral surface membrane that is designed for continuous UV exposure would be suitable at valley or other details where tile may allow UV exposure of the underlayment. An additional option at Closed Valley tile locations, products suitable for continuous UV exposure such as mortar may also be an option depending on roof design elements.

Special circumstances and questions should be addressed to POLYGLASS Technical Services Department.

04/12/2013
SCW