

TECHNICAL BULLETIN

POLYGLASS USA Inc.
Corporate Office
1111 West Newport Center Drive
Deerfield Beach, Florida 33442
Tel. (954) 233-1330 - Fax: (954) 418-4453
Email: technical@polyglass.com
Website: www.polyglass.com

Technical Bulletin #2019-01 (Revised from 2007-01)

TO: All **POLYGLASS** Distributors & Users
CC: POLYGLASS Sales & Technical Services
Date: January 15, 2019
Author: James E. Akins,
National Technical Services Manager
RE: Rotation and Storage of Polyglass Roll Products

In our efforts to provide support to Polyglass distributors and stock holders, we would offer the following guidelines to assist in the storage and handling, of Polyglass roll products.

- Polyglass promotes to rotate all stock in a first in first out (FIFO) basis. Seasonally specific, stocked product (Summer-Grade or Winter-Grade) should not be sold or used outside of their designated season. Stock not suitable for the seasonal condition, should be moved from actively used materials and held for appropriate climate conditions and/or season.
- Polyglass recommends that all boxed product be stored inside from weather and limited to double stacking of pallets. Any stacked pallets shall incorporate the use of a plywood separator between pallets.
- Non-boxed APP and SBS membranes are packaged for exterior storage. These products can usually be exposed to weather. Indoor storage is encouraged during winter months, if possible. Any double-stacked pallets shall incorporate the use of a plywood separator between pallets.
- Polyglass does allow the practice of triple stacking of palletized APP membranes/products (3 pallets). Any double-stacked or triple-stacked pallets shall incorporate the use of a plywood separator between pallets.
- Polyglass does allow the practice of double-stacking of palletized SBS membranes/products (2 pallets). Any double-stacked pallets shall incorporate the use of a plywood separator between pallets. Polyglass does not recommend nor support triple stacked SBS membranes/products.
- Roll membranes shall be stored upright on an elevated surface such as a pallet and on a flat surface. Rolls stored or transported in a laid down position, will result in distorted, damaged or “flattened” rolls.

Special circumstances and questions can be addressed to the POLYGLASS Technical Services Department.

