

# **SECTION 1 PRODUCT NAME AND COMPANY IDENTIFICATION**

**Product Name: Polybrite 84 Rust Inhibitive Primer** 

Recommended Use: Roofing and other construction applications

Restriction on Use: None

Manufacturer:
Polyglass U.S.A. Inc.
1111 West Newport Center Drive
Deerfield Beach, Florida 33442
866-222-9782

SDS Date of Preparation: 11/7/16

Emergency Contact: (800) 424-9300 CHEMTREC (USA)

# **SECTION 2: HAZARDS IDENTIFICATION**

# **Hazard Classification:**

Physical	Health
Not Hazardous	Skin Sensitization Category 1

### Label Elements:



Warning!

May cause an allergic skin reaction.

Avoid breathing mist, vapors or spray.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

Dispose of contents and container in accordance with local and national regulations.

# **SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS**

<u>INGREDIENTS</u>	<u>CAS#.</u>	<u>WT.%</u>
Titanium Dioxide	13463-67-7	30-50
Calcium Carbonate	1317-65-3	10-20
Propylene Glycol	57-55-6	10-20
Amorphous Silicon Dioxide	7631-86-9	1-10
Zinc Oxide	1314-13-2	1-5
Surfactant	Proprietary	0.1-<1



Note: The titanium dioxide in this product is inextricably bound so no exposure will occur and the carcinogen classification does not apply

The exact percentage (concentration) of composition has been withheld as a trade secret.

#### **SECTION 4 FIRST AID MEASURERS**

Eyes: Flush eyes with water while lifting the upper and lower lids. Get medical attention if irritation persists.

**Skin:** Remove contaminated clothing. Wash skin thoroughly with soap and water. If irritation or rash develops, get medical attention. Launder clothing before re-use.

Inhalation: If symptoms develop, move to fresh air. If symptoms persist, get medical attention.

**Ingestion:** If conscious, rinse mouth with water. Never give anything by mouth to a person who is unconscious or convulsing. If large amount if swallowed or gastrointestinal effects develop, get medical attention.

**Most important symptoms/effects, acute and delayed:** Causes mild eye irritation. Prolonged contact may cause skin irritation and dryness. May cause an allergic skin reaction based on animal data.

**Indication of immediate medical attention and special treatment, if necessary:** Immediate medical attention is not normally required.

### **SECTION 5 FIRE FIGHTING MEASURES**

**Extinguishing Media:** Use any media appropriate for the surrounding fire. Cool fire exposed containers with water. **Special Protective Equipment and Precautions for Fire-fighters:** Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus. Do not allow run-off from firefighting to enter drains or water courses. **Specific Hazards Arising from the Chemical:** This product is an aqueous mixture that will not burn until all water has evaporated. Residue will burn after the fire has evaporated. Combustion products may include oxides of carbon and zinc.

#### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

**Personal Precautions, Protective Equipment, and Emergency Procedures:** Wear appropriate protective clothing to avoid eye and skin contact.

**Methods and Materials for Containment and Cleaning Up:** Dike the spilled material. Attempt to reclaim the free product, if this is possible. Place in an appropriate container for use or disposal. Collect residue with inert material and place into a closable container for disposal. Wash spill area. Prevent runoff to storm sewers and ditches leading to natural waterways. Report spill as required by local and federal regulations.

#### **SECTION 7 HANDLING and STORAGE**

**Precautions for Safe Handling:** Avoid contact with the eyes. Avoid prolonged contact with skin and clothing. Avoid breathing vapors and mists. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use.

Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

**Conditions for Safe Storage, Including any Incompatibilities**: Store in a dry, well-ventilated area. Protect from physical damage. Keep container closed when not in use.



# **SECTION 8 EXPOSURE CONTROLS and PERSONAL PROTECTION**

# **Exposure Guidelines:**

INGREDIENTS	EXPOSURE LIMITS	
Titanium Dioxide	15 mg/m3 TWA OSHA PEL (total dust)	
	10 mg/m3 TWA ACGIH TLV	
Calcium Carbonate	5 mg/m3 TWA OSHA PEL (respirable fraction)	
	15 mg/m3 TWA OSHA PEL (total dust)	
Propylene Glycol	10 mg/m3 TWA AIHA WEEL	
Amorphous Silicon Dioxide	5 mg/m3 TWA OSHA PEL (respirable fraction)	
	15 mg/m3 TWA OSHA PEL (total dust)	
Titanium Dioxide	15 mg/m3 TWA OSHA PEL (total dust)	
	10 mg/m3 TWA ACGIH TLV	
Zinc Oxide	5 mg/m3 TWA OSHA PEL (respirable fraction)	
	15 mg/m3 TWA OSHA PEL (total dust)	
	2 mg/m3 TWA ACGIH TLV, 10 mg/m3 STEL (respirable)	
Surfactant	None Established	

**Appropriate Engineering Controls:** Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits.

**Respiratory Protection:** If the exposure limits are exceeded a NIOSH approved respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Gloves: Rubber or other impervious gloves are recommended to prevent prolonged skin contact.

Eye Protection: Chemical safety goggles should be worn if splashing is possible.

Other Protective Equipment: Impervious clothing as needed to avoid prolonged skin contact. For operations where contact can occur, a safety shower and an eye wash facility should be available.

### **SECTION 9 PHYSICAL and CHEMICAL PROPERTIES**

Appearance And Odor: Black liquid with a paint-like odor.

Appearance 7 tha Gaor. Black riquid with a paint like odor.		
<b>Boiling Point (@ 760 mmHg):</b> 212°F (100°C)	Freezing Point: Not available	
Odor Threshold: Not determined	Viscosity: Not determined	
Relative density (H2O=1): Not available	Vapor Pressure: Not available	
VOC: Not available	Vapor Density (AIR=1): >1	
Evaporation Rate: Not available	Solubility In Water: Dispersible	
pH: not available	Partition Coefficient n-Octanol/Water: Not available	
Flash Point: >212 F (>100 C) Setaflash	Autoignition Temperature: Not applicable	
Decomposition Temperature: Not determined	Flammability (solid, gas): Not applicable	
Flammable Limits: (vol % in air) LEL – Not applicable UEL – Not applicable		

### **SECTION 10 STABILITY and REACTIVITY**

Reactivity: Not normally reactive.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known.

Conditions to avoid: None known. Incompatible materials: None known.

Hazardous decomposition products: Thermal decomposition may yield oxides of carbon and zinc.



#### **SECTION 11 TOXICOLOGICAL INFORMATION**

Eye: Contact may cause mild irritation with redness and tearing.

**Skin:** Prolonged skin contact may cause mild irritation and drying of the skin. May cause an allergic skin reaction. **Inhalation:** Inhalation of vapors or mists may cause mucous membrane and upper respiratory tract irritation

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sensitization: The surfactant has been shown to cause skin sensitization in studies with laboratory animal.

Chronic Effects: None known.

**Carcinogenicity:** Titanium dioxide is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B. However, the titanium dioxide in this product is bound in the polymer matrix and dust exposure would not be expected. None of the other components present at 0.1% or greater are listed as a carcinogen by NTP, IARC, ACGIH or OSHA.

#### **Numerical Measures of Toxicity:**

Titanium Dioxide: Oral rat LD50: >5000 mg/kg Calcium Carbonate: Oral rat LD50: 6450 mg/kg

Propylene Glycol: Oral rat LD50: 22,000 mg/kg; Inhalation rat LC50: > >31.7042 mg/L/2 hr; Skin rabbit LD50: >2000 mg/kg

Amorphous Silicon Dioxide: No toxicity data available

Zinc Oxide: Oral rat LD 50 >5 g/kg, Inhalation mouse LC50 >5.7 mg/L/4 hr

Surfactant: Oral rat LD50 >2000 mg/kg, Inhalation rat LC50 1-5 mg/L/4 hr, Dermal rat LD50 >2000 mg/kg

#### **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity: Zinc oxide is classified as very toxic to aquatic organisms. LC50 zebra fish 1.8 mg/L/96 hr; IC50 algae 0.136 mg/L

Persistence and degradability: No data available Bioaccumulative potential: No data available

Mobility in soil: No data available
Other adverse effects: No data available

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Dispose in accordance with all local, state and federal regulations.

# **SECTION 14: TRANSPORT INFORMATION**

Proper Shipping Name: Not Regulated

**UN Number:** None

Hazard Class/Packing Group: None

Labels Required: None

Environmental hazards: None known

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable

Special precautions: None known

### **SECTION 15: REGULATORY INFORMATION**

SARA Hazard Category (311/312): Acute Health

**EPA SARA 313:** This product contains the following chemicals regulated under SARA Title III, section 313: Zinc Oxide (as Zinc Compounds) 1-5%

CERCLA Hazardous Substances (Section 103)/RQ: This product is not subject to CERCLA reporting requirements as it is sold.

Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Polybrite 84 Rust Inhibitive Primer

Page 4 of 5



Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory.

California Proposition 65: This product contains chemicals known to the State of California to cause cancer or reproductive toxicity.

#### **SECTION 16: OTHER INFORMATION**

**NFPA Rating:** Health = 2 Fire = 1 Instability = 0 **HMIS Rating:** Health = 2 Fire = 1 Physical Hazard = 0

SDS Date of Preparation: 11/7/16

Revision Summary: Section 11 Sensitization, Section 15 SARA Hazard Category (311/312)

#### NOTICE

This above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Polyglass U.S.A. Inc. shall not be held liable for any damage resulting from handling or from contact with the above product. This information relates only to the product designated herein and does not relate to its use in combination with any other material or process.