

POLYBRITE® 90.1

HIGH SOLIDS SILICONE ROOF COATING

PRODUCT DESCRIPTION

PolyBrite 90.1 is a premium grade high solids, moisture cure, liquid applied silicone coating which cures to form a seamless membrane when applied over the entire roof area. It also keeps the surface cool, providing protection from ultraviolet sun and other weather exposures.

USES


- Designed for use on existing smooth surface BUR, granulated cap sheets, well adhered acrylic coatings, concrete, metal, sprayed in place polyurethane foam (SPF) and various single-ply roofing membranes. Primer may be required. Contact Polyglass Technical Services for clarification of unusual surfaces or project conditions.

FEATURES AND BENEFITS

- Excellent resistance to weathering including: UV radiation, extreme temperatures, as well as rain, ice and snow.
- Extends the useful life of the roof.
- PolyBrite 90.1 can reduce energy costs by decreasing roof surface temperature.
- Fungal and algal resistant – even in high temperatures.

TYPICAL PHYSICAL PROPERTIES

| TEST PROPERTY | TEST VALUE | TEST PROCEDURE |
|--|------------|------------------------|
| Accelerated Weathering @ 5000 hr (pass/fail) | pass | ASTM D6694 |
| Permeance (perms) | 10.7 | ASTM E96 (procedure B) |
| Elongation (%) | 237 | ASTM D412 |
| Tensile Strength (psi) | 247 | ASTM D412 |
| Hardness (Shore A) | 87 | ASTM D2240 |
| Solids Volume (%) | 92 ± 3 | ASTM D2369 |
| Temperature Stability Range (°F) | -35 to 212 | |
| Tack-free time (hrs, subject to temp/humidity) | 1 – 2 | |
| VOC (gm/l) | < 50 | Calculated |
| Flash Point (°F) | 141 | PMCC |
| Initial Solar Reflectivity | 89 | ASTM C1549 |
| Initial Thermal Emissivity | 90 | ASTM C1371 |
| SRI Value | 113 | Calculated |

|  CRRC COOL ROOF RATING COUNCIL® | Rated Product ID #: 0616-0030 | | | | | | | | | |
|---|--|--|--|--------|-------|----------------|-------------|-----------|----------------|-------------|
| | | | | | | | | | | |
| | Solar Reflectance Thermal Emittance | <table border="1"> <thead> <tr> <th></th> <th>Smooth</th> <th>Rough</th> </tr> <tr> <th>Initial / Aged</th> <td>0.89 / 0.73</td> <td>Not Rated</td> </tr> <tr> <th>Initial / Aged</th> <td>0.90 / 0.88</td> <td>Not Rated</td> </tr> </thead> </table> | | Smooth | Rough | Initial / Aged | 0.89 / 0.73 | Not Rated | Initial / Aged | 0.90 / 0.88 |
| | Smooth | Rough | | | | | | | | |
| Initial / Aged | 0.89 / 0.73 | Not Rated | | | | | | | | |
| Initial / Aged | 0.90 / 0.88 | Not Rated | | | | | | | | |

The ratings above are subject to CRRC rating program conditions, requirements and limitations. Visit coolroofs.org for important information and disclaimers about CRRC rating requirements and limitations. For the purposes of a CRRC rating, a rough substrate is defined as a surface that is equally coarse or coarser than a new (i.e., unweathered) #11 granulated modified bitumen sheet.

Solar Reflectance Index (SRI) – Initial: 113 • Aged: 90

PONDING WATER

The chemistry of silicone, which Polyglass Silicone roof coatings are manufactured with, is not adversely affected by ponding water or prolonged rain exposure. Please be advised that good roofing practices, Building Codes and The National Roofing Contractors Association (NRCA) consider ponding water on any roof undesirable and recommend that all roof systems be designed and built to ensure positive drainage (See the NRCA Roofing and Waterproofing Manual and any applicable Code Ordinances).



APPLICABLE STANDARDS

- Meets or exceeds the requirements of ASTM D6694 Standard Specification For Liquid-Applied Silicone Coating.
- Meets or exceeds the requirements of ASTM C1305 Standard Test Method for Crack Bridging Ability of Liquid Applied Waterproofing Membrane.
- UL Classified - File #R14571
- FM Approved
- Can be used to comply with 2016 Title 24 Part 6 Cool Roof requirements. (White only)
- CRRC Listed. (White only)
- NSF Protocol P151 - Health Effects from Rainwater Catchment System Components. See listing at www.nsf.org for application and cure instructions for rainwater catchment use.
- Texas Department of Insurance
- Florida Building Code
- Miami-Dade County Product Control Approved



PACKAGING

- 5 Gallon (18.9 Liters) Pail
- 55 Gallon (208.1 Liters) Drum

COLORS

Standard colors are White, Light Grey, Dark Grey, and Tan.



www.polyglass.us

POLYBRITE® 90.1

HIGH SOLIDS SILICONE ROOF COATING

APPLICATION INSTRUCTIONS

Surface Preparation:

- Surfaces to be coated with PolyBrite 90.1 must be properly prepared. All surfaces must be clean dry and free of loose particles.

Application:

- Stir well prior to application.
- PolyBrite 90.1 is recommended to be applied with high pressure sprayer for best appearance and coverage. It may also be applied by roller or brush applications.
- PolyBrite 90.1 can be applied in excess of 40 mils in a single coat without blistering, while maintaining maximum adhesion.

Application Equipment:

This product may be sprayed, brushed, or rolled. Due to the high viscosity of the material, a high-pressure airless paint pump capable of producing 3500 PSI should be used. The pump should have a minimum of 3 gallons per minute output. Always use components rated for pump pressure. Hoses should be BUNA-N jacketed for prevention of moisture contamination. Hoses should have a minimum I.D. of ¾" and an adequate working pressure. The spray gun should be high pressure (5000 PSI) with reverse-a-clean spray tip, having a minimum orifice of .030 and a 50° fan tip.

DO NOT USE hose that has been used for Acrylics or other waterborne coatings as the liner absorbs moisture and initiates the silicone cure process.

Storage and Cleaning:

- Shelf life is 24 months if stored in original unopened containers.
- All containers should be sealed when not in use.
- Keep from freezing.
- Store between 40°F and 100°F
- Observe normal safeguards for storing and handling of this product prior to and during application.
- Clean equipment and overspray with water.
- Clean hands with waterless hand cleaner.
- Application tools and equipment can be cleaned with lukewarm water and soap, followed by a rinse of isopropanol, acetone, or Simple Green®. Recirculate through lines and gun until residual coating is removed.
- DO NOT USE MINERAL SPIRITS, XYLENE, TOLUENE, OR VMP & NAPHTHA SOLVENTS.

For Professional Use Only - Keep out of the reach of children.

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Waco, TX
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.
1111 West Newport Center Drive
Deerfield Beach, FL 33442

www.polyglass.us

General Line: (888) 410-1375

(954) 233-1330

Customer Service: (800) 222-9782

Technical Service: (866) 794-9659

Questions? technical@polyglass.com

Product Disclaimer: Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects that result in the material not complying with product specifications for a period of 12 months.

Refer to safety data sheet (SDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances. The product user, and not Polyglass, is responsible for determining the suitability and compatibility of our products for the user's intended use.

For the most current product data and warranty information, visit www.polyglass.us



www.polyglass.us