

ELASTOFLEX SA V

SELF-ADHERING FLASHING STRIPS

Elastoflex SA V Flashing Strips are factory cut rolls of Elastoflex SA V membrane featuring patented ADESO® Dual-Compound Self-Adhered Technology. The Styrene-Butadiene-Styrene (SBS) modified asphalt compound is applied on the top layer and an aggressive self-adhesive compound is applied on the bottom layer. Elastoflex SA V Flashing Strips are comprised of a high performance reinforced fiberglass mat for excellent dimensional stability. Elastoflex SA V Flashing Strips are finished with a polyolefin film on the top surface and film protecting the adhesive on the bottom surface.

When Would Elastoflex SA V Flashing Strips be Used?

- New construction, re-roofing, and BUR repair
- Where an air and moisture barrier is required
- Starter strips for SA membrane systems and most torch applications
- Precut strip for any flanged metal flashing
- Vertical and horizontal tie-in for envelope closure
- Joint treatments
- Sandwich metal in low slope self-adhered systems and steep slope underlayment
- Wall and penetration detailing for SA membrane systems and most torch applications
- Stripping in plywood sheets for increased wind design pressures

Benefits of Using Elastoflex SA V Flashing Strips?

- Self-Adhering for easy application
- Saves time and labor
- Encourages safety by eliminating field fabrication on the roof
- Reliable size and quality
- No wasted materials
- Consistency with field base sheet properties & application



Product Data

Coverage (Approx) per box..... 200 sq ft
Weight (Approx) 97 lbs
Thickness (Nominal) 2.0 mm, 80 mils
Boxes/Pallet..... 20

Standard Stocking Widths & Total Length per Box

4" strip width - (10) rolls per box @ total length of 656' 6"
6" strip width - (6) rolls per box @ total length of 394'
9" strip width - (4) rolls per box @ total length of 262' 6"

| Rolls | | |
|-----------|----------|------------|
| Roll WxL | Wt/Roll | Rolls/Box |
| 4" x 66' | 8.8 lbs | (10 rolls) |
| 6" x 66' | 13.3 lbs | (6 rolls) |
| 9" x 66' | 20.0 lbs | (4 rolls) |
| 13" x 66' | 26.7 lbs | (3 rolls) |
| 18" x 66' | 40.0 lbs | (2 rolls) |

Applicable Standards

- ASTM D1970; ASTM D6163
- ASTM E2578 – Air Barrier
- UL Classified for use in class A, B or C roofs, as listed the latest UL "Roofing Materials and Systems Directory"
- ICC ESR-2018
- Florida Building Code
- Texas Department of Insurance



Used on a drip edge detail and plywood seam.