PREMIUM WATERPROOFING PROTECTION FOR TILE ASSEMBLIES

A Two-Ply Underlayment System







Double Down on Your Protection

Roof tiles serve as a water shedding surface layer in your roof tile assembly; it is a high-performance underlayment that provides for the waterproofing protection you expect.

Polystick® Self-Adhered Underlayments, produced by Polyglass U.S.A., are manufactured with ADESO®, a patented dual-compound self-adhesive technology which provides for a high temperature weathering surface and an aggressive adhesive compound on the bottom, all of which is reinforced with a high strength fiberglass mat.











SEALLap® ULTR

MULTIPLE SURFACE SOLUTIONS

Featuring:

- TU Plus and TU Max Uniquely designed for foam or screw installed roof tile;
- MTS Plus Specially designed for high temperature environments

Each on their own provide for exceptional waterproofing protection and when combined, this two-layer underlayment system doubles the waterproofing protection of your home along with an extended 30 Year Warranty!


Independently tested and Miami-Dade County Approved, the Polystick Two-Ply Underlayment System is the only two-layer system currently available in the Florida Market, offering long lasting waterproofing protection and peace of mind.

Benefits of Polystick Underlayment System

- Independently tested and certified
- May help reduce your insurance premiums*
- Cleaner and faster installation
- Provides meaningful warranty coverage
- Economical, long-term performance
- Watertight protection
- Consult your insurance provider for the most up to date information.









4 billion sq. ft. of dried in homes and counting!



30 Year Warranty

Polyglass U.S.A., Inc. offers up to a 30 year limited warranty for Polystick Two-Ply Underlayment Systems installed only by Polyglass registered contractors.



Florida Made

Polystick roof underlayments are manufactured in Polyglass' Florida plant to meet the needs of Florida weather.



Water Resistant

Polystick underlayments are self-adhering waterproofing membranes specifically designed for tile, metal roofing and shingle roofs.



High Temperature

All Polystick underlayments are designed for high-temperature environments.



High Wind Performance

Polystick underlayments meet Florida Building Codes and Miami-Dade County Approval.



SEALLap®

Patented SEALLap® factory applied adhesive at membrane side laps. No other manufacturer offers this protection.



Self-Sealing Membrane

Polystick underlayments seal around fasteners for best possible waterproofing characteristics.

180 day exposure!

Approvals

- ASTM D 1970, D 5147
- Miami-Dade County Approved for mechanically and foam attached tile
- UL Classified for use in Class A & B roofs, as listed in the latest UL "Roofing Materials and Systems Directory"
- ICC ESR-1697
- Florida Building Code













POLYGLASS U.S.A., Inc.

1111 West Newport Center Drive Deerfield Beach, FL 33442 pgmarketing@polyglass.com Customer Service: (800) 222-9782

polyglass.us

© 2020 Polyglass U.S.A., Inc. All rights reserved.