



ACRYLIC COATINGS MATRIX

Polyglass Product	Single Ply Membranes	Metal Roofs	Smooth Mod Bit or Smooth BUR	Granulated Mod-Bit	Concrete	Roof Foam
PolyBrite® 78 Rinseable EPDM Primer	500 sq. ft./gal. (Sprayer Only)	N/A	N/A	N/A	N/A	N/A
PolyBrite® 745 Acrylic Stain Blocker	N/A	N/A	150-200 sq. ft./gal.	100-150 sq. ft./gal.	100-200 sq. ft./gal.	N/A
PolyBrite® 79 Solvent-based TPO Primer	300-400 sq. ft./gal. (TPO Only)	N/A	N/A	N/A	N/A	N/A
PolyBrite® 84 Rust Inhibitive Primer	N/A	200-300 sq. ft./gal.	N/A	N/A	N/A	N/A
PolyBrite® 70, PolyBrite® 70-QS, PG 700, PG 700-QS, PolyBrite® 75, PolyBrite® 55 Premium Acrylic Coating ^{2,3}	10 Yr = 2.5 Gal/Sq 15 Yr = 3.5 Gal/Sq 20 Yr = 4.5 Gal/Sq	10 Yr = 2.5 Gal/Sq 15 Yr = 3.5 Gal/Sq 20 Yr = 4.5 Gal/Sq	10 Yr = 2.5 Gal/Sq 15 Yr = 3.5 Gal/Sq 20 Yr = 4.5 Gal/Sq	10 Yr = 3.0 Gal/Sq 15 Yr = 4.0 Gal/Sq 20 Yr = 4.5 Gal/Sq	10 Yr = 2.5 Gal/Sq 15 Yr = 3.5 Gal/Sq 20 Yr = 4.5 Gal/Sq	10 Yr = 2.5 Gal/Sq 15 Yr = 3.5 Gal/Sq 20 Yr = 4.5 Gal/Sq
	10 Yr = 40 WFT/20 DFT 15 Yr = 56 WFT/28 DFT 20 Yr = 72 WFT/36 DFT	10 Yr = 40 WFT/20 DFT 15 Yr = 56 WFT/28 DFT 20 Yr = 72 WFT/36 DFT	10 Yr = 40 WFT/20 DFT 15 Yr = 56 WFT/28 DFT 20 Yr = 72 WFT/36 DFT	10 Yr = 48 WFT/24 DFT 15 Yr = 64 WFT/32 DFT 20 Yr = 72 WFT/36 DFT	10 Yr = 40 WFT/20 DFT 15 Yr = 56 WFT/28 DFT 20 Yr = 72 WFT/36 DFT	10 Yr = 40 WFT/20 DFT 15 Yr = 56 WFT/28 DFT 20 Yr = 72 WFT/36 DFT
PolyBrite® 71-HS and PolyBrite® 71 High-Solids Acrylic Coating ^{2,3}	10 Yr = 2.5 Gal/Sq 15 Yr = 3.5 Gal/Sq 20 Yr = 4.5 Gal/Sq	10 Yr = 2.5 Gal/Sq 15 Yr = 3.5 Gal/Sq 20 Yr = 4.5 Gal/Sq	10 Yr = 2.5 Gal/Sq 15 Yr = 3.5 Gal/Sq 20 Yr = 4.5 Gal/Sq	10 Yr = 3.0 Gal/Sq 15 Yr = 4.0 Gal/Sq 20 Yr = 4.5 Gal/Sq	10 Yr = 2.5 Gal/Sq 15 Yr = 3.5 Gal/Sq 20 Yr = 4.5 Gal/Sq	N/A
	10 Yr = 40 WFT/24 DFT 15 Yr = 56 WFT/33 DFT 20 Yr = 72 WFT/43 DFT	10 Yr = 40 WFT/24 DFT 15 Yr = 56 WFT/28 DFT 20 Yr = 72 WFT/43 DFT	10 Yr = 40 WFT/24 DFT 15 Yr = 56 WFT/33 DFT 20 Yr = 72 WFT/43 DFT	10 Yr = 48 WFT/28 DFT 15 Yr = 64 WFT/38 DFT 20 Yr = 72 WFT/43 DFT	10 Yr = 40 WFT/24 DFT 15 Yr = 56 WFT/33 DFT 20 Yr = 72 WFT/43 DFT	N/A
PolyFlash® 1C¹ 1-Part Flashing Compound	4.0 gal/sq. 64 WFT/52 DFT	4.0 gal/sq. 64 WFT/52 DFT	4.0 gal/sq. 64 WFT/52 DFT	4.0 gal/sq. 64 WFT/52 DFT	4.0 gal/sq. 64 WFT/52 DFT	4.0 gal/sq. 64 WFT/52 DFT
1 Gallon applied at 32 Wet Mils (26 Dry Mils) 6" wide will theoretically cover 100 lineal feet						
PolyBrite® 73 "Stretch-Span" Flashing Compound	5.0 Gal/Sq. 80 WFT/42 DFT	5.0 Gal/Sq. 80 WFT/42 DFT	5.0 Gal/Sq. 80 WFT/42 DFT	5.0 Gal/Sq. 80 WFT/42 DFT	5.0 Gal/Sq. 80 WFT/42 DFT	5.0 Gal/Sq. 80 WFT/42 DFT
1 Gallon applied at 80 Wet Mils (42 Dry Mils) 4" wide will theoretically cover 60 lineal feet 1 Gallon applied at 80 Wet Mils (42 Dry Mils) 6" wide will theoretically cover 40 lineal feet						
PolyBrite® 77 Premium SEBS Cement	3.0 gal/sq. 48 WFT/23 DFT	250 - 300 fasteners per gallon, approx.	N/A	N/A	3.0 gal/sq. 48 WFT/23 DFT	N/A
1 Gallon applied at 48 Wet Mils (23 Dry Mils) 4" wide will theoretically cover 100 lineal feet 1 Gallon applied at 48 Wet Mils (23 Dry Mils) 6" wide will theoretically cover 66 lineal feet						

- 1 - The amount listed represents the total volume of product required when applied using the three-course method, including both layers—under and over the fabric.
- 2 - Apply at 24 wet mils (1.5 gallon per 100 square feet maximum) per coat. If more than 1.5 gallons are required, apply in multiple coats. To minimize potential voids or pinholes, apply additional coats perpendicular to the previous coat.
- 3 - Above coverages is for Labor & Material and NDL Warranties for Registered Contractors.

Warranty Fees:

NDL - 10 Year \$.05 per square foot or \$500 Minimum.
 NDL - 15 Year \$.07 per square foot or \$700 Minimum.
 NDL - 20 Year \$.09 per square foot or \$900 Minimum.