Safety Data Sheet POLYGLASS PMMA FLASHING

Safety Data Sheet dated: 11/08/2021 - version 5

Date of first edition: 11/04/2020



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: POLYGLASS PMMA FLASHING

Trade code: 903PB9990

Recommended use of the chemical and restrictions on use

Recommended use: Coating Restrictions on use: N.A.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION





Classification of the chemical

Flam. Liq. 3 Flammable liquid and vapour.

Skin Irrit. 2 Causes skin irritation.

Skin Sens. 1B May cause an allergic skin reaction. STOT SE 3 May cause respiratory irritation.

Aquatic Acute 3 Harmful to aquatic life

Label elements

Pictograms and Signal Words



Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H335 May cause respiratory irritation.

H402 Harmful to aquatic life

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist/vapours/spray.
P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

Date 11/8/2021 Production Name POLYGLASS PMMA FLASHING Page n. 1 of 10

P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a doctor if you feel unwell.
P321	Specific treatment (see supplementary instructions on this label)
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
10-20 %	METHYL METHACRYLATE	CAS:80-62-6	Flam. Liq. 2, H225; STOT SE 3, H335; Skin Irrit. 2, H315; Skin Sens. 1, H317	
10-20 %	2-ETHYLHEXYL ACRYLATE	CAS:103-11-7 EC:203-080-7 Index:607-107- 00-7	Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335; Aquatic Chronic 3, H412; Flam. Liq. 4, H227; Aquatic Acute 2, H401	,
1-2.5 %	TITANIUM DIOXIDE	CAS:13463-67-7 EC:236-675-5 Index:022-006- 00-2	Carc. 2, H351	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Date 11/8/2021 Production Name POLYGLASS PMMA FLASHING Page n. 2 of 10

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Date 11/8/2021 Production Name POLYGLASS PMMA FLASHING Page n. 3 of 10

Cool and adequately ventilated.

Safety electric system.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

List of components with OEL value

	OEL Type	Country	Ceiling	Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
METHYL METHACRYLATE	OSHA			410	100				
	ACGIH				50		100		A4 - Not Classifiable as a Human Carcinogen;body weight effects;eye and upper respiratory tract irritation;pulmonary edema;Sensitizer;
	EU				50		100	Indicative	
	MAK	GERMANY		210	50				
	ACGIH				50		100		A4 - Not Classifiable as a Human Carcinogen; body weight effects; eye and upper respiratory tract irritation; pulmonary edema; dermal sensitizer
	MAK	AUSTRIA		210	50	420	100		
	MAK	SWITZERLAND		210	50				
2-ETHYLHEXYL ACRYLATE	MAK	GERMANY		38	5				
	MAK	AUSTRIA		82	10	82	10		
	MAK	SWITZERLAND		38	5				
	MAK	AUSTRIA	С			82	10		
TITANIUM DIOXIDE	OSHA			15					
	ACGIH			10					A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation;
	MAK	GERMANY		0.3					
	ACGIH			10					A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation
	MAK	AUSTRIA		5		10			

Appropriate engineering controls: N.A.

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Date 11/8/2021 Production Name POLYGLASS PMMA FLASHING Page n. 4 of 10

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: viscous liquid various

Odour: Like: Ester

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available Initial boiling point and boiling range: 101 °C (214 °F)

Flash point: 35 °C (95 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: 1.21 g/cm3 Solubility in water: immiscible Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information on main components of the mixture:

METHYL METHACRYLATE a) acute toxicity LC50 Inhalation Rat = 4632 ppm 4h

LD50 Skin Rabbit 5000 mg/kg

LC50 Inhalation Rat = 7093 ppm 4h

LD50 Oral Rat 8420 mg/kg

2-ETHYLHEXYL ACRYLATE a) acute toxicity LD50 Skin Rabbit = 7522 mg/kg

LD50 Oral Rat = 4435 mg/kg

TITANIUM DIOXIDE a) acute toxicity LD50 Oral Rat > 10000 mg/kg

Substance(s) listed on the IARC Monographs:

Date 11/8/2021 Production Name POLYGLASS PMMA FLASHING Page n. 5 of 10

METHYL METHACRYLATE Group 3 2-ETHYLHEXYL ACRYLATE Group 2B TITANIUM DIOXIDE Group 2B

Substance(s) listed as OSHA Carcinogen(s):

2-ETHYLHEXYL ACRYLATE TITANIUM DIOXIDE

Substance(s) listed as NIOSH Carcinogen(s):

TITANIUM DIOXIDE

Substance(s) listed on the NTP report on Carcinogens:

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

List of components with eco-toxicological properties

List of components with eco-to	xicological properti	les .
Component	Ident. Numb.	Ecotox Infos
METHYL METHACRYLATE	CAS: 80-62-6	a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 243 mg/L 96h EPA
		a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus 170 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss > 79 mg/L 96h IUCLID
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = $69 \text{ mg/L } 48 \text{h}$ IUCLID
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 170 mg/L 96h IUCLID
		a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 125.5 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 153.9 mg/L 96h EPA
		a) Aquatic acute toxicity: LC50 Fish Poecilia reticulata 326.4 mg/L 96h EPA
2-ETHYLHEXYL ACRYLATE	CAS: 103-11-7 - EINECS: 203-080-7 - INDEX: 607-107- 00-7	a) Aquatic acute toxicity: EC50 Algae Desmodesmus subspicatus = 44 mg/L 72h IUCLID
		a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 47 mg/L 96h IUCLID
		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 1.81 mg/L 96h ECHA
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 17.45 mg/L 48h IUCLID
Persistence and degradability		
N.A.		
Bioaccumulative potential		

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

11/8/2021 POLYGLASS PMMA FLASHING Date Production Name Page n. 6 of 10 Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

ADR-UN number: 1263 DOT-UN Number: UN1263 IATA-Un number: 1263 IMDG-Un number: 1263

UN proper shipping name

ADR-Shipping Name: PAINT
DOT-Proper Shipping Name: PAINT
IATA-Technical name: PAINT
IMDG-Technical name: PAINT

Transport hazard class(es)

ADR-Class: 3

DOT-Hazard Class: 3

IATA-Class: 3
IMDG-Class: 3

Packing group

ADR-Packing Group: III DOT-Packing group: III IATA-Packing group: III IMDG-Packing group: III

Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 367, B1, B52, B131, IB3, T2, TP1, TP29

DOT-Label(s): 3

DOT-Symbol: N/A

DOT-Cargo Aircraft: N/A

DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A DOT-Non-Bulk: N/A Road and Rail (ADR-RID) :

ADR-Label: 3

ADR-Hazard identification number: 30

ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air (IATA):

IATA-Passenger Aircraft: 355 IATA-Cargo Aircraft: 366

IATA-Label: 3

Date 11/8/2021 Production Name POLYGLASS PMMA FLASHING Page n. 7 of 10

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3 A72 A192

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 163 223 367 955

IMDG-Page: N/A
IMDG-Label: N/A
IMDG-EMS: F-E, S-E
IMDG-MFAG: N/A

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

METHYL METHACRYLATE is listed in TSCA Section 8b
2-ETHYLHEXYL ACRYLATE is listed in TSCA Section 8b
TITANIUM DIOXIDE is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

METHYL METHACRYLATE

Section 313 - Toxic chemical list:

METHYL METHACRYLATE

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

METHYL METHACRYLATE Reportable quantity: 1000 pounds

CAA - Clean Air Act

CAA listed substances:

METHYL METHACRYLATE is listed in CAA Section 112(b) - HAP Section 112(b) - HON

2-ETHYLHEXYL ACRYLATE is listed in CAA Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

METHYL METHACRYLATE is listed in CWA Section 311

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

TITANIUM DIOXIDE Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

METHYL METHACRYLATE 2-ETHYLHEXYL ACRYLATE

TITANIUM DIOXIDE

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

METHYL METHACRYLATE

2-ETHYLHEXYL ACRYLATE

TITANIUM DIOXIDE

New Jersey Right to know

Date 11/8/2021 Production Name POLYGLASS PMMA FLASHING Page n. 8 of 10

Substance(s) listed under New Jersey Right to know:

METHYL METHACRYLATE

2-ETHYLHEXYL ACRYLATE

TITANIUM DIOXIDE

Canada - Federal regulations

DSL - Domestic Substances List

DSL Inventory:

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL Inventory:

No substances listed

NPRI - National Pollutant Release Inventory

Substances listed in NPRI:

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 11/8/2021 - version 5

Additional classification information

NFPA Health: 1 = Slight

NFPA Flammability: 3 = Flammable liquid

NFPA Reactivity: 2 = Moderate

NFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

Date 11/8/2021 Production Name POLYGLASS PMMA FLASHING Page n. 9 of 10

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 3. COMPOSITION/INFORMATION ON INGREDIENTS

- 12. ECOLOGICAL INFORMATION

Date 11/8/2021 Production Name POLYGLASS PMMA FLASHING Page n. 10 of 10