# **POLYFORZA™ COPING**

# FLASHLESS FASCIA FOR BUR/MODIFIED SYSTEMS

# **PRODUCT DESCRIPTION**

PolyForza Coping is a tested roof edge system that enhances any building's parapet conditions. The system features factory fabricated snap-on cover and 20 ga. galvanized steel anchor clips for quick and easy installation. Polyforza Coping is available in a variety of colors along with tapered, flat or existing slope of options for different wall conditions.

#### **FEATURES AND BENEFITS**

- Full, snap-on design in 12'-0" lengths eliminates crimping and exposed fasteners, reduces installation time, and lowers labor costs.
- Pre-punched fastening holes ensure proper thermal movement and attachment to the building substrate.
- Corrosion resistant, stainless-steel springs are factory attached to the anchor clips and provide long-term, positive spring loading.
- Factory fabricated miters and accessories provide a cleaner appearance and eliminates field fabrication, providing time and labor savings.
- Radius is available to meet the unique needs of each project.
- Additional accessories included are:
  - 8" wide concealed splice plates with dual non-curling isocryl butyl sealant strips allow for thermal movement of materials and seals all joints.
  - 12" wide, 20 ga. galv. steel anchor clips that provide more positive attachment ensuring extra stability for the system. (Anchor clip spacing determined by manufacturer)
  - All required fasteners

# **APPLICATION INSTRUCTIONS**

See PolyForza Coping Installation Instructions.

# **MANUFACTURING FACILITIES**

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Waco, TX
- Winter Haven, FL

#### **CORPORATE HEADQUARTERS**

Polyglass U.S.A., Inc. 1111 West Newport Center Drive Deerfield Beach, FL 33442 www.polyglass.us

General Line: (888) 410-1375

(954) 233-1330

Customer Service: (800) 222-9782 Technical Service: (866) 794-9659

Questions? technical@polyglass.com

**Product Disclaimer:** Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects that result in the material not complying with product specifications for a period of 1 year.

All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.

Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control. For most current product data and warranty information, visit www.polyglass.us



#### **PRODUCT DATA**

#### **Materials**

- 24 ga. steel
- 22 ga. steel
- 0.040" aluminum
- 0.050" aluminum
- 0.063" aluminum

#### **Sizes**

- Face Size/Outside Face:3" to 12"\*
- Back Size/Inside Face:
  2.25" to 4"\*
  - O No Testing or Approvals: Max 12"
- Wall Size:
  - o 3.5" to 16"\*
  - No Testing or Approvals: Max 39.875"

### **APPLICABLE STANDARDS**

- ANSI/SPRI/FM 4435/ES-1 Standard
- FM Approved
- Miami-Dade County Approved





#### **AVAILABLE COLORS**

Choose from over 30 colors and finishes, see color chart for color options.



<sup>\*</sup>Tested/Approved