# POLYFORZA<sup>™</sup> ONE EXTENDED FASCIA

## FLASHLESS FASCIA FOR BUR/MODIFIED SYSTEMS

#### **PRODUCT DESCRIPTION**

PolyForza One Extended Fascia offers a convenient and economical way to protect and enhance the appearance of the roof edge. PolyForza One Extended Fascia for BUR or modified roofs extends your coverage on the roof edge while protecting against high wind events, saving the building from costly damage. The design eliminates the stripping in typical of other products, making it fast and easy to install.

#### **FEATURES AND BENEFITS**

- Snap-on cover with extruded aluminum bar for secure membrane termination and easy installation.
- Provided in 12'-0" lengths with pre-punched holes for quicker installation and lower labor cost.
- Slotted fastening holes to allow for proper thermal movement of the materials and ensure correct fastener placement and spacing.
- Factory fabricated miters and accessories provide a cleaner appearance and eliminates field fabrication, providing time and labor savings.
- Additional accessories included are:
  - Formed cleat
  - Stainless steel springs
  - Lap joint or splice plate depending on cover material
  - All required fasteners

#### **APPLICATION INSTRUCTIONS**

See PolyForza One Extended Fascia Installation Instructions.

#### **MANUFACTURING FACILITIES**

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Waco, TX
- Winter Haven, FL

#### **CORPORATE HEADQUARTERS**

Polyglass U.S.A., Inc. 1111 West Newport Center Drive Deerfield Beach, FL 33442 www.polyglass.us

General Line: (888) 410-1375

(954) 233-1330

Customer Service: (800) 222-9782 Technical Service: (866) 794-9659

Questions? technical@polyglass.com

**Product Disclaimer:** Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects that result in the material not complying with product specifications for a period of 1 year.

All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.

Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control. For most current product data and warranty information, visit www.polyglass.us



#### **PRODUCT DATA**

#### Materials

- 22 ga. steel
- 0.050" aluminum
- 0.063" aluminum

#### **Extended Sizes**

- 9.5"
- ]]"
- 12.5"

#### APPLICABLE STANDARDS

- ANSI/SPRI/FM 4435/ES-1 Standard
- FM Approved
- Miami-Dade County Approved





### **AVAILABLE COLORS**

Choose from over 30 colors and finishes, see color chart for color options.

