

POLYFORZA™ ONE FASCIA

FLASHLESS FASCIA FOR BUR/MODIFIED SYSTEMS

PRODUCT DESCRIPTION

PolyForza One Fascia offers a convenient and economical way to protect and enhance the appearance of the roof edge. PolyForza One Fascia for BUR or modified roofs protects against high wind events, saving the building from costly damage. The design eliminates the stripping in typical of other products, making it fast and easy to install.

FEATURES AND BENEFITS

- Snap-on cover with extruded aluminum bar for secure membrane termination and easy installation.
- Provided in 12'-0" lengths with pre-punched holes for quicker installation and lower labor cost.
- Slotted fastening holes to allow for proper thermal movement of the materials and ensure correct fastener placement and spacing.
- Factory fabricated miters and accessories provide a cleaner appearance and eliminates field fabrication, providing time and labor savings.
- Additional accessories included are:
 - Formed cleat
 - Stainless steel springs
 - Lap joint or splice plate depending on cover material
 - All required fasteners

APPLICATION INSTRUCTIONS

See PolyForza One Fascia Installation Instructions.

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Waco, TX
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.
1111 West Newport Center Drive
Deerfield Beach, FL 33442
www.polyglass.us

General Line: (888) 410-1375
(954) 233-1330

Customer Service: (800) 222-9782


Technical Service: (866) 794-9659

Questions? technical@polyglass.com

Product Disclaimer: Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects that result in the material not complying with product specifications for a period of 1 year.

All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.

Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control. For most current product data and warranty information, visit www.polyglass.us



PRODUCT DATA

Materials

- 24 ga. steel
- 22 ga. steel
- 0.040" aluminum
- 0.050" aluminum
- 0.063" aluminum

Standard Sizes

- 5"
- 6.5"
- 8"

APPLICABLE STANDARDS

- ANSI/SPRI/FM 4435/ES-1 Standard
- FM Approved
- Miami-Dade County Approved

*In 24 ga. Steel, 22 ga. Steel, and 0.040" Aluminum



AVAILABLE COLORS

Choose from over 30 colors and finishes, see color chart for color options.



www.polyglass.us