POLYSTICK® TU PLUS

UYGLASS

STICK TU PLUS

POL TU

Tile Un

Self-Adhered Reinforced Wind & Water Tile Underlayment



Now with 360 Days Exposure!



Proven track record since 2005!

tade in Florida for Florida, and has been tested by nature in Florida since 2005. Just ask (hurricanes) Frances, Ivan, Wilma, Irma, and Ian about Polystick TU PLUS proven High Wind Performance up to -255 psf!

Approvals	Polystick [®] TU PLUS	Competitor A	Competitor B	Competitor C	Competitor D
FBC Non-HVHZ Product Approval	1	<i>√</i>	<i>√</i>	<i>√</i>	1
FBC HVHZ Product Approval	\checkmark		✓	✓	
Miami-Dade NOA	1		<i>✓</i>	1	1
FRSA/TRI 09-18	\checkmark	5	<i>✓</i>	<i>✓</i>	1
ASTM D1970	1	1	<i>✓</i>	1	1
TAS 103	\checkmark		<i>✓</i>	<i>✓</i>	1
Exposure	360 Days*	360 Days	180 Days	180 Days	180 Days
Use with Foam Adhered Tile	1		1	1	1
Use with Mechanically Fastened Tile	1	<i>√</i>	1	1	1
Use with Asphalt Shingles	1	5	1	1	
Use with Metal Panels/Shingles	1	1	<i>✓</i>	1	1
Use with Slate or Slate-Type Shingles	1	1	1	1	
Use with Wood Shingles or Shakes	1	1	1	1	
Approved over Structural Concrete	1	<i>✓</i>	1	1	
Approved over Insulation	1				
Approved over Base Sheet	1		<i>✓</i>	<i>✓</i>	
Direct-to-Deck – MDP (plywood)	-165 psf	-45 psf	-135 psf	-142.5 psf	-142.5 psf
Direct-to-Deck – MDP (plywood) – WITH PRIMER	-255 psf	n/a	n/a	-210 psf	n/a
Direct-to-Deck – MDP (OSB)	-52.5 psf	n/a	-52.5 psf	-45 psf	n/a
Direct-to-Deck – MDP (concrete)	-315 psf	n/a	-45 psf	-120 psf	n/a
2-Ply System – MDP (plywood)	-202.5 psf	n/a	n/a	n/a	n/a
2-Ply System – MDP (concrete)	-315 psf	n/a	n/a	-120 psf	n/a
Over M/A Base Sheet – MDP ²	-127.5 psf	n/a	n/a	n/a	n/a

*Approved as part of a multi-ply system with mechanically fastened prepared roof coverings only. Tile applications only.

All Polystick underlayments meet or exceed industry code approvals, and Polystick TU PLUS features up to 12 month exposure (mechanically attached roof covering). Up to 6 month exposure (adhesive set roof covering). Refer to local codes, listings, or requirements of the AHJ. Codes supersede Polyglass requirements and recommendations. Florida Building Code Approval for exposure beyond 6 months is pending.



For more information, contact your Polyglass Sales Representative

POLYSTICK® TU PLUS

Self-Adhered Reinforced Wind & Water Tile Underlayment



Equivalent to 287,000 buildings protected since 2005 and counting

But wait, there's more... We make it, We warrant it, Up to 30 Years!















30 Year Warranty

Florida Made

Water Resistant

High Temperature

High-Wind Performance

Membrane

Why Use Polyglass Polystick Self-Adhered Underlayments?

When selecting a roof assembly to install, a Polyglass roof underlayment can play a critical role in the performance of the roof system. Provide your customers with the most technically advanced and time and weather tested underlayment products on the market.

- ADESO[®] Self-Adhered Dual-Compound Technology
- Split-release film/paper for ease of installation
- Nail seal-ability
- Patented SEALLap[®] on select underlayments, a factory-applied adhesive treatment along the side lap
- Surfaces engineered for superior slip resistance and long-term performance
- Warranty up to 30 years
- Safe: no flames, fumes or odors
- Increased labor efficiency and roof dry-in speed

Service & Support

Polyglass provides service and support when you need it. Our team of experts assist customers from concept to completion with each phase of the project. We provide consistent communication and technical support, to expedite the process, keeping your projects on time and on budget.

14 Florida sales representatives 4 Florida technical representatives

DON'T FORGET! PolyFlash® 1C, PolyPlus® 50 and PG 500 Accessories

DOUBLE POINTS good through March 31, 2023

polyglass.us

STAY CONNECTED f 🎔 🛈 in 🕨