

Safety Data Sheet

POLYGLASS PMMA LIGHT TRAFFIC SMOOTH (LTS) SURFACE FINISH

Safety Data Sheet dated: 03/15/2023 - version 3

Date of first edition: 10/14/2022



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: POLYGLASS PMMA LIGHT TRAFFIC SMOOTH (LTS) SURFACE FINISH

Trade code: 906BESTEX

Recommended use of the chemical and restrictions on use

Recommended use: Coating

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flammable Liquids — Category 2

Highly flammable liquid and vapour.

Skin irritation, Category 2

Causes skin irritation.

Skin Sensitization, Category 1B

May cause an allergic skin reaction.

Specific target organ toxicity following single exposure, Category 3

May cause respiratory irritation.

Acute aquatic hazard, category 3

Harmful to aquatic life

Label elements

Pictograms and Signal Words



Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H402 Harmful to aquatic life

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272	Contaminated work clothing must not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a doctor if you feel unwell.
P321	Specific treatment (see supplementary instructions on this label)
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
25-50 %	methyl methacrylate; methyl 2-methylprop-2-enoate	CAS:80-62-6 EC:201-297-1 Index:607-035-00-6	Flam. Liq. 2, H225; STOT SE 3, H335; Skin Irrit. 2, H315; Skin Sens. 1, H317	
10-20 %	2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester	CAS:103-11-7 EC:203-080-7 Index:607-107-00-7	Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335; Aquatic Chronic 3, H412; Flam. Liq. 4, H227; Aquatic Acute 2, H401	
5-10 %	titanium dioxide; Dioxotitanium	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	Carc. 2, H351	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Opened containers must be carefully resealed and kept upright to prevent leakage.

Flammable mixtures may accumulate within the headspace of containers at room temperature.

Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.

Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.

Avoid accumulating electrostatic charge.
 Keep away from food, drink and feed.
 Electrical installations / working materials must comply with the technological safety standards.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Temperature of storage facilities must be adequately monitored to avoid hazardous conditions.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
methyl methacrylate; methyl 2-methylprop-2-enoate CAS: 80-62-6	OSHA		Long Term: 410 mg/m ³ - 100 ppm
	ACGIH		Long Term: 50 ppm; Short Term: 100 ppm A4 - Not Classifiable as a Human Carcinogen; body weight effects; eye and upper respiratory tract irritation; pulmonary edema; Sensitizer;
	EU		Long Term: 50 ppm; Short Term: 100 ppm Behaviour Indicative
	MAK ACGIH	GERMANY	Long Term: 210 mg/m ³ - 50 ppm Long Term: 50 ppm; Short Term: 100 ppm A4 - Not Classifiable as a Human Carcinogen; body weight effects; eye and upper respiratory tract irritation; pulmonary edema; dermal sensitizer
	MAK MAK	AUSTRIA SWITZERLAND	Long Term: 210 mg/m ³ - 50 ppm; Short Term: 420 mg/m ³ - 100 ppm Long Term: 210 mg/m ³ - 50 ppm
2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester CAS: 103-11-7	MAK	GERMANY	Long Term: 38 mg/m ³ - 5 ppm
	MAK MAK	AUSTRIA SWITZERLAND	Long Term: 82 mg/m ³ - 10 ppm; Short Term: 82 mg/m ³ - 10 ppm Long Term: 38 mg/m ³ - 5 ppm
	MAK	AUSTRIA	Ceiling - Short Term: 82 mg/m ³ - 10 ppm
	OSHA		Long Term: 15 mg/m ³
titanium dioxide; Dioxotitanium CAS: 13463-67-7	ACGIH		Long Term: 10 mg/m ³ A4 - Not Classifiable as a Human Carcinogen; lower respiratory tract irritation;
	MAK ACGIH	GERMANY	Long Term: 0.3 mg/m ³ Long Term: 10 mg/m ³ A4 - Not Classifiable as a Human Carcinogen; lower respiratory tract irritation
	MAK	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³
	MAK	SWITZERLAND	Long Term: 3 mg/m ³

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid various

Odour: Like: Ester

Odour threshold: Not Relevant

pH: Not Relevant

Melting point / freezing point: Not Relevant

Initial boiling point and boiling range: 101 °C (214 °F)

Flash point: 13 °C (55 °F)

Evaporation rate: Not Relevant

Upper/lower flammability or explosive limits: Not Relevant

Vapour density: Not Relevant

Vapour pressure: 38.70 (kPa 50°C) hPa (29 mm Hg) (MMA)

Relative density: 1.04 g/cm³

Solubility in water: immiscible

Solubility in oil: Not Relevant

Partition coefficient (n-octanol/water): Not Relevant

Auto-ignition temperature: Not Relevant

Decomposition temperature: Not Relevant

Viscosity: No data available

Kinematic viscosity: > 20,5 mm²/sec (40 °C) mm²/s

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Solid/gas flammability: Not Relevant

Other information

Substance Groups relevant properties Not Relevant

Miscibility: Not Relevant

Fat Solubility: Not Relevant

Conductivity: Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin irritation, Category 2(H315)
c) serious eye damage/irritation	Not classified Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1B(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	The product is classified: Specific target organ toxicity following single exposure, Category 3(H335)
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

methyl methacrylate; a) acute toxicity LC50 Inhalation Rat = 4632 ppm 4h
methyl 2-methylprop-2-enoate

LD50 Skin Rabbit 5000 mg/kg
LC50 Inhalation Rat = 7093 ppm 4h
LD50 Oral Rat 8420 mg/kg

2-ethylhexyl acrylate; 2- a) acute toxicity LD50 Skin Rabbit = 7522 mg/kg
Propenoic acid, 2-ethylhexyl ester

LD50 Oral Rat = 4435 mg/kg
LC50 Inhalation Rat > 1.19 mg/l 8h

titanium dioxide; a) acute toxicity LD50 Oral Rat > 10000 mg/kg
Dioxotitanium

Substance(s) listed on the IARC Monographs:

methyl methacrylate; methyl 2- methylprop-2-enoate Group 3

2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester Group 2B

titanium dioxide; Dioxotitanium Group 2B

Substance(s) listed as OSHA Carcinogen(s):

2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester
titanium dioxide; Dioxotitanium

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide; Dioxotitanium

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 3(H402)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
methyl methacrylate; methyl 2-methylprop-2-enoate	CAS: 80-62-6 - EINECS: 201-297-1 - INDEX: 607-035-00-6	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 243 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 170 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss > 79 mg/L 96h IUCLID
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 69 mg/L 48h IUCLID
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 170 mg/L 96h IUCLID
		a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 125.5 mg/L 96h EPA
2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester	CAS: 103-11-7 - EINECS: 203-080-7 - INDEX: 607-107-00-7	a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 153.9 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata 326.4 mg/L 96h EPA
		a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 44 mg/L 72h IUCLID
		a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 47 mg/L 96h IUCLID
		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 1.81 mg/L 96h ECHA
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 17.45 mg/L 48h IUCLID

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN1263
ADR-UN number: 1263
IATA-Un number: 1263
IMDG-Un number: 1263

UN proper shipping name

DOT-Proper Shipping Name: PAINT
ADR-Shipping Name: PAINT
IATA-Technical name: PAINT
IMDG-Technical name: PAINT

Transport hazard class(es)

DOT-Hazard Class: 3
ADR-Class: 3
IATA-Class: 3
IMDG-Class: 3

Packing group

DOT-Packing group: III
ADR-Packing Group: III
IATA-Packing group: III
IMDG-Packing group: III

Environmental hazards

Marine pollutant: No
Environmental Pollutant: Not Applicable
DOT-RQ: Not Applicable

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 367, B1, B52, B131, IB3, T2, TP1, TP29
DOT-Label(s): 3
DOT-Symbol: N/A
DOT-Cargo Aircraft: N/A
DOT-Passenger Aircraft: N/A
DOT-Bulk: N/A
DOT-Non-Bulk: N/A

Road and Rail (ADR-RID):

ADR-Label: 3
ADR-Hazard identification number: -
ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366
IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3L
IATA-Special Provisions: A3 A72 A192

Sea (IMDG):

IMDG-Stowage Code: Category A
IMDG-Stowage Note: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisions: 163 223 367 955
IMDG-Page: N/A
IMDG-Label: N/A

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

methyl methacrylate; methyl 2- is listed in TSCA Section 8b
methylprop-2-enoate

2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester is listed in TSCA Section 8b Section 5

titanium dioxide; Dioxotitanium is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

methyl methacrylate; methyl 2-methylprop-2-enoate

Section 313 - Toxic chemical list:

methyl methacrylate; methyl 2-methylprop-2-enoate

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

methyl methacrylate; methyl 2- Reportable quantity: 1000 pounds
methylprop-2-enoate

CAA - Clean Air Act

CAA listed substances:

methyl methacrylate; methyl 2- is listed in CAA Section 112(b) - HAP Section 112(b) - HON
methylprop-2-enoate

2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester is listed in CAA Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

methyl methacrylate; methyl 2- is listed in CWA Section 311
methylprop-2-enoate

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester Listed as carcinogen

titanium dioxide; Dioxotitanium Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

methyl methacrylate; methyl 2-methylprop-2-enoate

2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester

titanium dioxide; Dioxotitanium

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

methyl methacrylate; methyl 2-methylprop-2-enoate

2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester

titanium dioxide; Dioxotitanium

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

methyl methacrylate; methyl 2-methylprop-2-enoate

2-ethylhexyl acrylate; 2-Propenoic acid, 2-ethylhexyl ester

titanium dioxide; Dioxotitanium

Canada - Federal regulations

DSL - Domestic Substances List

DSL (Domestic Substances List)

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL (Non Domestic Substances List)

No substances listed

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 3/15/2023 - version 3

Additional classification information

NFPA Health: 2 = Moderate

NFPA Flammability: 3 = Flammable liquid

NFPA Reactivity: 2 = Moderate

NFPA Special Risk: N.A.

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.



Code	Description
H225	Highly flammable liquid and vapour.
H227	Combustible liquid
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H401	Toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
B.6/2	Flam. Liq. 2	Flammable Liquids — Category 2
B.6/4	Flam. Liq. 4	Flammable Liquids — Category 4
US-HAE/A2	Aquatic Acute 2	Acute aquatic hazard, category 2
US-HAE/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION