

GENERAL NOTATIONS:

1. Polyglass details may exceed the minimum standards required by Code, always refer/comply with applicable Code of the Authority Having Jurisdiction (AHJ).
2. For a list of approved substrates please see the Technical Bulletin at Suitable Substrates (Make this the link <https://polyglass.us/wp-content/uploads/2018/12/Technical-Bulletin-2012-02-Suitable-SA-Substrates.pdf>) at www.polyglass.us.
3. Polystick underlayment's to be back-nailed at slopes 2/12" or greater, or as otherwise required by local Building Code. Be sure that all nails are covered by the overlapping sheet.
4. Any exposed areas of non-mineral surfaced underlayment's needs to be protected from UV exposure. Consult a local Technical Representative for more information at technical@polyglass.com.
5. Do not apply Polystick underlayment's direct to shingles or other roof coverings.
6. Apply Polyglass underlayment's only when weather is dry and material interface temperatures (air, roof deck, and membrane) are 40°F and rising.
7. Overlap side-laps a minimum 3" and endlaps a minimum 6".
8. Remove all release films before completing installation.
9. If full roof coverage application is desired, proper venting of the structure is required. Consult a design professional for proper venting requirements.
10. Polystick underlayment's exposure limits vary, refer to www.polyglass.us and locate the product being installed to determine exposure limitations unless otherwise limited by local authorities.
11. Apply a minimum 6" uniform bed of modified roof cement (i.e., PolyPlus 50 or PG 500) between the underlayment layers to seal all end laps, hip and ridge details, and any "Self-Adhered compound to fabric" splices, patches or details.
12. Apply primer (i.e., PG100 or WB3000) on all metal flashing detail work, such as edge metal, lead flashings, vents, as well as concrete, and other similar roof accessories.



polyglass.us

1111 West Newport Center Drive
Deerfield Beach, FL 33442
Technical Service: (866) 794-9659
technical@polyglass.com

Description:

GENERAL INSTALLATION NOTES

Number:

PG-SS-INS-01

Revision Date:

071723