

Safety Data Sheet
VERTIWRAP NPL LT

Safety Data Sheet dated: 10/02/2023 - version 2

Date of first edition: 05/16/2023

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: VERTIWRAP NPL LT

Trade code: PLY0125

Recommended use of the chemical and restrictions on use

Recommended use: Paint

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flammable Liquids — Category 2

Highly flammable liquid and vapour.

Skin irritation, Category 2

Causes skin irritation.

Reproductive toxicity, Category 2

Suspected of damaging fertility or the unborn child if inhaled, in contact with skin and if swallowed.

Specific target organ toxicity following repeated exposure, Category 2

May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Acute aquatic hazard, category 3

Harmful to aquatic life

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H361 Suspected of damaging fertility or the unborn child if inhaled, in contact with skin and if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

H402 Harmful to aquatic life

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

- P243 Take precautionary measures against static discharge.
- P260 Do not breathe mist/vapours/spray.
- P264 Wash skin thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment (see supplementary instructions on this label)
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
25-50 %	o-xylene	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	01-2119488216-32-XXXX
5-10 %	ethylbenzene	CAS:100-41-4 EC:202-849-4 Index:601-023-00-4	Flam. Liq. 2, H225; Acute Tox. 4, H332; STOT RE 2, H373; Asp. Tox. 1, H304	
5-10 %	toluene	CAS:108-88-3 EC:203-625-9 Index:601-021-00-3	Flam. Liq. 2, H225; Asp. Tox. 1, H304; STOT RE 2, H373; Skin Irrit. 2, H315; STOT SE 3, H336; Repr. 2, H361; Aquatic Chronic 3, H412; Aquatic Acute 2, H401	01-2119471310-51-XXXX
1-2.5 %	propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate	CAS:108-65-6 EC:203-603-9 Index:607-195-00-7	Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H336	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

store in a tightly closed container in a cool, dry, well-ventilated area.

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Opened containers must be carefully resealed and kept upright to prevent leakage.
 Flammable mixtures may accumulate within the headspace of containers at room temperature.
 Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.
 Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.
 Avoid accumulating electrostatic charge.
 Keep away from food, drink and feed.
 Electrical installations / working materials must comply with the technological safety standards.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Temperature of storage facilities must be adequately monitored to avoid hazardous conditions.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.
 Safety electric system.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
o-xylene CAS: 1330-20-7	MAK	GERMANY	Long Term: 220 mg/m ³ - 50 ppm
	OSHA		Long Term: 435 mg/m ³ - 100 ppm
	ACGIH		Long Term: 100 ppm; Short Term: 150 ppm A4 - Not Classifiable as a Human Carcinogen; CNS impairment; eye and upper respiratory tract irritation
	MAK	AUSTRIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
	MAK	SWITZERLAND	Long Term: 435 mg/m ³ - 100 ppm
ethylbenzene CAS: 100-41-4	EU		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin (pure)
	EU		Long Term: 442 mg/m ³ - 100 ppm; Short Term: 884 mg/m ³ - 200 ppm Skin
	ACGIH		Long Term: 20 ppm A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair
	MAK	GERMANY	Long Term: 88 mg/m ³ - 20 ppm
	OSHA		Long Term: 435 mg/m ³ - 100 ppm
toluene CAS: 108-88-3	ACGIH		Long Term: 20 ppm A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans; upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment
	MAK	AUSTRIA	Long Term: 440 mg/m ³ - 100 ppm; Short Term: 880 mg/m ³ - 200 ppm
	MAK	SWITZERLAND	Long Term: 220 mg/m ³ - 50 ppm
	EU		Long Term: 442 mg/m ³ - 100 ppm; Short Term: 884 mg/m ³ - 200 ppm Behaviour Indicative Possibility of significant uptake through the skin
	EU		Long Term: 192 mg/m ³ - 50 ppm; Short Term: 384 mg/m ³ - 100 ppm Skin
toluene CAS: 108-88-3	ACGIH		Long Term: 20 ppm A4, BEI - Visual impair, female repro, pregnancy loss
	MAK	GERMANY	Long Term: 190 mg/m ³ - 50 ppm
	OSHA		Long Term: 200 ppm

ACGIH		Long Term: 20 ppm A4 - Not Classifiable as a Human Carcinogen;female reproductive damage;pregnancy loss;visual impairment
OSHA		Short Term: Ceiling - 300 ppm
EU		Long Term: 192 mg/m ³ - 50 ppm; Short Term: 384 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin
MAK	AUSTRIA	Long Term: 190 mg/m ³ - 50 ppm; Short Term: 380 mg/m ³ - 100 ppm
MAK	SWITZERLAND	Long Term: 190 mg/m ³ - 50 ppm
	D	
propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate CAS: 108-65-6	EU	Long Term: 275 mg/m ³ - 50 ppm; Short Term: 550 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin;
	MAK	GERMANY Long Term: 270 mg/m ³ - 50 ppm
	MAK	AUSTRIA Long Term: 275 mg/m ³ - 50 ppm; Short Term: 550 mg/m ³ - 100 ppm
	MAK	SWITZERLAND Long Term: 275 mg/m ³ - 50 ppm
	D	
	EU	Long Term: 275 mg/m ³ - 50 ppm; Short Term: 550 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin

Biological limit values

o-xylene CAS: 1330-20-7	Biological Indicator: Methyl uric Acid; Sampling Period: End of turn Value: 1.5 GGCREAT; Medium: Urine
ethylbenzene CAS: 100-41-4	Biological Indicator: Mandelic acid and fenilgliossalico; Sampling Period: End of turn Value: 0.15 GGCREAT; Medium: Urine Remark: Not Specific
toluene CAS: 108-88-3	Biological Indicator: Toluene; Sampling Period: Before last turn of the working week Value: 0.02 mg/L; Medium: Blood
	Biological Indicator: Toluene; Sampling Period: End of turn Value: 0.03 mg/L; Medium: Urine
	Biological Indicator: O-Cresol; Sampling Period: End of turn Value: 0.3 MGGCREAT; Medium: Urine Remark: Background

Predicted No Effect Concentration (PNEC) values

toluene CAS: 108-88-3	Exposure Route: Freshwater sediments Remark: PNEC
	Exposure Route: Soil Remark: PNEC
	Exposure Route: Marine water sediments Remark: PNEC
	Exposure Route: Fresh Water Remark: PNEC
	Exposure Route: Marine water Remark: PNEC
	Exposure Route: Intermittent release Remark: PNEC
	Exposure Route: Microorganisms in sewage treatments

Derived No Effect Level (DNEL) values

toluene CAS: 108-88-3	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Industry: 384 mg/m ³ ; Consumer: 226 mg/kg
	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Worker Industry: 192 mg/m ³
	Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Consumer: 226 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 384 mg/m³

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid Dark grey

Odour: hydrocarbons like

Odour threshold: Not Relevant

pH: Not Relevant

Melting point / freezing point: Not Relevant

Initial boiling point and boiling range: 103.3 °C (217.9 °F)

Flash point: 4.4 °C (39.9 °F)

Evaporation rate: Not Relevant

Upper/lower flammability or explosive limits: Not Relevant

Vapour density: Not Relevant

Vapour pressure: Not Relevant

Relative density: Not Relevant

Solubility in water: Not Relevant

Solubility in oil: Not Relevant

Partition coefficient (n-octanol/water): Not Relevant

Auto-ignition temperature: Not Relevant

Decomposition temperature: Not Relevant

Viscosity: Not Relevant

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Solid/gas flammability: Not Relevant

Other information

Substance Groups relevant properties Not Relevant

Miscibility: Not Relevant

Fat Solubility: Not Relevant

Conductivity: Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

Stable

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Heat and open flames.

Avoid accumulating electrostatic charge.

Incompatible materials

Oxidizers

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin irritation, Category 2(H315)
c) serious eye damage/irritation	Not classified
	Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	Not classified
	Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Reproductive toxicity, Category 2(H361)
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	The product is classified: Specific target organ toxicity following repeated exposure, Category 2(H373)
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

o-xylene	a) acute toxicity	LD50 Skin Rabbit > 4350 mg/kg LC50 Inhalation Rat = 29.08 mg/l 4h LD50 Oral Rat = 3500 mg/kg
ethylbenzene	a) acute toxicity	LD50 Skin Rabbit = 5000 mg/kg LD50 Oral Rat = 3500 mg/kg LC50 Inhalation Rat = 17.4 mg/l 4h
toluene	a) acute toxicity	LD50 Oral Rat = 5580 mg/kg LD50 Skin Rabbit = 12124 mg/kg LC50 Inhalation Rat = 12.5 mg/l 4h
	g) reproductive toxicity	NOAEC Rat = 1200 ppm NOAEL Rat = 2000 ppm
propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate	a) acute toxicity	LD50 Skin Rabbit > 5 g/kg LD50 Oral Rat = 8532 mg/kg LD50 Skin Rabbit > 5 g/kg

Substance(s) listed on the IARC Monographs:

o-xylene	Group 3
ethylbenzene	Group 2B

Substance(s) listed as OSHA Carcinogen(s):

ethylbenzene

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION**Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 3(H402)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
o-xylene	CAS: 1330-20-7 - EINECS: 215-535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 13.4 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 2.661 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 13.5 mg/L 96h IUCLID
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 13.1 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 19 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 7.711 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 23.53 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 780 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio > 780 mg/L 96h IUCLID
		a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata 30.26 mg/L 96h EPA
toluene	CAS: 108-88-3 - EINECS: 203-625-9 - INDEX: 601-021-00-3	a) Aquatic acute toxicity : EC50 Daphnia water flea = 3.82 mg/L 48h
		a) Aquatic acute toxicity : LC50 Daphnia Gammarus lacustris = 0.6 mg/L 48h
		a) Aquatic acute toxicity : EC50 Algae = 134 mg/L 3
		a) Aquatic acute toxicity : LC50 Fish = 5.5 mg/L 96h EPA
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 5.46 mg/L 48h EPA
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata > 433 mg/L 96h IUCLID
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 12.5 mg/L 72h EPA
		b) Aquatic chronic toxicity : NOEC Daphnia = 0.74 mg/L - 7 days
		a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 161 mg/L 96h IUCLID
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna > 500 mg/L 48h IUCLID
propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate	CAS: 108-65-6 - EINECS: 203-603-9 - INDEX: 607-195-00-7	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 161 mg/L 96h IUCLID
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna > 500 mg/L 48h IUCLID

Persistence and degradability**Component****Persistance/Degradability:**

toluene

Readily biodegradable

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN1993

ADR-UN number: 1993

IATA-Un number: 1993

IMDG-Un number: 1993

UN proper shipping name

DOT-Proper Shipping Name: Flammable liquids, n.o.s. (ethylbenzene - toluene)

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (vapour pressure at 50 °C more than 110 kPa) (ethylbenzene - toluene)

IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (ethylbenzene - toluene)

IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (ethylbenzene - toluene)

Transport hazard class(es)

DOT-Hazard Class: 3

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

Packing group

DOT Packing Group: II

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: Yes DOT-RQ - Quantity: 100 lbs

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): IB2, T7, TP1, TP8, TP28

DOT-Label(s): 3
DOT-Symbol: N/A
DOT-Cargo Aircraft: N/A
DOT-Passenger Aircraft: N/A
DOT-Bulk: N/A
DOT-Non-Bulk: N/A

Road and Rail (ADR-RID):

ADR-Label: 3
ADR-Hazard identification number: 33
ADR-Transport category (Tunnel restriction code): 2 (D/E)

Air (IATA):

IATA-Passenger Aircraft: 353
IATA-Cargo Aircraft: 364
IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3H
IATA-Special Provisions: A3

Sea (IMDG):

IMDG-Stowage Code: Category B
IMDG-Stowage Note: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisions: 274
IMDG-EMS: F-E, S-E

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

o-xylene	is listed in TSCA	Section 8b
ethylbenzene	is listed in TSCA	Section 8b
toluene	is listed in TSCA	Section 8b
propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate	is listed in TSCA	Section 8b Section 8a - PAIR

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

o-xylene
ethylbenzene
toluene

Section 313 - Toxic chemical list:

o-xylene
ethylbenzene
toluene

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

o-xylene	Reportable quantity:	100	pounds
ethylbenzene	Reportable quantity:	1000	pounds
toluene	Reportable quantity:	1000	pounds

CAA - Clean Air Act

CAA listed substances:

o-xylene	is listed in CAA	Section 112(b) - HAP	Section 112(b) - HON
ethylbenzene	is listed in CAA	Section 112(b) - HAP	Section 112(b) - HON

toluene is listed in CAA Section 112(b) - HAP Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

o-xylene is listed in CWA Section 311
ethylbenzene is listed in CWA Section 307 Section 311
toluene is listed in CWA Section 307 Section 311

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

ethylbenzene Listed as carcinogen
toluene Listed as reproductive toxicant

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

o-xylene
ethylbenzene
toluene

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

o-xylene
ethylbenzene
toluene

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

o-xylene
ethylbenzene
toluene

Canada - Federal regulations

DSL - Domestic Substances List

Not compliant to DSL inventory

NDSL - Non Domestic Substances List

Not compliant to NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 10/2/2023 - version 2

Additional classification information

NFPA Health: 1 = Slight
NFPA Flammability: 4 = Flammable gas or extremely flammable liquid
NFPA Reactivity: 1 = Slight
NFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.7/2	Repr. 2	Reproductive toxicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2
B.6/2	Flam. Liq. 2	Flammable Liquids — Category 2
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3
US-HAE/A2	Aquatic Acute 2	Acute aquatic hazard, category 2
US-HAE/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Legend to abbreviations and acronyms used in the safety data sheet:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
- IMDG: International Maritime Code for Dangerous Goods.
- IATA: International Air Transport Association.
- IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
- ICAO: International Civil Aviation Organization.
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- CLP: Classification, Labeling, Packaging.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- INCI: International Nomenclature of Cosmetic Ingredients.
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- GefStoffVO: Ordinance on Hazardous Substances, Germany.
- LC50: Lethal concentration, for 50 percent of test population.
- LD50: Lethal dose, for 50 percent of test population.
- DNEL: Derived No Effect Level.
- PNEC: Predicted No Effect Concentration.
- TLV: Threshold Limiting Value.
- TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
- STEL: Short Term Exposure limit.
- STOT: Specific Target Organ Toxicity.
- WGK: German Water Hazard Class.
- KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION