

SURFACE COAT POLYBRITE 90 OR POLYBRITE 95, SILICONE BASED ROOF COATING. APPLY ACCORDING TO SPECIFICATION.

BASE COAT

POLYBRITE 90 OR POLYBRITE 95, SILICONE BASED ROOF COATING. APPLY ACCORDING TO SPECIFICATION.

POLYBRITE 90 OR POLYBRITE 95, USING POLYBRITE REINFORCING POLYESTER. THREE COURSING.

FLASHING COMPOUND
 POLYBRITE 90 OR POLYBRITE 95 MIXED IN WITH FMT (MICROFIBER) MIXED
IN WITH HAND TOOLS AT THE RATIO OF 20% - 30%.

• SURFACE PREPARATION POWER WASH ROOF SURFACE USING CLEANING DETERGENT, MAKE SURE TO RINSE OFF. APPLY PRIMERS ACCORDING TO SPECIFICATION.

POLYGLASS

GROUP

polyglass.us

1111 West Newport Center Drive Deerfield Beach, FL 33442 Technical Service: (866) 794-9659 technical@polyglass.com

Description:

TYPICAL ROOF CANT (AT CORNER) FLASHING DETAIL

NOT DRAWN TO SCALE

Number: PG-RFD Effective Date: 082324