



Florida Product Approval No.
 FL5259 - Latest Revision

SYSTEM DESCRIPTION				
DECK THICKNESS	BASE SHEET	UNDERLAYMENT	FASTENER	NOTES
1 ⁵ / ₃₂ inch min.	Polyanchor HV	Polystick UV Max	Cap Nail	Non-HVHZ

FASTENER LAYOUT					
NO. OF FIELD ROWS	LAP WIDTH	FASTENER SPACING FIELD	PASSING WIND UPLIFT	MDP	FASTENERS PER SQUARE
3	2 inch	6 inch	75 psf	37.5 psf	257

NOTES:

- Above pattern is a genetic layout and not project specific.
- Polyglass approved fasteners only to be used.
- Refer to Polyglass website www.Polyglass.us for specific product limitations and installation guidelines.
- Refer to any local Building Codes regarding limitations of specific applications.
- Local Codes or requirements of the AHJ supercede Polyglass Requirements and Recommendations.

POLYGLASS



polyglass.us

1111 West Newport Center Drive
 Deerfield Beach, FL 33442
 Technical Service: (866) 794-9659
technical@polyglass.com

Description: POLYANCHOR FASTENING
 PATTERN #2
 257 FASTENERS PER SQUARE

NOT DRAWN TO SCALE

Number: PG-LS-FP-PA-2

Effective Date: 102324