



**Florida Product Approval No.**  
FL5259 - Latest Revision

SYSTEM DESCRIPTION				
DECK THICKNESS	BASE SHEET	UNDERLAYMENT	FASTENER	NOTES
1 <sup>5</sup> / <sub>32</sub> inch min.	Polyanchor HV	Polystick UV Max	Tin Cap & Nails	

FASTENER LAYOUT					
NO. OF FIELD ROWS	LAP WIDTH	FASTENER SPACING FIELD	PASSING WIND UPLIFT	MDP	FASTENERS PER SQUARE
8	4 inch	24 inch	150 psf	75 psf	153

**NOTES:**

- Above pattern is a genetic layout and not project specific.
- Polyglass approved fasteners only to be used.
- Refer to Polyglass website [www.Polyglass.us](http://www.Polyglass.us) for specific product limitations and installation guidelines.
- Refer to any local Building Codes regarding limitations of specific applications.
- Local Codes or requirements of the AHJ supercede Polyglass Requirements and Recommendations.

**POLYGLASS**



**polyglass.us**

1111 West Newport Center Drive  
Deerfield Beach, FL 33442  
Technical Service: (866) 794-9659  
technical@polyglass.com

**Description:** POLYANCHOR FASTENING  
PATTERN #23  
153 FASTENERS PER SQUARE

NOT DRAWN TO SCALE

**Number:** PG-LS-FP-PA-23

**Effective Date:** 102324