



**Florida Product Approval No.**  
 FL5259 - Latest Revision

SYSTEM DESCRIPTION				
DECK THICKNESS	BASE SHEET	UNDERLAYMENT	FASTENER	NOTES
1 <sup>9</sup> / <sub>32</sub> inch min.	Polyanchor HV	Polystick TU Max	Tin Cap & Nails ( 1 <sup>1</sup> / <sub>2</sub> " )	6" O.C in the 4" wide lap and 12" O.C in two staggered rows in field

FASTENER LAYOUT					
NO. OF FIELD ROWS	LAP WIDTH	FASTENER SPACING FIELD	PASSING WIND UPLIFT	MDP	FASTENERS PER SQUARE
2	4 inch	12 inch	90 psf	45 psf	122

**NOTES:**

- Above pattern is a genetic layout and not project specific.
- Polyglass approved fasteners only to be used.
- Refer to Polyglass website [www.Polyglass.us](http://www.Polyglass.us) for specific product limitations and installation guidelines.
- Refer to any local Building Codes regarding limitations of specific applications.
- Local Codes or requirements of the AHJ supercede Polyglass Requirements and Recommendations.

**POLYGLASS**  
  
 polyglass.us  
 1111 West Newport Center Drive  
 Deerfield Beach, FL 33442  
 Technical Service: (866) 794-9659  
 technical@polyglass.com

**Description:**

**POLYANCHOR HV  
 FASTENING PATTERN #18  
 122 FASTENERS PER SQUARE**

NOT DRAWN TO SCALE

**Number:**

PG-LS-FP-PA-18

**Effective Date:**

112224