

## Florida Product Approval No.

FL5259 - Latest Revision

SYSTEM DESCRIPTION										
DECK THICKNES	S BASE SHE	ET	UNDERLAYMENT		FASTENER		NOTES			
$^{15}\!$	Polyanchor	HV	Polystick	TU Max		Cap Nail	Non-HVHZ FBC			
FASTENER LAYOUT										
NO. OF FIELD ROWS	LAP WIDTH	FASTENER SPACING FIELD		PASSING WIND UPLIFT		MDP	FASTENERS PER SQUARE			
3	2 inch	6 inch		75 psf		37.5 psf	257			

## NOTES:

- 1. Above pattern is a genetic layout and not project specific.
- 2. Polyglass approved fasteners only to be used.
- 3. Refer to Polyglass website www.Polyglass.us for specific product limitations and installation guidelines.
- 4. Refer to any local Building Codes regarding limitations of specific applications.
- 5. Local Codes or requirements of the AHJ supercede Polyglass Requirements and Recommendations.

POLYGLASS	Description: POLYANCHOR HV						
<b>polyglass.us</b> 1111 West Newport Center Drive Deerfield Beach, FL 33442	FASTENING PATTERN #2 257 FASTENERS PER SQUARE						
Technical Service: (866) 794-9659 technical@polyglass.com	Number:	PG-LS-FP-PA-2	Effective Date:	112224			

Q:\CAD Technical Dept\Detail Drawings\Phase 1-Refresh\Fastening Patterns - Low-Slope\Polyanchor HV\CAD