



**Florida Product Approval No.**  
 FL5259 - Latest Revision

SYSTEM DESCRIPTION				
DECK THICKNESS	BASE SHEET	UNDERLAYMENT	FASTENER	NOTES
1 <sup>5</sup> / <sub>32</sub> inch min.	Polyanchor HV	Polystick TU Max	Tin Cap & Nails	Non-HVHZ and HVHZ FBC

FASTENER LAYOUT					
NO. OF FIELD ROWS	LAP WIDTH	FASTENER SPACING FIELD	PASSING WIND UPLIFT	MDP	FASTENERS PER SQUARE
4	4 inch	6 inch	165 psf	82.5 psf	339

**NOTES:**

- Above pattern is a genetic layout and not project specific.
- Polyglass approved fasteners only to be used.
- Refer to Polyglass website [www.Polyglass.us](http://www.Polyglass.us) for specific product limitations and installation guidelines.
- Refer to any local Building Codes regarding limitations of specific applications.
- Local Codes or requirements of the AHJ supercede Polyglass Requirements and Recommendations.

**POLYGLASS**



**polyglass.us**

1111 West Newport Center Drive  
 Deerfield Beach, FL 33442  
 Technical Service: (866) 794-9659  
 technical@polyglass.com

**Description:**

**POLYANCHOR HV  
 FASTENING PATTERN #33  
 339 FASTENERS PER SQUARE**

NOT DRAWN TO SCALE

**Number:**

PG-LS-FP-PA-33

**Effective Date:**

112224