



**Florida Product Approval No.**  
 FL5259 - Latest Revision

SYSTEM DESCRIPTION				
DECK THICKNESS	BASE SHEET	UNDERLAYMENT	FASTENER	NOTES
1 5/32 inch min.	Polyanchor HV	Polystick TU Max	Tin Cap & Nails	Non-HVHZ FBC

FASTENER LAYOUT					
NO. OF FIELD ROWS	LAP WIDTH	FASTENER SPACING FIELD	PASSING WIND UPLIFT	MDP	FASTENERS PER SQUARE
4	4 inch	5 inch	210 psf	105 psf	407

**NOTES:**

- Above pattern is a genetic layout and not project specific.
- Polyglass approved fasteners only to be used.
- Refer to Polyglass website [www.Polyglass.us](http://www.Polyglass.us) for specific product limitations and installation guidelines.
- Refer to any local Building Codes regarding limitations of specific applications.
- Local Codes or requirements of the AHJ supercede Polyglass Requirements and Recommendations.

**POLYGLASS**



**polyglass.us**

1111 West Newport Center Drive  
 Deerfield Beach, FL 33442  
 Technical Service: (866) 794-9659  
[technical@polyglass.com](mailto:technical@polyglass.com)

**Description:**

**POLYANCHOR HV  
 FASTENING PATTERN #5  
 407 FASTENERS PER SQUARE**

NOT DRAWN TO SCALE

**Number:**

PG-LS-FP-PA-5

**Effective Date:**

112224