

### Florida Product Approval No.

FL5259 - Latest Revision

SYSTEM DESCRIPTION							
DECK THICKNESS	DECK THICKNESS BASE SHEET UNDERLAYMENT		FASTENER	NOTES			
<sup>19</sup> / <sub>32</sub> inch min.	Polyanchor HV	Polystick TU Max	Tin Cap & Nails	Non-HVHZ FBC			

FASTENER LAYOUT							
NO. OF FIELD ROWS	LAP WIDTH	FASTENER SPACING FIELD	PASSING WIND UPLIFT	MDP	FASTENERS PER SQUARE		
3	4 inch	5 inch	240 psf	120 psf	326		

### NOTES:

- 1. Above pattern is a genetic layout and not project specific.
- 2. Polyglass approved fasteners only to be used.
- 3. Refer to Polyglass website www.Polyglass.us for specific product limitations and installation guidelines.
- 4. Refer to any local Building Codes regarding limitations of specific applications.
- 5. Local Codes or requirements of the AHJ supercede Polyglass Requirements and Recommendations.

## POLYGLASS

### polyglass.us

1111 West Newport Center Drive Deerfield Beach, FL 33442 Technical Service: (866) 794-9659 technical@polyglass.com **Description:** 

# POLYANCHOR HV FASTENING PATTERN #7 326 FASTENERS PER SQUARE

NOT DRAWN TO SCALE

Number: PG-LS-FP-PA-7 Effective Date: 112224