

Safety Data Sheet

PRIMER EP-1020 NA /B

Safety Data Sheet dated: 07/19/2024 - version 1

Date of first edition: 07/19/2024

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: PRIMER EP-1020 NA /B

Trade code: 9001969

Recommended use of the chemical and restrictions on use

Recommended use: Primer

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Acute toxicity (oral), Category 4

Skin corrosion, Category 1B

Serious eye damage, Category 1

Skin Sensitization, Category 1A

Reproductive toxicity, Category 2

Acute aquatic hazard, category 2

Chronic (long term) aquatic hazard, category 2

Acute toxicity (inhalation), Category 4

Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Toxic to aquatic life

Toxic to aquatic life with long lasting effects.

Harmful if inhaled.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H361 Suspected of damaging fertility or the unborn child.

H401 Toxic to aquatic life

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist/vapours/spray.

P264 Wash skin thoroughly after handling.

- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/clothing and eye/face protection.
- P301+P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.
- P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
- 1
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- 3
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- 8
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P310 Immediately call a POISON CENTER.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P391 Collect spillage.
- P501 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
25-50 %	benzyl alcohol; benzenemethanol	CAS:100-51-6 EC:202-859-9 Index:603-057-00-5	Acute Tox. 4, H332; Acute Tox. 4, H302; Eye Irrit. 2A, H319
25-50 %	isophorone diamine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS:2855-13-2 EC:220-666-8 Index:612-067-00-9	Acute Tox. 4, H302; Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1A, H317
10-20 %	salicylic acid; 2-Hydroxybenzoic acid	CAS:69-72-7 EC:200-712-3 Index:607-732-00-5	Acute Tox. 4, H302; Eye Dam. 1, H318; Repr. 2, H361
10-20 %	1,3-benzenedimethanamine; m-phenylenebis(methylamine)	CAS:1477-55-0 EC:216-032-5	Acute Tox. 4, H332; Acute Tox. 4, H302; Aquatic Chronic 3, H412; Aquatic Acute 3, H402; Skin Corr. 1B, H314; Skin Sens. 1B, H317
5-10 %	fatty acids, c18-unsaturated, dimers, reaction products with polyethylenepolyamines; polyethylene polyamine, dimer fatty acid condensate	CAS:1226892-45-0, 68410-23-1 EC:629-725-6	Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Corr. 1C, H314; Skin Sens. 1A, H317
2.5-5 %	phenol, styrenated; Petroleum resins	CAS:61788-44-1 EC:262-975-0	Aquatic Chronic 2, H411; Aquatic Acute 1, H400

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.
OBTAIN IMMEDIATE MEDICAL ATTENTION.
Obtain medical attention if skin related symptoms persist.
Remove contaminated clothing immediately and dispose of safely.
After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Protect uninjured eye.

In case of Ingestion:

Give nothing to eat or drink.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.
In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.
Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
Hazardous combustion products: Not available
Explosive properties: Not available
Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Use appropriate respiratory protection.
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Do not use on extensive surface areas in premises where there are occupants.
Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
benzyl alcohol; benzenemethanol CAS: 100-51-6	MAK	GERMANY	Long Term: 22 mg/m ³ - 5 ppm
	MAK	SWITZERLAND	Long Term: 22 mg/m ³ - 5 ppm
1,3-benzenedimethanamine; m-phenylenebis(methylamine) CAS: 1477-55-0	ACGIH		Short Term: Ceiling - 0.1 mg/m ³ Skin - Eye, skin, and GI irr
	ACGIH		Short Term: Ceiling - 0.1 mg/m ³
	ACGIH		Skin - potential significant contribution to overall exposure by the cutaneous route;eye, gastrointestinal and skin irritation
	MAK	AUSTRIA	Long Term: 0.1 mg/m ³ ; Short Term: 0.1 mg/m ³
	MAK	SWITZERLAND	Long Term: 0.1 mg/m ³
	MAK	AUSTRIA	Short Term: Ceiling - 0.1 mg/m ³
	ACGIH		Short Term: Ceiling - 0.1 mg/m ³
	ACGIH		Skin - potential significant contribution to overall exposure by the cutaneous route;eye, gastrointestinal and skin irritation
ACGIH		Short Term: Ceiling - 0.018 ppm	

Predicted No Effect Concentration (PNEC) values

benzyl alcohol; benzenemethanol CAS: 100-51-6	Exposure Route: Fresh Water; PNEC Limit: 1 mg/l
	Exposure Route: Marine water; PNEC Limit: 0.1 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 5.27 mg/kg
	Exposure Route: Marine water sediments; PNEC Limit: 0.527 mg/kg
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 39 mg/l
	Exposure Route: Soil; PNEC Limit: 0.45 mg/kg
isophorone diamine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2	Exposure Route: Intermittent release; PNEC Limit: 2.3 mg/l
	Exposure Route: Fresh Water; PNEC Limit: 0.06 mg/l
	Exposure Route: Marine water; PNEC Limit: 0.006 mg/l
	Exposure Route: Intermittent release; PNEC Limit: 0.23 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 5.784 mg/kg
	Exposure Route: Marine water sediments; PNEC Limit: 0.578 mg/kg
	Exposure Route: Soil; PNEC Limit: 1.121 mg/kg

salicylic acid; 2-Hydroxybenzoic acid
CAS: 69-72-7

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.18 mg/l
Exposure Route: Fresh Water; PNEC Limit: 0.2 mg/l

1,3-benzenedimethanamine; m-phenylenebis (methylamine)
CAS: 1477-55-0

Exposure Route: Intermittent release; PNEC Limit: 1 mg/l
Exposure Route: Marine water; PNEC Limit: 0.02 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 1.42 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 0.14 mg/kg
Exposure Route: Soil; PNEC Limit: 0.16 mg/kg
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 162 mg/l
Exposure Route: Fresh Water; PNEC Limit: 0.094 mg/kg

phenol, styrenated; Petroleum resins
CAS: 61788-44-1

Exposure Route: Marine water; PNEC Limit: 0.0094 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 0.43 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 0.043 mg/kg
Exposure Route: Intermittent release; PNEC Limit: 0.152 mg/l
Exposure Route: Soil; PNEC Limit: 0.045 mg/kg
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l
Exposure Route: Fresh Water; PNEC Limit: 0.001 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 65778 mg/kg
Exposure Route: Freshwater sediments; PNEC Limit: 65778 mg/kg
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 0.17 mg/l
Exposure Route: Soil; PNEC Limit: 31525 mg/kg

Derived No Effect Level (DNEL) values

benzyl alcohol; benzenemethanol
CAS: 100-51-6

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 20 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 4 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 110 mg/m³; Consumer: 27 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 22 mg/m³; Consumer: 5.4 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Industry: 40 mg/kg; Consumer: 20 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 8 mg/kg; Consumer: 4 mg/kg

isophorone diamine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine
CAS: 2855-13-2

Exposure Route: Human Inhalation
Worker Industry: 20.1 mg/m³

salicylic acid; 2-Hydroxybenzoic acid
CAS: 69-72-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 16 mg/m³; Consumer: 0.2 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 4 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 2 mg/kg; Consumer: 1 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 4 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 1 mg/kg

1,3-benzenedimethanamine;
m-phenylenebis
(methylamine)
CAS: 1477-55-0

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 0.33 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 1.2 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 0.2 mg/m³

phenol, styrenated;
Petroleum resins
CAS: 61788-44-1

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 11.02 mg/m³; Consumer: 2.717 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 6.25 mg/kg; Consumer: 3.125 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 1.562 mg/kg

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

Nitrile rubber - NBR: thickness $\geq 0,35$ mm; breakthrough time ≥ 480 min.

Butyl rubber - IIR: thickness $\geq 0,5$ mm; breakthrough time ≥ 480 min.

Fluorinated rubber - FKM: thickness $\geq 0,4$ mm; breakthrough time ≥ 480 min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid yellow

Odour: ammonia

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available

Initial boiling point and boiling range: 160 °C (320 °F)

Flash point: No data available

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available

Vapour pressure: No data available

Relative density: 1.05 g/cm³

Solubility in water: partly soluble

Solubility in oil: slightly soluble

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available

Decomposition temperature: No data available

Viscosity: 200.00 cPs

Kinematic viscosity: $> 20,5$ mm²/sec (40 °C) mm²/s

Explosive properties: No data available

Oxidizing properties: No data available
Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available
Miscibility: No data available
Fat Solubility: No data available
Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	The product is classified: Acute toxicity (oral), Category 4(H302), Acute toxicity (inhalation), Category 4(H332) ATEmix - Oral : 1293.37 mg/kg bw ATEmix - Inhalation (Vapours) : 32.5926 mg/l
b) skin corrosion/irritation	The product is classified: Skin corrosion, Category 1B(H314)
c) serious eye damage/irritation	The product is classified: Serious eye damage, Category 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1A(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Reproductive toxicity, Category 2(H361)
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

benzyl alcohol; benzenemethanol	a) acute toxicity	LD50 Oral Rat = 1620 mg/kg LC50 Inhalation Mist Rat = 4.178 mg/l 4h
	g) reproductive toxicity	NOAEL Rat = 1072 mg/m3
	a) acute toxicity	LC50 Inhalation Dust Rat > 5.01 mg/l 4h LD50 Oral Rat = 1030 mg/kg LD50 Skin Rat > 2000 mg/kg

isophorone diamine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine	a) acute toxicity	LC50 Inhalation Dust Rat > 5.01 mg/l 4h LD50 Oral Rat = 1030 mg/kg LD50 Skin Rat > 2000 mg/kg
--	-------------------	---

salicylic acid; 2-	a) acute toxicity	LC50 Inhalation Rat > 0.9 mg/l 1h
--------------------	-------------------	-----------------------------------

Hydroxybenzoic acid

LD50 Oral Rat = 891 mg/kg
LD50 Skin Rabbit > 2000 mg/kg
LD50 Skin Rat > 2 g/kg
LC50 Inhalation Rat > 900 mg/m³ 1h
LD50 Oral Rat = 891 mg/kg
LD50 Skin Rat > 2 g/kg

1,3-benzenedimethanamine;
m-phenylenebis
(methylamine)

a) acute toxicity

LD50 Oral Mouse = 930 mg/kg

LD50 Skin Rabbit = 2000 mg/kg
LC50 Inhalation Mist Rat = 1.34 mg/l 4h
LC50 Inhalation Rat = 700 ppm 1h

fatty acids, c18-unsaturated, dimers, reaction products with polyethylenepolyamines; polyethylene polyamine, dimer fatty acid condensate

a) acute toxicity

LD50 Oral Rat > 2000 mg/kg

phenol, styrenated;
Petroleum resins

a) acute toxicity

LD50 Oral Rat > 2000 mg/kg

LD50 Skin Rat > 2000 mg/kg

Substance(s) listed on the IARC Monographs:

None

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 2(H401), Chronic (long term) aquatic hazard, category 2(H411)

List of Eco-Toxicological properties of the components

Component

Ident. Numb. Ecotox Data

benzyl alcohol; benzenemethanol

CAS: 100-51-6 - a) Aquatic acute toxicity : EC50 Daphnia = 230 mg/L 48
EINECS: 202-859-9 - INDEX:
603-057-00-5

a) Aquatic acute toxicity : LC50 Fish = 770 mg/L 1
a) Aquatic acute toxicity : EC50 Algae = 770 mg/L 72
a) Aquatic acute toxicity : LC50 Fish = 460 mg/L 96
a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 460 mg/L 96h

EPA

isophorone diamine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine

CAS: 2855-13-2 a) Aquatic acute toxicity : LC50 Fish = 110 mg/L 96
- EINECS: 220-666-8 - INDEX: 612-067-00-9

- a) Aquatic acute toxicity : EC50 Daphnia = 23 mg/L 48
- a) Aquatic acute toxicity : EC50 Daphnia = 388 mg/L 48
- a) Aquatic acute toxicity : EC50 Algae > 50 mg/L 72
- b) Aquatic chronic toxicity : NOEC Daphnia = 3 mg/L - 21 d
- a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 14.6 mg/L 48h EPA
- a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 37 mg/L 72h IUCLID

salicylic acid; 2-Hydroxybenzoic acid

CAS: 69-72-7 - a) Aquatic acute toxicity : EC50 Daphnia = 870 mg/L 48
EINECS: 200-712-3 - INDEX: 607-732-00-5

- a) Aquatic acute toxicity : LC50 Fish = 90 mg/L
- a) Aquatic acute toxicity : EC50 Algae > 100 mg/L 72
- a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 870 mg/L 48h EPA

1,3-benzenedimethanamine; m-phenylenebis(methylamine)

CAS: 1477-55-0 a) Aquatic acute toxicity : EC50 Algae = 20 mg/L 72h
- EINECS: 216-032-5

- a) Aquatic acute toxicity : EC50 Daphnia = 15.2 mg/L 48h
- a) Aquatic acute toxicity : LC50 Fish Oryzias latipes = 87.6 mg/L 96h ECHA

phenol, styrenated; Petroleum resins

CAS: 61788-44-1 - EINECS: 262-975-0 a) Aquatic acute toxicity : EC50 Daphnia = 4.6 mg/L 48 ECHA

- a) Aquatic acute toxicity : LC50 Fish = 5.6 mg/L 96h ECHA

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN2735

ADR-UN number: 2735

IATA-Un number: 2735

IMDG-Un number: 2735

UN proper shipping name

DOT-Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - fatty acids, amines react. prod.)

ADR-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - fatty acids, amines react. prod.)

IATA-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - fatty acids, amines react. prod.)

IMDG-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. (isophoronediamine - fatty acids, amines react. prod.)

Transport hazard class(es)

DOT-Hazard Class: 8

ADR-Class: 8

IATA-Class: 8

IMDG-Class: 8

Packing group

DOT Packing Group: II

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: Not Applicable

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): B2, IB2, T11, TP1, TP27

DOT-Label(s): 8

DOT-Symbol: N/A

DOT-Cargo Aircraft: 30 L

DOT-Passenger Aircraft: 1 L

DOT-Bulk: 242

DOT-Non-Bulk: 202

DOT-Limited Quantity threshold: 1 L

Road and Rail (ADR-RID) :

ADR-Label: 8

ADR-Hazard identification number: 80

ADR-Transport category (Tunnel restriction code): 2 (E)

Air (IATA) :

IATA-Passenger Aircraft: 851

IATA-Cargo Aircraft: 855

IATA-Label: 8

IATA-Subsidiary hazards: -

IATA-Erg: 8L

IATA-Special Provisioning: A3 A803

Sea (IMDG) :

IMDG-Stowage Code: Category A

IMDG-Stowage Note: SG35 SGG18

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 274

IMDG-EMS: F-A, S-B

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA listed substances:

benzyl alcohol; benzenemethanol is listed in TSCA Section 8b
isophorone diamine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine is listed in TSCA Section 8b
salicylic acid; 2-Hydroxybenzoic acid is listed in TSCA Section 8b
1,3-benzenedimethanamine; m-phenylenebis(methylamine) is listed in TSCA Section 8b
phenol, styrenated; Petroleum resins is listed in TSCA Section 8a - PAIR Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

benzyl alcohol; benzenemethanol is listed in CAA Section 112(b) - HON
salicylic acid; 2-Hydroxybenzoic acid is listed in CAA Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

No substances listed

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

benzyl alcohol; benzenemethanol
1,3-benzenedimethanamine; m-phenylenebis(methylamine)

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

benzyl alcohol; benzenemethanol
1,3-benzenedimethanamine; m-phenylenebis(methylamine)

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

isophorone diamine; 3-aminomethyl-3,5,5-trimethylcyclohexylamine
1,3-benzenedimethanamine; m-phenylenebis(methylamine)

Canada - Federal regulations

DSL - Domestic Substances List

NDSL - Non Domestic Substances List

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 7/19/2024 - version 1

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child if inhaled and in contact with skin.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
A.2/1C	Skin Corr. 1C	Skin corrosion, Category 1C
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1A	Skin Sens. 1A	Skin Sensitization, Category 1A
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.7/2	Repr. 2	Reproductive toxicity, Category 2
US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
US-HAE/A3	Aquatic Acute 3	Acute aquatic hazard, category 3
US-HAE/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
US-HAE/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Legend to abbreviations and acronyms used in the safety data sheet:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
- IMDG: International Maritime Code for Dangerous Goods.
- IATA: International Air Transport Association.
- IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
- ICAO: International Civil Aviation Organization.
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- CLP: Classification, Labeling, Packaging.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- INCI: International Nomenclature of Cosmetic Ingredients.
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- GefStoffVO: Ordinance on Hazardous Substances, Germany.
- LC50: Lethal concentration, for 50 percent of test population.
- LD50: Lethal dose, for 50 percent of test population.
- DNEL: Derived No Effect Level.
- PNEC: Predicted No Effect Concentration.
- TLV: Threshold Limiting Value.
- TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
- STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.