Safety Data Sheet TECNOCOAT H 2049/B

Safety Data Sheet dated: 10/12/2023 - version 1

Date of first edition: 10/12/2023



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: TECNOCOAT H 2049/B

Trade code: 904TH9990

Recommended use of the chemical and restrictions on use

Recommended use: Poliureic membrane Restrictions on use: Data not available.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION







Classification of the chemical

Eye irritation, Category 2A Causes serious eye irritation.
Carcinogenicity, Category 2 Suspected of causing cancer.

Specific target organ toxicity following repeated exposure, May cause damage to organs through prolonged or repeated

Category 2 expos

outogo., _

Toxic to aquatic life

Chronic (long term) aquatic hazard, category 2 Toxic to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word

Acute aquatic hazard, category 2



Warning

Hazard statements

H319 Causes serious eye irritation.H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

Print date 04/24/2024 Production Name TECNOCOAT H 2049/B Page n. 1 of 10

P314 Get medical advice/attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.
P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
20-25 %	diethyltoluenediamine; Diethylmethylbenzenediamine	EC:270-877-4	STOT RE 2, H373; Eye Irrit. 2A, H319; Acute Tox. 4, H302; Acute Tox. 4, H312; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	01-2119486805-25-XXXX
5-10 %	titanium dioxide; Dioxotitanium	CAS:13463-67-7 EC:236-675-5 Index:022-006- 00-2	Carc. 2, H351	01-2119489379-17-XXXX

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Print date 04/24/2024 Production Name TECNOCOAT H 2049/B Page n. 2 of 10

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Country

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ΛEI

Control parameters

Community Occupational Exposure Limits (OEL)

	Туре	Country	Occupational Exposure Limit
titanium dioxide; Dioxotitanium CAS: 13463-67-7	ACGIH		Long Term: 10 mg/m3 A4 - LRT irr
	MAK	GERMANY	Long Term: 0.3 mg/m3
	OSHA		Long Term: 15 mg/m3
	ACGIH		Long Term: 10 mg/m3 A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation
	MAK	AUSTRIA	Long Term: 5 mg/m3; Short Term: 10 mg/m3
	MAK	SWITZERLAN D	Long Term: 3 mg/m3

Occupational Exposure Limit

Predicted No Effect Concentration (PNEC) values

Print date 04/24/2024 Production Name TECNOCOAT H 2049/B Page n. 3 of 10

diethyltoluenediamine; Diethylmethylbenzenedia

mine

CAS: 68479-98-1

Exposure Route: Fresh Water; PNEC Limit: 0.001 mg/l

Exposure Route: Intermittent release; PNEC Limit: 0.005 mg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 17 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0.029 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 0.003 mg/kg

Exposure Route: Soil; PNEC Limit: 0.0056 mg/kg Exposure Route: Oral; PNEC Limit: 2 mg/kg

titanium dioxide; Dioxotitanium CAS: 13463-67-7 Exposure Route: Fresh Water; PNEC Limit: 0.184 mg/l

Exposure Route: Soil; PNEC Limit: 100 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

Exposure Route: Marine water; PNEC Limit: 0.0184 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 100 mg/kg Exposure Route: Freshwater sediments; PNEC Limit: 1000 mg/kg Exposure Route: Intermittent release; PNEC Limit: 0.193 mg/l

Derived No Effect Level (DNEL) values

diethyltoluenediamine;

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects Diethylmethylbenzenedia Worker Industry: 0.13 mg/m3; Consumer: 0.1 mg/m3

mine

CAS: 68479-98-1

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Industry: 1 mg/kg; Consumer: 1 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 0.1 mg/kg

titanium dioxide; Dioxotitanium CAS: 13463-67-7 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

Worker Industry: 10 mg/m3; Worker Professional: 10 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 700 mg/kg

Appropriate engineering controls: Not available

Individual protection measures

Eve protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid grey

Odour: characteristic

Odour threshold: No data available

pH: No data available

Print date 04/24/2024 Production Name TECNOCOAT H 2049/B Page n. 4 of 10 Melting point / freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point: 100 °C (212 °F) Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: 1,02 g/cm3 Solubility in water: No data available

Solubility in water: No data available Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: 1.000,00 cPs

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation The product is classified: Eye irritation, Category 2A(H319)

d) respiratory or skin sensitisation $\,$ Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity The product is classified: Carcinogenicity, Category 2(H351)

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure The product is classified: Specific target organ toxicity following repeated exposure,

Category 2(H373)

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Print date 04/24/2024 Production Name TECNOCOAT H 2049/B Page n. 5 of 10

Toxicological information on main components of the mixture:

diethyltoluenediamine;

Diethylmethylbenzenedia

mine

a) acute toxicity LD50 Oral Rat = 738 mg/kg

titanium dioxide;

Dioxotitanium

a) acute toxicity

LD50 Oral Rat > 5000 mg/kg

LD50 Skin Rat > 2000 mg/m3

LC50 Inhalation Dust Rat > 6.82 mg/l 4h

LD50 Skin Rabbit > 10000 mg/kg

Substance(s) listed on the IARC Monographs:

titanium dioxide; Dioxotitanium Group 2B

Substance(s) listed as OSHA Carcinogen(s):

titanium dioxide; Dioxotitanium

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide; Dioxotitanium

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment. **Eco-Toxicological Information:**

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 2(H401), Chronic (long term) aquatic hazard, category 2(H411)

List of Eco-Toxicological properties of the components

Component Ident. Numb. Ecotox Da

diethyltoluenediamine; CAS: 68479-98- a) Aquatic acute toxicity: LC50 Fish = 200 mg/L 48h

Diethylmethylbenzenediamine

1 - EINECS: 270-877-4 -INDEX: 612-130-00-0

> a) Aquatic acute toxicity: EC50 Daphnia = 0.5 mg/L 48h a) Aquatic acute toxicity: EC50 Algae = 104 mg/L 72h

titanium dioxide; Dioxotitanium CAS: 13463-67- a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96

7 - EINECS: 236-675-5 -INDEX: 022-006-00-2

> a) Aquatic acute toxicity: EC50 Algae = 16 mg/L 72 a) Aquatic acute toxicity: NOEC Algae = 5600 mg/L 72 a) Aquatic acute toxicity: EC50 Daphnia > 100 mg/L 48

Persistence and degradability

Component Persitence/Degradability:

diethyltoluenediamine; Diethylmethylbenzenediamine Non-readily biodegradable

Bioaccumulative potential

Component	Bioaccumulation	Test	Value
diethyltoluenediamine; Diethylmethylbenzenediamine	Not bioaccumulative	BCF - Bioconcentrantion factor	2.750

Mobility in soil

Print date 04/24/2024 Production Name TECNOCOAT H 2049/B 6 of 10 Page n.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN3082 ADR-UN number: 3082 IATA-Un number: 3082 IMDG-Un number: 3082

UN proper shipping name

DOT-Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (diethylmethylbenzenediamine)

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (diethylmethylbenzenediamine)

IATA-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (diethylmethylbenzenediamine)

IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (diethylmethylbenzenediamine)

Transport hazard class(es)

DOT-Hazard Class: 9
ADR-Class: 9
IATA-Class: 9
IMDG-Class: 9

Packing group

DOT Packing Group: III ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: Not Applicable

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 8, 146, 173, 335, IB3, T4, TP1, TP29

DOT-Label(s): 9
DOT-Symbol: N/A
DOT-Cargo Aircraft: N/A
DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A

Print date 04/24/2024 Production Name TECNOCOAT H 2049/B Page n. 7 of 10

DOT-Non-Bulk: N/A Road and Rail (ADR-RID) :

ADR-Label: 9

ADR-Hazard identification number: 90

ADR-Transport category (Tunnel restriction code): 3 (-)

Air (IATA):

IATA-Passenger Aircraft: 964 IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisioning: A97 A158 A197

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 274 335 969

IMDG-EMS: F-A, S-F

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

diethyltoluenediamine; is listed in TSCA Section 8b Section 12b

Diethylmethylbenzenediamine

titanium dioxide; Dioxotitanium is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

titanium dioxide; Dioxotitanium Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

titanium dioxide; Dioxotitanium

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

titanium dioxide; Dioxotitanium

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Print date 04/24/2024 Production Name TECNOCOAT H 2049/B Page n. 8 of 10

Canada - Federal regulations

DSL - Domestic Substances List

Not compliant to DSL inventory

NDSL - Non Domestic Substances List

Not compliant to NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 10/12/2023 - version 1

Additional classification information

NFPA Health: 0 = Minimal

NFPA Flammability: 1 = Combustible if heated

NFPA Reactivity: 0 = Minimal NFPA Special Risk: NONE



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

H319	Causes serious eye irritation.	
H351	Suspected of causing cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
Code	Hazard class and hazard category Description	

Code	Hazard class and hazard category	Description
A.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2
US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
US-HAE/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

04/24/2024 TECNOCOAT H 2049/B Print date Production Name Page n. 9 of 10

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Print date 04/24/2024 Production Name TECNOCOAT H 2049/B Page n. 10of 10