

Safety Data Sheet

TECNOTOP S-3000 T /B

Safety Data Sheet dated: 12/01/2023 - version 1

Date of first edition: 12/01/2023

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: TECNOTOP S-3000 T /B

Trade code: 904TR99998

Recommended use of the chemical and restrictions on use

Recommended use: Coating

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flammable Liquids — Category 3

Flammable liquid and vapour.

Skin irritation, Category 2

Causes skin irritation.

Eye irritation, Category 2A

Causes serious eye irritation.

Respiratory Sensitization, Category 1

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sensitization, Category 1B

May cause an allergic skin reaction.

Specific target organ toxicity following single exposure, Category 3

May cause respiratory irritation.

Specific target organ toxicity following repeated exposure, Category 2

May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Aspiration hazard, Category 1

May be fatal if swallowed and enters airways.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P284 US\$P284
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment (see supplementary instructions on this label).
- P331 Do NOT induce vomiting.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire, use a foam fire extinguisher to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
20-25 %	3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers	CAS:53880-05-0 EC:500-125-5	Skin Sens. 1B, H317; STOT SE 3, H335	01-2119488734-24-0002
10-20 %	xylenes; 1,2 dimethylbenzene	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT RE 2, H373; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	01-2119488216-32-XXXX

10-20 %	propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate	CAS:108-65-6 EC:203-603-9 Index:607-195-00-7	Flam. Liq. 3, H226; STOT SE 3, H336	01-2119475791-29-XXXX
2.5-5 %	reaction mass of ethylbenzene and xylene	EC:905-588-0	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335; STOT RE 2, H373; Asp. Tox. 1, H304	01-2119539452-40-XXXX
0.25-0.49 %	isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	CAS:4098-71-9 EC:223-861-6 Index:615-008-00-5	Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Acute Tox. 1, H330; Resp. Sens. 1, H334; Skin Sens. 1, H317; Aquatic Chronic 2, H411	01-2119490408-31-XXXX

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- If breathing is irregular or stopped, administer artificial respiration.
- In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

- Eye irritation
- Eye damages
- Skin Irritation
- Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

- (see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

- In case of fire, use a foam fire extinguisher to extinguish.

Unsuitable extinguishing media:

- None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: Not available
- Explosive properties: Not available
- Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
 Remove all sources of ignition.
 Wear breathing apparatus if exposed to vapours/dusts/aerosols.
 Provide adequate ventilation.
 Use appropriate respiratory protection.
 Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
 Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
 Do not use on extensive surface areas in premises where there are occupants.
 Use localized ventilation system.
 Don't use empty container before they have been cleaned.
 Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 Contaminated clothing should be changed before entering eating areas.
 Do not eat or drink while working.
 See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
 Store in a well-ventilated place. Keep cool.
 Avoid direct exposure to sunlight.
 Opened containers must be carefully resealed and kept upright to prevent leakage.
 Flammable mixtures may accumulate within the headspace of containers at room temperature.
 Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.
 Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.
 Avoid accumulating electrostatic charge.
 Keep away from food, drink and feed.
 Electrical installations / working materials must comply with the technological safety standards.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.
 Safety electric system.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
xylenes; 1,2 dimethylbenzene CAS: 1330-20-7	EU		Long Term: 221 mg/m3 - 50 ppm; Short Term: 442 mg/m3 - 100 ppm Skin
	ACGIH		Long Term: 100 ppm; Short Term: 150 ppm A4, BEI - URT and eye irr, CNS impair
	MAK	GERMANY	Long Term: 440 mg/m3 - 100 ppm
	OSHA		Long Term: 435 mg/m3 - 100 ppm
	ACGIH		Long Term: 100 ppm; Short Term: 150 ppm A4 - Not Classifiable as a Human Carcinogen; CNS impairment; eye and upper respiratory tract irritation

	MAK	AUSTRIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm
	MAK	SWITZERLAND	Long Term: 435 mg/m ³ - 100 ppm
		D	
	EU		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin (pure)
	MAK	GERMANY	Long Term: 220 mg/m ³ - 50 ppm
propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate CAS: 108-65-6	ACGIH		Long Term: 275 mg/m ³ - 50 ppm; Short Term: 550 mg/m ³ - 100 ppm Skin
	EU		Long Term: 275 mg/m ³ - 50 ppm; Short Term: 550 mg/m ³ - 100 ppm Skin
	EU		Long Term: 275 mg/m ³ - 50 ppm; Short Term: 550 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin
	MAK	GERMANY	Long Term: 270 mg/m ³ - 50 ppm
	MAK	AUSTRIA	Long Term: 275 mg/m ³ - 50 ppm; Short Term: 550 mg/m ³ - 100 ppm
	MAK	SWITZERLAND	Long Term: 275 mg/m ³ - 50 ppm
		D	
	EU		Long Term: 275 mg/m ³ - 50 ppm; Short Term: 550 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin
isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate CAS: 4098-71-9	MAK	GERMANY	Long Term: 0.046 mg/m ³ - 0.005 ppm
	ACGIH		Long Term: 0.005 ppm respiratory sensitization
	MAK	AUSTRIA	Long Term: 0.046 mg/m ³ - 0.005 ppm; Short Term: 0.092 mg/m ³ - 0.01 ppm
	MAK	SWITZERLAND	Long Term: 0.02 mg/m ³
		D	

Biological limit values

xylene; 1,2 dimethylbenzene
CAS: 1330-20-7

Biological Indicator: Methyl uric Acid; Sampling Period: End of turn
Value: 1.5 GGCREAT; Medium: Urine

Predicted No Effect Concentration (PNEC) values

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers
CAS: 53880-05-0

Exposure Route: Fresh Water; PNEC Limit: 0.0015 mg/l

Exposure Route: Marine water; PNEC Limit: 0.00015 mg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

xylene; 1,2 dimethylbenzene
CAS: 1330-20-7

Exposure Route: Fresh Water; PNEC Limit: 0.327 mg/l

Exposure Route: Marine water; PNEC Limit: 0.327 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 12.46 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 12.46 mg/kg

Exposure Route: Soil; PNEC Limit: 2.31 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6.58 mg/l

Exposure Route: Intermittent release; PNEC Limit: 0.32 mg/l

propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate
CAS: 108-65-6

Exposure Route: Fresh Water; PNEC Limit: 0.635 mg/l

Exposure Route: Marine water; PNEC Limit: 0.0635 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 3.29 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 0.329 mg/kg
Exposure Route: Intermittent release; PNEC Limit: 6.35 mg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l
Exposure Route: Soil; PNEC Limit: 0.29 mg/kg

Derived No Effect Level (DNEL) values

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers
CAS: 53880-05-0
Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Industry: 0.58 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 0.29 mg/m³

xylene; 1,2 dimethylbenzene
CAS: 1330-20-7

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Industry: 289 mg/m³; Consumer: 174 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 289 mg/m³; Consumer: 174 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 180 mg/kg; Consumer: 108 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 77 mg/m³; Consumer: 14.8 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 1.6 mg/kg

propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate
CAS: 108-65-6

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 796 mg/kg; Consumer: 320 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 275 mg/m³; Consumer: 33 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 36 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Industry: 550 mg/m³

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid colourless

Odour: No data available

Odour threshold: No data available
pH: No data available
Melting point / freezing point: No data available
Initial boiling point and boiling range: No data available
Flash point: 23 °C (73 °F)
Evaporation rate: No data available
Upper/lower flammability or explosive limits: No data available
Vapour density: No data available
Vapour pressure: No data available
Relative density: 1,50 g/cm³
Solubility in water: No data available
Solubility in oil: No data available
Partition coefficient (n-octanol/water): No data available
Auto-ignition temperature: No data available
Decomposition temperature: No data available
Viscosity: 1.000,00 cPs
Kinematic viscosity: ≤ 14 mm²/sec (40 °C) mm²/s
Explosive properties: No data available
Oxidizing properties: No data available
Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available
Miscibility: No data available
Fat Solubility: No data available
Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

- | | |
|--------------------------------------|---|
| a) acute toxicity | Not classified
Based on available data, the classification criteria are not met |
| b) skin corrosion/irritation | The product is classified: Skin irritation, Category 2(H315) |
| c) serious eye damage/irritation | The product is classified: Eye irritation, Category 2A(H319) |
| d) respiratory or skin sensitisation | The product is classified: Respiratory Sensitization, Category 1(H334), Skin Sensitization, Category 1B(H317) |
| e) germ cell mutagenicity | Not classified
Based on available data, the classification criteria are not met |
| f) carcinogenicity | Not classified
Based on available data, the classification criteria are not met |
| g) reproductive toxicity | Not classified
Based on available data, the classification criteria are not met |
| h) STOT-single exposure | The product is classified: Specific target organ toxicity following single exposure, Category 3(H335) |
| i) STOT-repeated exposure | The product is classified: Specific target organ toxicity following repeated exposure, |

j) aspiration hazard

The product is classified: Aspiration hazard, Category 1(H304)

Toxicological information on main components of the mixture:

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers	a) acute toxicity	LC50 Inhalation Rat > 5 mg/l 4h
		LD50 Oral Rat > 14000 mg/kg
xylenes; 1,2 dimethylbenzene	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg
		LC50 Inhalation Vapour Rat = 11 mg/l 4h
		LD50 Skin Rabbit = 3200 mg/kg
		LD50 Skin Rabbit > 4350 mg/kg
		LC50 Inhalation Rat = 29.08 mg/l 4h
		LD50 Oral Rat = 3500 mg/kg
	e) germ cell mutagenicity	NOAEL Inhalation Rat > 2000 ppm
	f) carcinogenicity	NOAEL Oral Rat = 500 mg/kg
		NOAEL Oral Rat = 1000 mg/kg
	g) reproductive toxicity	NOAEL Inhalation Rat = 500 ppm
propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg
		LD50 Skin Rabbit > 5000 mg/kg
		LD50 Skin Rabbit > 5 g/kg
	e) germ cell mutagenicity	NOAEL Inhalation Rat = 1000 ppm
	g) reproductive toxicity	NOAEL Inhalation Rat = 500 ppm
isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	a) acute toxicity	LD50 Skin Rabbit > 5000 mg/kg
		LC50 Inhalation Rat = 0.135 mg/l 4h
		LD50 Oral Rat = 4814 mg/kg

Substance(s) listed on the IARC Monographs:

xylenes; 1,2 dimethylbenzene Group 3

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION**Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers	CAS: 53880-05-0 - EINECS: 500-125-5	a) Aquatic acute toxicity : LC50 Fish > 1.51 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia > 3.36 mg/L 48 a) Aquatic acute toxicity : EC50 Algae > 3.1 mg/L 72 c) Bacteria toxicity : EC50 Bacteria > 10000 mg/L 3
xylenes; 1,2 dimethylbenzene	CAS: 1330-20-7 - EINECS: 215-535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : EC50 Daphnia = 165 mg/L 48 a) Aquatic acute toxicity : LC50 Fish > 2 mg/L 96 a) Aquatic acute toxicity : EC50 Algae = 2.2 mg/L 72 c) Bacteria toxicity : EC50 = 96 mg/L 24 b) Aquatic chronic toxicity : NOEC Fish > 1.3 mg/L b) Aquatic chronic toxicity : NOEC Daphnia = 1.57 mg/L a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 13.4 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 2.661 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 13.5 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 13.1 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 19 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 7.711 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 23.53 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 780 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio > 780 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata 30.26 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia water flea = 3.82 mg/L 48h a) Aquatic acute toxicity : LC50 Daphnia Gammarus lacustris = 0.6 mg/L 48h
propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate	CAS: 108-65-6 - EINECS: 203-603-9 - INDEX: 607-195-00-7	a) Aquatic acute toxicity : LC50 Fish = 130 mg/L 96h a) Aquatic acute toxicity : EC50 Daphnia >= 100 mg/L 48h b) Aquatic chronic toxicity : NOEC Fish = 47.5 mg/L - 14 d b) Aquatic chronic toxicity : NOEC Daphnia >= 100 mg/L - 21 d b) Aquatic chronic toxicity : NOEC Algae >= 1000 mg/L
isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	CAS: 4098-71-9 - EINECS: 223-861-6 - INDEX: 615-008-00-5	a) Aquatic acute toxicity : EC50 Daphnia = 27 mg/L 48h a) Aquatic acute toxicity : IC50 Fish = 4 mg/L 96h a) Aquatic acute toxicity : NOEC Algae = 4.4 mg/L 72h a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 118.7 mg/L 72h IUCLID

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN1263

ADR-UN number: 1263

IATA-Un number: 1263

IMDG-Un number: 1263

UN proper shipping name

DOT-Proper Shipping Name: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound

ADR-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound) (having a flash-point below 23 °C and viscous according to 2.2.3.1.4) (vapour pressure at 50 °C more than 110 kPa)

IATA-Technical name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IMDG-Technical name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Transport hazard class(es)

DOT-Hazard Class: 3

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

Packing group

DOT Packing Group: III

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: Not Applicable

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 367, B1, B52, B131, IB3, T2, TP1, TP29

DOT-Label(s): 3

DOT-Symbol: N/A
DOT-Cargo Aircraft: N/A
DOT-Passenger Aircraft: N/A
DOT-Bulk: N/A
DOT-Non-Bulk: N/A

Road and Rail (ADR-RID) :

ADR-Label: 3
ADR-Hazard identification number: 30
ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air (IATA) :

IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366
IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3L
IATA-Special Provisioning: A3 A72 A192

Sea (IMDG) :

IMDG-Stowage Code: Category A
IMDG-Stowage Note: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisioning: 163 223 367 955
IMDG-EMS: F-E, S-E

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers is listed in TSCA Section 8b
xylenes; 1,2 dimethylbenzene is listed in TSCA Section 8b
propylene glycol monomethyl ether acetate; 2-methoxy-1-methylethyl acetate is listed in TSCA Section 8b Section 8a - PAIR
isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate is listed in TSCA Section 8b Section 8a - PAIR Section 5

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Section 304 - Hazardous substances:

xylenes; 1,2 dimethylbenzene

Section 313 - Toxic chemical list:

xylenes; 1,2 dimethylbenzene
isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

xylenes; 1,2 dimethylbenzene Reportable quantity: 100 pounds

CAA - Clean Air Act

CAA listed substances:

xylenes; 1,2 dimethylbenzene is listed in CAA Section 112(b) - HAP Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

xylenes; 1,2 dimethylbenzene is listed in CWA Section 311

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

No substances listed

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

xylenes; 1,2 dimethylbenzene

isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

xylenes; 1,2 dimethylbenzene

isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

xylenes; 1,2 dimethylbenzene

isophorone diisocyanate (ipdi); 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Canada - Federal regulations

DSL - Domestic Substances List

Not compliant to DSL inventory

NDSL - Non Domestic Substances List

Not compliant to NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 12/1/2023 - version 1

Additional classification information

NFPA Health: 2 = Moderate

NFPA Flammability: 3 = Flammable liquid

NFPA Reactivity: 0 = Minimal

NFPA Special Risk: NONE



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/1/Inhal	Acute Tox. 1	Acute toxicity (inhalation), Category 1
A.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4

A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.1/1	Resp. Sens. 1	Respiratory Sensitization, Category 1
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.