POLYGLASS RKD-4 KIT SIEVERT FLAMELESS TORCH

PRODUCT DESCRIPTION

Polyglass RKD-4 Kit offers safe, fast and convenient repairs of modified bitumen membranes. Comes with a hook that can easily attach to belt. This can also be used as a "core cut" kit – perfect for estimating. Includes all the parts listed below in a very handy canvas carrying case.

As shown at our Polyschool contractor training classes, the flameless torch helps ensure watertight seals on Self-Adhered products at seams and details, particularly in colder weather. This will improve product performance and quality of installs and contractors will remember Polyglass every time they use the tool.

KIT COMPONENTS

- 3366-97 ProMatic Universal Handle with piezo ignition
- 3358-90 Hot-air burner (3K BTU/hr)
- 3015-04 4 ft hose and regulator for disposable cylinders of Mapp or Propane
- 5013-90 Canvas bag with Sievert embroidered Sievert logo
- Polyglass logo embroidered on bag

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Waco, TX
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc. 1111 West Newport Center Drive Deerfield Beach, FL 33442 www.polyglass.us General Line: (888) 410-1375 (954) 233-1330 Customer Service: (800) 222-9782 Technical Service: (866) 794-9659

Questions? technical@polyglass.com

Product Disclaimer: Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects that result in the material not complying with product specifications for a period of 12 months.

Refer to safety data sheet (SDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances. The product user, and not Polyglass, is responsible for determining the suitability and compatibility of our products for the user's intended use.

For the most current product data and warranty information, visit www.polyglass.us







PRODUCT CODE • RKH-4S-PG

