

Safety Data Sheet

PG 350 LV

Safety Data Sheet dated: 03/11/2025 - version 4

Date of first edition: 02/01/2022

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: PG 350 LV

Trade code: 9067036

Recommended use of the chemical and restrictions on use

Recommended use: Bituminous adhesive solvent based

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive

33442 - Deerfield Beach - FL - USA

Phone: +1 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887 Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flammable Liquids — Category 3

Eye irritation, Category 2A

Carcinogenicity, Category 1A

Specific target organ toxicity following repeated exposure, Category 1

Acute aquatic hazard, category 2

Chronic (long term) aquatic hazard, category 3

Flammable liquid and vapour.

Causes serious eye irritation.

May cause cancer if inhaled, in contact with skin and if swallowed.

Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Toxic to aquatic life

Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H350 May cause cancer if inhaled, in contact with skin and if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

H401 Toxic to aquatic life

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe mist/vapours/spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/clothing and eye/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- 3
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- 8
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
25-50 %	asphalt; bitumen	CAS:8052-42-4 EC:232-490-9	Carc. 2, H351	01-2119480172-44-XXXX
10-20 %	petroleum hydrocarbons; Stoddard Solvent	CAS:8052-41-3 EC:232-489-3 Index:649-345-00-4	Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304	
2.5-5 %	amines, n-tallow alkyltrimethylenedi-, acetates; amine acetate	CAS:61791-54-6 EC:263-188-5	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Acute 1, H400	N.A.
1-2.5 %	1,2,4-trimethyl-benzene; pseudocumene	CAS:95-63-6 EC:202-436-9 Index:601-043-00-3	Flam. Liq. 3, H226; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Acute Tox. 4, H332	01-2119472135-42-XXXX
1-2.5 %	naphthenic oil; Low boiling point naphtha - unspecified	CAS:64742-95-6, 128601-23-0 EC:265-199-0 Index:649-356-00-4	STOT SE 3, H335; STOT SE 3, H336; Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411	01-2119486773-24-XXXX
1-2.5 %	naphthalene	CAS:91-20-3 EC:202-049-5 Index:601-052-00-2	Carc. 2, H351; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	
0.49-1 %	silica sand; quartz	CAS:14808-60-7	STOT RE 1, H372; Carc. 1A, H350	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- If breathing is irregular or stopped, administer artificial respiration.
- In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

- In case of fire, use a dry powder fire extinguisher to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: Not available
- Explosive properties: Not Relevant
- Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.
-

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove all sources of ignition.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Provide adequate ventilation.
- Use appropriate respiratory protection.
- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Limit leakages with earth or sand.

Methods and material for containment and cleaning up

- Suitable material for taking up: absorbing material, organic, sand
 - Retain contaminated washing water and dispose it.
-

7. HANDLING AND STORAGE

Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Exercise the greatest care when handling or opening the container.
- Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Opened containers must be carefully resealed and kept upright to prevent leakage.

Flammable mixtures may accumulate within the headspace of containers at room temperature.

Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.

Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Electrical installations / working materials must comply with the technological safety standards.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
asphalt; bitumen CAS: 8052-42-4	ACGIH		Long Term: 0.5 mg/m ³ (I), A4, BEI - URT and eye irr
	MAK	GERMANY	Long Term: 1.5 mg/m ³
	ACGIH		Long Term: 0.5 mg/m ³ A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free);eye and upper respiratory tract irritation (fume)
petroleum hydrocarbons; Stoddard Solvent CAS: 8052-41-3	MAK	SWITZERLAN D	Long Term: 10 mg/m ³
	OSHA		Long Term: 2900 mg/m ³ - 500 ppm
	ACGIH		Long Term: 100 ppm CNS impairment;eye, kidney and skin damage;nausea;
1,2,4-trimethyl-benzene; pseudocumene CAS: 95-63-6	ACGIH		Long Term: 100 ppm CNS impairment;eye, kidney and skin damage;nausea
	EU		Long Term: 100 mg/m ³ - 20 ppm
	MAK	GERMANY	Long Term: 100 mg/m ³ - 20 ppm
naphthalene CAS: 91-20-3	MAK	AUSTRIA	Long Term: 100 mg/m ³ - 20 ppm; Short Term: 150 mg/m ³ - 30 ppm
	EU		Long Term: 100 mg/m ³ - 20 ppm Behaviour Indicative
	ACGIH		Long Term: 50 mg/m ³ - 10 ppm
	ACGIH		Long Term: 10 ppm

		Skin, A3 - URT irr, cataracts, hemolytic anemia
	OSHA	Long Term: 50 mg/m3 - 10 ppm
	ACGIH	Long Term: 10 ppm A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans;Skin - potential significant contribution to overall exposure by the cutaneous route;cataract;upper respiratory tract irritation;hemolytic anemia
	MAK	AUSTRIA Long Term: 50 mg/m3 - 10 ppm
	MAK	SWITZERLAND Long Term: 50 mg/m3 - 10 ppm
	EU	Long Term: 50 mg/m3 - 10 ppm Behaviour Indicative
silica sand; quartz CAS: 14808-60-7	ACGIH	Long Term: 0.025 mg/m3 A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA Long Term: 0.15 mg/m3
	ACGIH	Long Term: 0.025 mg/m3 (R), A2 - Pulm fibrosis, lung cancer
	MAK	SWITZERLAND Long Term: 0.15 mg/m3
	EU	Long Term: 0.1 mg/m3 Behaviour Binding

Biological limit values

asphalt; bitumen
CAS: 8052-42-4
Biological Indicator: 1-Hydroxypyrene; Sampling Period: End of turn; End of working week
Medium: Urine
Remark: Not Quantitative

Biological Indicator: 1-Hydroxypyrene; Sampling Period: End of turn; End of working week
Value: 2.5 µg/L; Medium: Urine
Remark: Background

Biological Indicator: 3-Hydroxybenzo(a)pyrene with hydrolysis; Sampling Period: End of turn; End of working week
Medium: Urine
Remark: Not Quantitative

naphthalene
CAS: 91-20-3
Biological Indicator: 1,2-Naphthol; Sampling Period: End of turn
Remark: Not Quantitative; Not Specific

Derived No Effect Level (DNEL) values

asphalt; bitumen
CAS: 8052-42-4
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 2.9 mg/m3; Consumer: 0.6 mg/m3

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: viscous liquid dark brown
Odour: mild
Odour threshold: Not Relevant
pH: Not Relevant
Melting point / freezing point: Not Relevant
Initial boiling point and boiling range: No data available
Flash point: 40.5 °C (104.9 °F)
Evaporation rate: Not Relevant
Upper/lower flammability or explosive limits: Not Relevant
Vapour density: Not Relevant
Vapour pressure: Not Relevant
Relative density: 1.12 g/cm³
Solubility in water: insoluble
Solubility in oil: Not Relevant
Partition coefficient (n-octanol/water): Not Relevant
Auto-ignition temperature: Not Relevant
Decomposition temperature: Not Relevant
Viscosity: Not Relevant
Explosive properties: Not Relevant
Oxidizing properties: Not Relevant
Solid/gas flammability: Not Relevant

Other information

Substance Groups relevant properties Not Relevant
Miscibility: Not Relevant
Fat Solubility: Not Relevant
Conductivity: Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	Not classified Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	The product is classified: Carcinogenicity, Category 1A(H350)
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met

i) STOT-repeated exposure The product is classified: Specific target organ toxicity following repeated exposure, Category 1(H372)

j) aspiration hazard Not classified
Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

asphalt; bitumen	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg LD50 Skin Rabbit > 2000 mg/kg LC50 Inhalation Mist Rat > 94.4 mg/l 4h LD50 Skin Rabbit > 2000 mg/kg LC50 Inhalation Rat > 94.4 mg/m ³ 4.5h LD50 Oral Rat > 5000 mg/kg LC50 Inhalation Rat > 94.4 mg/m ³ 4.5h LD50 Oral Rat > 5000 mg/kg	
	i) STOT-repeated exposure	NOAEL Skin Rat = 200 mg/kg	90 d
		NOAEC Inhalation Mist Rat = 20.1 mg/l	90 d
petroleum hydrocarbons; Stoddard Solvent	a) acute toxicity	LD50 Skin Rabbit > 3000 mg/kg LC50 Inhalation Rat > 5.5 mg/l 4h	
1,2,4-trimethyl-benzene; pseudocumene	a) acute toxicity	LD50 Skin Rabbit > 3160 mg/kg LC50 Inhalation Rat = 18 g/m ³ 4h LD50 Oral Rat = 3280 mg/kg	
naphthenic oil; Low boiling point naphtha - unspecified	a) acute toxicity	LD50 Skin Rabbit > 2000 mg/kg LD50 Oral Rat = 3492 mg/kg LC50 Inhalation Vapour Rat = 6193 mg/m ³	
naphthalene	a) acute toxicity	LD50 Oral Rat = 1110 mg/kg	
silica sand; quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg LD50 Skin > 2000 mg/kg	

Substance(s) listed on the IARC Monographs:

asphalt; bitumen	Group 2B
naphthalene	Group 2B
silica sand; quartz	Group 1

Substance(s) listed as OSHA Carcinogen(s):

asphalt; bitumen
naphthalene
silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

asphalt; bitumen
silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

naphthalene
silica sand; quartz

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 2(H401), Chronic (long term) aquatic hazard, category 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
asphalt; bitumen	CAS: 8052-42-4 - EINECS: 232-490-9	a) Aquatic acute toxicity : LC50 Fish = 1000 mg/L b) Aquatic chronic toxicity : NOEC Fish = 1000 mg/L - 28 d
1,2,4-trimethyl-benzene; pseudocumene	CAS: 95-63-6 - EINECS: 202-436-9 - INDEX: 601-043-00-3	G : LC50 Avian Colinus virginianus > 6500 ppm 5d IUCLID G : LD50 Avian Colinus virginianus > 2250 mg/kg IUCLID a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 7.19 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 6.14 mg/L 48h IUCLID
naphthenic oil; Low boiling point naphtha - unspecified	CAS: 64742-95-6, 128601-23-0 - EINECS: 265-199-0 - INDEX: 649-356-00-4	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 9.22 mg/L 96h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 21.3 mg/L 48h IUCLID
naphthalene	CAS: 91-20-3 - EINECS: 202-049-5 - INDEX: 601-052-00-2	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 5.74 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 1.6 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 0.91 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 1.99 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 31.0265 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 2.16 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 1.96 mg/L 48h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 1.09 mg/L 48h EPA

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN1999

ADR-UN number: 1999

IATA-Un number: 1999

IMDG-Un number: 1999

UN proper shipping name

DOT-Proper Shipping Name: Tars, liquid including road oils and cutback bitumens

ADR-Shipping Name: TARS, LIQUID, including road oils, and cutback bitumens

IATA-Technical name: TARS, LIQUID including road asphalt and oils, bitumen and cut backs

IMDG-Technical name: TARS, LIQUID, including road oils, and cutback bitumens

Transport hazard class(es)

DOT-Hazard Class: 3

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

Packing group

DOT Packing Group: III

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: Yes DOT-RQ - Quantity: 100 lbs

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): B1, B13, IB3, T1, TP3

DOT-Label(s): 3

DOT-Symbol: N/A

DOT-Cargo Aircraft: 220 L

DOT-Passenger Aircraft: 60 L

DOT-Bulk: 242

DOT-Non-Bulk: 203

DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID) :

ADR-Label: 3

ADR-Hazard identification number: 30

ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air (IATA) :

IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366
IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3L
IATA-Special Provisioning: A3

Sea (IMDG) :

IMDG-Stowage Code: Category A
IMDG-Stowage Note: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisioning: 955
IMDG-EMS: F-E, S-E

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

asphalt; bitumen	is listed in TSCA	Section 8b
petroleum hydrocarbons; Stoddard Solvent	is listed in TSCA	Section 8b
amines, n-tallow alkyltrimethylenedi-, acetates; amine acetate	is listed in TSCA	Section 8b
1,2,4-trimethyl-benzene; pseudocumene	is listed in TSCA	Section 8b
naphthenic oil; Low boiling point naphtha - unspecified	is listed in TSCA	Section 8b
naphthalene	is listed in TSCA	Section 8b Section 5 Section 8a - PAIR
silica sand; quartz	is listed in TSCA	Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

naphthalene

Section 313 - Toxic chemical list:

1,2,4-trimethyl-benzene; pseudocumene
naphthalene

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

naphthalene	Reportable quantity:	100	pounds
-------------	----------------------	-----	--------

CAA - Clean Air Act

CAA listed substances:

1,2,4-trimethyl-benzene; pseudocumene	is listed in CAA	Section 112(b) - HON
naphthalene	is listed in CAA	Section 112(b) - HAP Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

naphthalene	is listed in CWA	Section 307 Section 311
-------------	------------------	-------------------------

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

asphalt; bitumen	Listed as carcinogen
naphthalene	Listed as carcinogen

silica sand; quartz

Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

asphalt; bitumen
petroleum hydrocarbons; Stoddard Solvent
1,2,4-trimethyl-benzene; pseudocumene
naphthalene
silica sand; quartz

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

asphalt; bitumen
petroleum hydrocarbons; Stoddard Solvent
1,2,4-trimethyl-benzene; pseudocumene
naphthalene
silica sand; quartz

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

asphalt; bitumen
petroleum hydrocarbons; Stoddard Solvent
1,2,4-trimethyl-benzene; pseudocumene
naphthalene
silica sand; quartz

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 3/11/2025 - version 4

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3
US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
US-HAE/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
IMDG: International Maritime Code for Dangerous Goods.
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
CLP: Classification, Labeling, Packaging.
EINECS: European Inventory of Existing Commercial Chemical Substances.
INCI: International Nomenclature of Cosmetic Ingredients.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
GefStoffVO: Ordinance on Hazardous Substances, Germany.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
DNEL: Derived No Effect Level.
PNEC: Predicted No Effect Concentration.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.
KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 4. FIRST AID MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION