

Safety Data Sheet

PG 350

Safety Data Sheet dated: 03/24/2025 - version 3

Date of first edition: 11/11/2022

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: PG 350

Trade code: PLY0110

Recommended use of the chemical and restrictions on use

Recommended use: Bituminous adhesive solvent based

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Polyglass U.S.A. Inc.

1111 West Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 866-222-9782

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flammable Liquids — Category 3

Skin irritation, Category 2

Eye irritation, Category 2A

Specific target organ toxicity following repeated exposure, Category 1

Acute aquatic hazard, category 3

Chronic (long term) aquatic hazard, category 3

Carcinogenicity, Category 2

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Harmful to aquatic life

Harmful to aquatic life with long lasting effects.

Suspected of causing cancer if inhaled, in contact with skin and if swallowed.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer if inhaled, in contact with skin and if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

H402 Harmful to aquatic life

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

- P233

Keep container tightly closed.
- P240

Ground/bond container and receiving equipment.
- P241

Use explosion-proof electrical/ventilating/lighting equipment.
- P242

Use only non-sparking tools.
- P243

Take precautionary measures against static discharge.
- P260

Do not breathe mist/vapours/spray.
- P264

Wash skin thoroughly after handling.
- P270

Do not eat, drink or smoke when using this product.
- P273

Avoid release to the environment.
- P280

Wear protective gloves/clothing and eye/face protection.
- P302+P352

IF ON SKIN: Wash with plenty of water.
- P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313

IF exposed or concerned: Get medical advice/attention.
- P314

Get medical advice/attention if you feel unwell.
- P332+P313

If skin irritation occurs: Get medical advice/attention.
- P337+P313

If eye irritation persists: Get medical advice/attention.
- P362+P364

Take off contaminated clothing and wash it before reuse.
- P370+P378

In case of fire, use a dry powder fire extinguisher to extinguish.
- P403+P235

Store in a well-ventilated place. Keep cool.
- P501

Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

| Qty | Name | Ident. Numb. | Classification | Registration Number |
|---------|---|---|--|-----------------------|
| 25-50 % | asphalt; bitumen | CAS:8052-42-4 EC:232-490-9 | Carc. 2, H351 | 01-2119480172-44-XXXX |
| 25-50 % | petroleum hydrocarbons; Stoddard Solvent | CAS:8052-41-3 EC:232-489-3 Index:649-345-00-4 | Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304 | |
| 2.5-5 % | 1,2,4-trimethyl-benzene; pseudocumene | CAS:95-63-6 EC:202-436-9 Index:601-043-00-3 | Flam. Liq. 3, H226; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Acute Tox. 4, H332 | 01-2119472135-42-XXXX |
| 2.5-5 % | naphthenic oil; Low boiling point naphtha - unspecified | CAS:64742-95-6, 128601-23-0 EC:265-199-0 Index:649-356-00-4 | STOT SE 3, H335; STOT SE 3, H336; Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411 | 01-2119486773-24-XXXX |

| | | | | |
|-------------|---|--------------------------------|---|-----------------------|
| 1-2.5 % | 1-propanamine, 3-(isodecyloxy)-, acetate; 3-(Isodecyloxy)propylammonium acetate | CAS:28701-67-9 EC:249-166-8 | Acute Tox. 4, H302; Eye Dam. 1, H318; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | 01-2120794734-40-XXXX |
| 0.25-0.49 % | silica sand; quartz | CAS:14808-60-7 EC:238-878-4 | STOT RE 1, H372; Carc. 1A, H350 | |

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- If breathing is irregular or stopped, administer artificial respiration.
- In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

- In case of fire, use a dry powder fire extinguisher to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: Not available
- Explosive properties: Not available
- Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus.
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove all sources of ignition.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Provide adequate ventilation.
- Use appropriate respiratory protection.
- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Handle in a well ventilated place.
Always keep in a well ventilated place.
Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
Store in a well-ventilated place. Keep cool.
Avoid direct exposure to sunlight.
Opened containers must be carefully resealed and kept upright to prevent leakage.
Flammable mixtures may accumulate within the headspace of containers at room temperature.
Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.
Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.
Avoid accumulating electrostatic charge.
Keep away from food, drink and feed.
Electrical installations / working materials must comply with the technological safety standards.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

| | OEL Type | Country | Occupational Exposure Limit |
|---|----------|-------------|---|
| asphalt; bitumen CAS: 8052-42-4 | ACGIH | | Long Term: 0.5 mg/m ³ (I), A4, BEI - URT and eye irr |
| | MAK | GERMANY | Long Term: 1.5 mg/m ³ |
| | ACGIH | | Long Term: 0.5 mg/m ³ A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free);eye and upper respiratory tract irritation (fume) |
| petroleum hydrocarbons; Stoddard Solvent CAS: 8052-41-3 | MAK | SWITZERLAND | Long Term: 10 mg/m ³ |
| | OSHA | | Long Term: 2900 mg/m ³ - 500 ppm |
| | ACGIH | | Long Term: 100 ppm CNS impairment;eye, kidney and skin damage;nausea; |
| 1,2,4-trimethyl-benzene; pseudocumene CAS: 95-63-6 | ACGIH | | Long Term: 100 ppm CNS impairment;eye, kidney and skin damage;nausea |
| | EU | | Long Term: 100 mg/m ³ - 20 ppm |

| | | | |
|--|-------|-------------|--|
| silica sand; quartz CAS: 14808-60-7 | MAK | GERMANY | Long Term: 100 mg/m ³ - 20 ppm |
| | MAK | AUSTRIA | Long Term: 100 mg/m ³ - 20 ppm; Short Term: 150 mg/m ³ - 30 ppm |
| | EU | | Long Term: 100 mg/m ³ - 20 ppm Behaviour Indicative |
| | ACGIH | | Long Term: 0.025 mg/m ³ A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis |
| | MAK | AUSTRIA | Long Term: 0.15 mg/m ³ |
| | ACGIH | | Long Term: 0.025 mg/m ³ (R), A2 - Pulm fibrosis, lung cancer |
| | MAK | SWITZERLAND | Long Term: 0.15 mg/m ³ |
| | EU | | Long Term: 0.1 mg/m ³ Behaviour Binding |

Biological limit values

| | | | |
|------------------------------------|---|--|--|
| asphalt; bitumen CAS: 8052-42-4 | Biological Indicator: 1-Hydroxypyrene; Sampling Period: End of turn; End of working week Medium: Urine Remark: Not Quantitative | | |
| | Biological Indicator: 1-Hydroxypyrene; Sampling Period: End of turn; End of working week Value: 2.5 µg/L; Medium: Urine Remark: Background | | |
| | Biological Indicator: 3-Hydroxybenzo(a)pyrene with hydrolysis; Sampling Period: End of turn; End of working week Medium: Urine Remark: Not Quantitative | | |

Derived No Effect Level (DNEL) values

| | |
|------------------------------------|--|
| asphalt; bitumen CAS: 8052-42-4 | Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 2.9 mg/m ³ ; Consumer: 0.6 mg/m ³ |
|------------------------------------|--|

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness ≥0,5mm; breakthrough time ≥480min.

Nitrile rubber - NBR: thickness ≥0,35mm; breakthrough time ≥480min.

Butyl rubber - IIR: thickness ≥0,5mm; breakthrough time ≥480min.

Fluorinated rubber - FKM: thickness ≥0,4mm; breakthrough time ≥480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid black

Odour: hydrocarbons like

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available

Initial boiling point and boiling range: 154 °C (309 °F)

Flash point: 40.5 °C (104.9 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: 4.05 % w/w

Vapour density: >1

Vapour pressure: No data available
Relative density: 0.96 g/cm³
Solubility in water: insoluble
Solubility in oil: No data available
Partition coefficient (n-octanol/water): No data available
Auto-ignition temperature: No data available
Decomposition temperature: No data available
Viscosity: No data available
Explosive properties: No data available
Oxidizing properties: No data available
Solid/gas flammability: Data not applicable

Other information

Substance Groups relevant properties Not normally reactive
Miscibility: No data available
Fat Solubility: No data available
Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

Stable
It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid

Heat and open flames.
Avoid accumulating electrostatic charge.

Incompatible materials

Water
Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

Develop toxic gases when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

| | |
|--------------------------------------|---|
| a) acute toxicity | Not classified Based on available data, the classification criteria are not met |
| b) skin corrosion/irritation | The product is classified: Skin irritation, Category 2(H315) |
| c) serious eye damage/irritation | The product is classified: Eye irritation, Category 2A(H319) |
| d) respiratory or skin sensitisation | Not classified Based on available data, the classification criteria are not met |
| e) germ cell mutagenicity | Not classified Based on available data, the classification criteria are not met |
| f) carcinogenicity | The product is classified: Carcinogenicity, Category 2(H351) |
| g) reproductive toxicity | Not classified Based on available data, the classification criteria are not met |
| h) STOT-single exposure | Not classified Based on available data, the classification criteria are not met |
| i) STOT-repeated exposure | The product is classified: Specific target organ toxicity following repeated exposure, Category 1(H372) |
| j) aspiration hazard | Not classified Based on available data, the classification criteria are not met |

Toxicological information on main components of the mixture:

| | | |
|------------------|-------------------|---|
| asphalt; bitumen | a) acute toxicity | LD50 Oral Rat > 5000 mg/kg LD50 Skin Rabbit > 2000 mg/kg |
|------------------|-------------------|---|

| | | | |
|---|---------------------------|---|------|
| | | LC50 Inhalation Mist Rat > 94.4 mg/l 4h | |
| | | LD50 Skin Rabbit > 2000 mg/kg | |
| | | LC50 Inhalation Rat > 94.4 mg/m3 4.5h | |
| | | LD50 Oral Rat > 5000 mg/kg | |
| | | LC50 Inhalation Rat > 94.4 mg/m3 4.5h | |
| | | LD50 Oral Rat > 5000 mg/kg | |
| | i) STOT-repeated exposure | NOAEL Skin Rat = 200 mg/kg | 90 d |
| | | NOAEC Inhalation Mist Rat = 20.1 mg/l | 90 d |
| petroleum hydrocarbons; Stoddard Solvent | a) acute toxicity | LD50 Skin Rabbit > 3000 mg/kg | |
| | | LC50 Inhalation Rat > 5.5 mg/l 4h | |
| 1,2,4-trimethyl-benzene; pseudocumene | a) acute toxicity | LD50 Skin Rabbit > 3160 mg/kg | |
| | | LC50 Inhalation Rat = 18 g/m3 4h | |
| | | LD50 Oral Rat = 3280 mg/kg | |
| naphthenic oil; Low boiling point naphtha - unspecified | a) acute toxicity | LD50 Skin Rabbit > 2000 mg/kg | |
| | | LD50 Oral Rat = 3492 mg/kg | |
| | | LC50 Inhalation Vapour Rat = 6193 mg/m3 | |
| 1-propanamine, 3-(isodecyloxy)-, acetate; 3-(Isodecyloxy)propylammonium acetate | a) acute toxicity | LD50 Oral Rat = 1216 mg/kg | |
| silica sand; quartz | a) acute toxicity | LD50 Oral > 2000 mg/kg | |
| | | LD50 Skin > 2000 mg/kg | |

Substance(s) listed on the IARC Monographs:

| | |
|---------------------|----------|
| asphalt; bitumen | Group 2B |
| silica sand; quartz | Group 1 |

Substance(s) listed as OSHA Carcinogen(s):

asphalt; bitumen
silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

asphalt; bitumen
silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 3(H402), Chronic (long term) aquatic hazard, category 3(H412)

List of Eco-Toxicological properties of the components

| Component | Ident. Numb. | Ecotox Data |
|---|--|---|
| asphalt; bitumen | CAS: 8052-42-4 - EINECS: 232-490-9 | a) Aquatic acute toxicity : LC50 Fish = 1000 mg/L b) Aquatic chronic toxicity : NOEC Fish = 1000 mg/L - 28 d |
| 1,2,4-trimethyl-benzene; pseudocumene | CAS: 95-63-6 - EINECS: 202-436-9 - INDEX: 601-043-00-3 | G : LC50 Avian Colinus virginianus > 6500 ppm 5d IUCLID G : LD50 Avian Colinus virginianus > 2250 mg/kg IUCLID a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 7.19 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 6.14 mg/L 48h IUCLID |
| naphthenic oil; Low boiling point naphtha - unspecified | CAS: 64742-95-6, 128601-23-0 - EINECS: 265-199-0 - INDEX: 649-356-00-4 | a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 9.22 mg/L 96h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 21.3 mg/L 48h IUCLID |

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN1993

ADR-UN number: 1993

IATA-Un number: 1993

IMDG-Un number: 1993

UN proper shipping name

DOT-Proper Shipping Name: Flammable liquids, n.o.s. (solvent naphtha - trimethylbenzene)

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - trimethylbenzene)
IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - trimethylbenzene)
IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - trimethylbenzene)

Transport hazard class(es)

DOT-Hazard Class: 3
ADR-Class: 3
IATA-Class: 3
IMDG-Class: 3

Packing group

DOT Packing Group: III
ADR-Packing Group: III
IATA-Packing group: III
IMDG-Packing group: III

Environmental hazards

Marine pollutant: No
Environmental Pollutant: Not Applicable
DOT-RQ: Yes DOT-RQ - Quantity: 100 lbs

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): B1, B52, IB3, T4, TP1, TP29
DOT-Label(s): 3
DOT-Symbol: N/A
DOT-Cargo Aircraft: 220 L
DOT-Passenger Aircraft: 60 L
DOT-Bulk: 242
DOT-Non-Bulk: 203
DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID) :

ADR-Label: 3
ADR-Hazard identification number: -
ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA) :

IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366
IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3L
IATA-Special Provisioning: A3

Sea (IMDG) :

IMDG-Stowage Code: Category A
IMDG-Stowage Note: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisioning: 223 274 955
IMDG-EMS: F-E, [S-E]

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

| | | |
|--|-------------------|------------|
| asphalt; bitumen | is listed in TSCA | Section 8b |
| petroleum hydrocarbons; Stoddard Solvent | is listed in TSCA | Section 8b |
| 1,2,4-trimethyl-benzene; | is listed in TSCA | Section 8b |

pseudocumene

naphthenic oil; Low boiling point is listed in TSCA Section 8b
naphtha - unspecified

1-propanamine, 3-(isodecyloxy)-, is listed in TSCA Section 8b
acetate; 3-
(Isodecyloxy)propylammonium
acetate

silica sand; quartz is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

1,2,4-trimethyl-benzene; pseudocumene

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

1,2,4-trimethyl-benzene; is listed in CAA Section 112(b) - HON
pseudocumene

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

asphalt; bitumen Listed as carcinogen

silica sand; quartz Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

asphalt; bitumen

petroleum hydrocarbons; Stoddard Solvent

1,2,4-trimethyl-benzene; pseudocumene

silica sand; quartz

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

asphalt; bitumen

petroleum hydrocarbons; Stoddard Solvent

1,2,4-trimethyl-benzene; pseudocumene

silica sand; quartz

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

asphalt; bitumen

petroleum hydrocarbons; Stoddard Solvent

1,2,4-trimethyl-benzene; pseudocumene

silica sand; quartz

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

16. OTHER INFORMATION

Safety Data Sheet dated: 3/24/2025 - version 3

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

| Code | Description |
|------|---|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H350 | May cause cancer. |
| H351 | Suspected of causing cancer. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |

| Code | Hazard class and hazard category | Description |
|-------------|----------------------------------|--|
| A.1/4/Inhal | Acute Tox. 4 | Acute toxicity (inhalation), Category 4 |
| A.1/4/Oral | Acute Tox. 4 | Acute toxicity (oral), Category 4 |
| A.10/1 | Asp. Tox. 1 | Aspiration hazard, Category 1 |
| A.2/1B | Skin Corr. 1B | Skin corrosion, Category 1B |
| A.2/2 | Skin Irrit. 2 | Skin irritation, Category 2 |
| A.3/1 | Eye Dam. 1 | Serious eye damage, Category 1 |
| A.3/2A | Eye Irrit. 2A | Eye irritation, Category 2A |
| A.6/1A | Carc. 1A | Carcinogenicity, Category 1A |
| A.6/2 | Carc. 2 | Carcinogenicity, Category 2 |
| A.8/3 | STOT SE 3 | Specific target organ toxicity following single exposure, Category 3 |
| A.9/1 | STOT RE 1 | Specific target organ toxicity following repeated exposure, Category 1 |
| B.6/3 | Flam. Liq. 3 | Flammable Liquids — Category 3 |
| US-HAE/A1 | Aquatic Acute 1 | Acute aquatic hazard, category 1 |
| US-HAE/C1 | Aquatic Chronic 1 | Chronic (long term) aquatic hazard, category 1 |
| US-HAE/C2 | Aquatic Chronic 2 | Chronic (long term) aquatic hazard, category 2 |

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.
INCI: International Nomenclature of Cosmetic Ingredients.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
GefStoffVO: Ordinance on Hazardous Substances, Germany.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
DNEL: Derived No Effect Level.
PNEC: Predicted No Effect Concentration.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.
KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION