

POLYGLASS 3" RIBBED GALVALUME® PLATES

PRODUCT DESCRIPTION

Polyglass Steel Plates are made of Galvalume® coated steel. The round design provides an even distribution of loads and eliminates sharp corners that can damage the insulation. These plates are designed to be used with Polyglass fasteners to secure insulation.

COATING

Polyglass plates are coated with AZ55 corrosion resistant coating which passes the corrosion requirements of FM Approval Standard 4470 and EAD030351-00-0402.

APPLICATION

3" (75 mm) Ribbed Galvalume Plate Recessed: Used for attaching insulation to the substrate. Use with Polyglass Standard RoofGrip® Drill Point, Heavy Duty, Extra Heavy Duty, or Concrete (CD-10) fasteners.

3" (75 mm) Ribbed Galvalume Plate Flat Bottom: Used for attaching insulation to the substrate. Sits flat on hard cover boards. Use with Polyglass Standard RoofGrip® Drill Point, Heavy Duty, Extra Heavy Duty, or Concrete (CD-10) fasteners.

2 ¾" Barbed Seam Plate: Used for attaching modified bituminous membranes to the substrate. Use with Polyglass Standard RoofGrip® Drill Point, Heavy Duty, Extra Heavy Duty or Concrete (CD-10) fasteners.

ORDERING INFORMATION*

SKU	LENGTH IN (MM)	PKG QTY	WEIGHT LBS (KG)
SPGA3-RB-PG	3 (75)	1000	40 (18.14)
SPGA3-BRF-PG	3 (75)	1000	40 (18.14)
SPGA234B28-B	2 ¾ (70)	1000	45 (20.41)

*All sizes are nominal

APPLICABLE STANDARDS

- FM Approved



POLYGLASS



www.polyglass.us

POLYGLASS 3" RIBBED GALVALUME® PLATES

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Waco, TX
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.
1111 West Newport Center Drive
Deerfield Beach, FL 33442
www.polyglass.us

General Line: (888) 410-1375
(954) 233-1330
Customer Service: (800) 222-9782
Technical Service: (866) 794-9659

Questions? technical@polyglass.com

Product Disclaimer: Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects in its product that directly results in leakage for a period of 1 year.

Refer to safety data sheet (SDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.

Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control. For most current product data and warranty information, visit www.polyglass.us.