

Technical Bulletin #2018-07

To: All POLYGLASS Users
CC: POLYGLASS Sales & Technical Services
Re: **Guidelines for Cleaning Polyfresko G Membranes**

In our continued effort to support our customers, Polyglass provides the following guidelines for cleaning Polyfresko G membranes—whether APP, SBS, or self-adhered—in the event of algae buildup or incidental surface soiling.

Polyglass recommends using a solution of household bleach and water, applied with a hand-pump sprayer (such as an H.D. Hudson or similar garden-style sprayer). The recommended dilution is 40% bleach to 60% water. All bleach products should be handled and applied in strict accordance with the manufacturer's instructions. Polyglass is not responsible for any issues resulting from the misuse of cleaning agents.

Once the solution has been applied to the membrane surface, allow it to sit for several hours. Light brushing or brooming may be used if necessary to help loosen surface contaminants. After adequate dwell time, rinse the surface thoroughly using low-pressure water from a standard garden hose. Avoid using high-pressure washers or concentrated spray nozzles, as excessive pressure may damage the membrane surface.

Ensure that all rinse water and cleaning solution drains properly and do not result in areas of standing water. Proper drainage must be maintained to preserve the terms and coverage of the Polyglass warranty with respect to ponding or "birdbath" conditions.

For more detailed application or warranty inquiries, please contact the Polyglass Technical Services Department at 866-794-9659 or via email at Technical@Polyglass.com.



Rev 071725