

Technical Bulletin #2010-01

To: All POLYGLASS Users
CC: POLYGLASS Sales & Technical Services
Re: **Polystick Membranes as Compliant Secondary Water Resistant Barriers**

In support of our customers and industry partners, Polyglass provides the following information regarding the use of Polystick self-adhered (SA) membranes as a Secondary Water Resistant Barrier.

Be advised that Polystick self-adhered membranes, including, but not limited to, Polystick TU, TU P, TU Plus, MTS Plus, XFR, and IR-Xe, are compliant as a Secondary Water Resistant Barrier when applied directly to the structural roof deck, as defined by the State of Florida Uniform Mitigation Verification Inspection Form.

This installation must occur where permitted by local jurisdiction or building code. When installed in this manner, these membranes form a continuous, fully bonded layer that enhances protection against water intrusion in the event the primary roofing system is damaged or compromised.

This designation is often used for insurance mitigation purposes and may support eligibility for windstorm insurance discounts. However, final acceptance of a membrane as a qualifying Secondary Water Resistant Barrier remains at the discretion of the insurance carrier or local authority having jurisdiction.

For more detailed application or warranty inquiries, please contact the Polyglass Technical Services Department at 866-794-9659 or via email at Technical@Polyglass.com.



Rev 071725