

MAPEPLAN® P PROFILE RIBS

PVC PROFILE RIBS

PRODUCT DESCRIPTION

Mapeplan P Profile Ribs are extruded thermoplastic components used to replicate the look of a traditional standing seam metal roof. The ribs are hot-air welded to the surface of the Mapeplan roof membrane, giving full flexibility in rib spacing and layout while maintaining the performance of Mapeplan PVC system.

TYPICAL APPLICATIONS

- Cost-effective alternative to standing seam metal roofing

FEATURES AND BENEFITS

- Hot-air welded thermoplastic profiles can be installed on any roof slope
- Ribs do not penetrate the membrane, reducing the risk of leaks
- Fast, straightforward installation
- Flexible rib spacing to meet project design requirements

AVAILABLE COLORS

White (WH)

Grey (GR)

Tan (TA)

APPLICATION INSTRUCTIONS

1. Determine the desired spacing and layout for the Mapeplan P Profile Ribs. Mark the layout on the roof membrane using chalk lines to keep each rib straight and properly aligned.
2. Place the ribs along the layout lines. Connect rib sections by inserting the alignment pin into the hole provided on each section and pressing them together until fully seated.
3. Hold the rib flat and tight against the field membrane. Tack-weld the rib flange to the membrane using a handheld hot-air welder to lock the rib in place and maintain alignment.
4. Once positioned, fully weld both flanges of the rib to the field membrane using a handheld welder or a compatible hot-air welding machine.
5. Continue along the layout until all ribs are installed and fully welded to the membrane.



PRODUCT DATA

Size ...2" W x 1.2" H (50.8 mm W x 33.0 mm H)

Mapeplan P Profile Ribs are made to order.

PRODUCT CODES

- 84997000 — White, 10'
- 84997001 — Tan, 10'
- 84997002 — Grey, 10'

POLYGLASS®



www.polyglass.us

MAPEPLAN® P PROFILE RIBS

PVC PROFILE RIBS

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Waco, TX
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.
1111 West Newport Center Drive
Deerfield Beach, FL 33442
www.polyglass.us

General Line: (888) 410-1375
(954) 233-1330
Customer Service: (800) 222-9782
Technical Service: (866) 794-9659

Questions? technical@polyglass.com

Product Disclaimer: Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects in its product that directly results in leakage for a period of 1 year.

Refer to safety data sheet (SDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.

Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control. For most current product data and warranty information, visit www.polyglass.us.



POLYGLASS®



www.polyglass.us