

MAPEPLAN® P TRIM STRIP

PVC FLASHING MEMBRANE

PRODUCT DESCRIPTION

Mapeplan P Trim Strip is specifically designed to be used as a strip-in membrane for Mapeplan P Clad Metal perimeter edge and flashing details. The Mapeplan P Trim Strip is also installed with Mapeplan P FB Membrane for end joint details and for patch installations. Mapeplan P Trim Strip is a polyester-reinforced roofing membrane with built in chemical, UV and fire resistance. It is installed by hot-air welding, with a 2" (50.8 mm) minimum weld.

TYPICAL APPLICATIONS

- Stripping in Mapeplan P Clad Metal
- Laps on Mapeplan PVC FB Membrane when necessary
- Patches on the roof

FEATURES AND BENEFITS

- Flexible reinforced membrane
- Available in white, tan, and grey

TECHNICAL DESCRIPTION*

Physical Properties	ASTM Method	ASTM Value	Typical Performance
Overall thickness, min.	D751	0.045" (1.14 mm)	0.060" (1.52 mm)
Thickness over scrim, min.	D7635	0.016" (0.40 mm)	0.019" (0.48 mm)
Breaking strength, min.	D751 Grab Method	200 lbf/in (890 N)	200 lbf/in
Elongation at break, min.	D751 Grab Method	15%	15%
Seam strength, min.	D751 B-Tongue	75%	90%
Retention of properties after heat aging:	D3045		
Breaking strength, min.	D751 Grab Method	90%	90%
Elongation, min.	D751 Grab Method	90%	90%
Tearing strength, min.	D751	45 lbf (200 N)	45 lbf (200 N)
Low temperature bend	D2136	pass	-40°C (-40°F)
Accelerated weathering test (cracking/crazing)	G155	none	none
Linear dimensional change, max.	D1204	0.50%	0.50%
Change in weight after immersion in water, max.	D570	± 3.0%	± 3.0%
Static puncture resistance	D5602	pass	pass
Dynamic puncture resistance	D5635	pass	pass

*The properties in this table are "as manufactured" unless otherwise noted.

AVAILABLE COLORS

White (WH) Grey (GR) Tan (TA)

APPLICATION INSTRUCTIONS

- Ensure surfaces to receive Mapeplan P Trim Strip are clean, dry, and smooth.
- Mapeplan P Trim Strip must be hot-air welded. All seams must be probed.
- Follow all Polyglass Technical Specifications.



PRODUCT DATA

Thickness 60 mils (1.52 mm)
 Roll Size 8" x 100" (20 cm x 30.5 m)
 Rolls/Carton 2

PRODUCT CODES

- 7541838000 – White
- 7541838001 – Tan
- 7541838002 – Grey

POLYGLASS



www.polyglass.us

MAPEPLAN® P TRIM STRIP

PVC FLASHING MEMBRANE

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Waco, TX
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.
1111 West Newport Center Drive
Deerfield Beach, FL 33442
www.polyglass.us

General Line: (888) 410-1375
(954) 233-1330
Customer Service: (800) 222-9782
Technical Service: (866) 794-9659

Questions? technical@polyglass.com

Product Disclaimer: Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects in its product that directly results in leakage for a period of 1 year.

Refer to safety data sheet (SDS) for specific data and handling of our products. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.

Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control. For most current product data and warranty information, visit www.polyglass.us.



www.polyglass.us