

MAPEPLAN® P WALKWAY PAD

PVC WALKWAY PAD

PRODUCT DESCRIPTION

Mapeplan P Walkway Pad is a traffic-bearing rooftop walkway designed for use with Polyglass Mapeplan PVC roofing systems. It serves as a durable protective layer that shields the roof membrane from wear in areas with frequent foot traffic or routine maintenance activity. The pad is available in gray or safety yellow to clearly designate access paths, service zones, and high-visibility areas. Its textured surface provides excellent skid resistance, and its low-profile construction allows water to drain freely without creating obstructions on the roof.

TYPICAL APPLICATIONS

- Designating maintenance walkways on Mapeplan PVC roof systems
- Providing protection around rooftop equipment such as HVAC units, and vents
- Creating high-visibility access paths to ladders, hatches, and service points

FEATURES AND BENEFITS

- Durable, traffic-rated surface protects membrane from puncture, abrasion, and wear
- Textured top surface offers strong skid resistance for improved worker safety
- Low-profile design promotes proper drainage and minimizes debris accumulation
- Available in high-visibility colors to clearly identify designated walkways and service areas
- Hot-air welded perimeter ensures a secure, permanent bond to the Mapeplan PVC membrane

TECHNICAL DESCRIPTION*

Physical Properties	Value
Reinforcement	1000 denier polyester
Tear Strength (MD x XMD)	210 lbf x 200 lbf (934 N x 890 N)
Puncture Resistance	96 lbf (427 N)
Shore A Durometer	85
Low Temperature Bend	-40°F (-40°C)
Hydrostatic Resistance	400 psi (2758 kPa)
Dimensional Stability	less than 1%

*The properties in this table are "as manufactured" unless otherwise noted.

AVAILABLE COLORS

Safety Yellow (SY) Grey (GR)

APPLICATION INSTRUCTIONS

1. Install In Accordance with Mapeplan PVC Installation Instructions.
2. Install the Mapeplan P Walkway Pad to the roof surface using the hotair welding method. Weld the perimeter of each pad to the existing Mapeplan PVC membrane to create a secure, permanent bond.
3. Cut walkway rolls into sections no longer than 10' (3 m). Maintain a minimum 2" (50.8 mm) space between adjacent sections to allow for proper drainage and membrane movement.



PRODUCT DATA**

Net Coverage 150 ft² (13.9 m²)
Thickness 90 mils (2.3 mm)
Roll Size 2 1/2' x 60' (0.8 m x 18.3 m)
Rolls/Pallet..... 20

**All values are nominal at time of manufacturing

PRODUCT CODES

- 7541938000 – Grey
- 7541938001 – Yellow

MAPEPLAN® P WALKWAY PAD

PVC WALKWAY PAD

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Waco, TX
- Winter Haven, FL

CORPORATE HEADQUARTERS

Polyglass U.S.A., Inc.
1111 West Newport Center Drive
Deerfield Beach, FL 33442
www.polyglass.us

General Line: (888) 410-1375
(954) 233-1330
Customer Service: (800) 222-9782
Technical Service: (866) 794-9659

Questions? technical@polyglass.com

Product Disclaimer: Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) against manufacturing defects in its product that directly results in leakage for a period of 1 year.

Refer to the Safety Data Sheet (SDS) for the referenced product, which provides comprehensive information on chemical, physical, and health hazards, as well as guidance on safe handling, use, storage, and disposal. All data furnished refers to standard production and is given in good faith within the applicable manufacturing and testing tolerances.

Polyglass U.S.A., Inc., reserves the right to improve and change its products at any time without prior notice. Polyglass U.S.A., Inc. cannot be held responsible for the use of its products under conditions beyond its own control. For most current product data and warranty information, visit www.polyglass.us.



POLYGLASS®



www.polyglass.us