



# SILICONE COATINGS MATRIX

| Polyglass Product                                                                              | Single Ply Membranes                                                    | Metal Roofs                                                             | Smooth Mod Bit or Smooth BUR                                            | Granulated Mod-Bit                                                      | Concrete                                                                | Roof Foam                                                               |
|------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------|
| <b>PolyBrite® 78</b><br>Rinseable EPDM Primer                                                  | 500 sq. ft. @ gal.<br>(Sprayer Only)                                    | N/A                                                                     | N/A                                                                     | N/A                                                                     | N/A                                                                     | N/A                                                                     |
| <b>PolyBrite® 79</b><br>Solvent-based TPO Primer                                               | 300-400 sq. ft. @ gal.<br>(TPO Only)                                    | N/A                                                                     | N/A                                                                     | N/A                                                                     | N/A                                                                     | N/A                                                                     |
| <b>PolyBrite® 84</b><br>Rust Inhibitive Primer                                                 | N/A                                                                     | 200-300 sq. ft. @ gal.                                                  | N/A                                                                     | N/A                                                                     | N/A                                                                     | N/A                                                                     |
| <b>PolyBrite® 98</b><br>Acrylic Primer/Bleed Blocker @ Silicone                                | 200-300 sq. ft. @ gal.<br>(PVC Only)                                    | N/A                                                                     | 100-200 sq. ft. @ gal.                                                  | 100-200 sq. ft. @ gal.                                                  | 100-200 sq. ft. @ gal.                                                  | N/A                                                                     |
| <b>PolyBrite® 90 Series</b><br>High-Solids Premium Silicone Coating <sup>3</sup>               | 10 Yr = 1.5 Gal/Sq<br>15 Yr = 2.0 Gal/Sq<br>20 Yr = 2.5 Gal/Sq          | 10 Yr = 1.5 Gal/Sq<br>15 Yr = 2.0 Gal/Sq<br>20 Yr = 2.5 Gal/Sq          | 10 Yr = 1.5 Gal/Sq<br>15 Yr = 2.0 Gal/Sq<br>20 Yr = 2.5 Gal/Sq          | 10 Yr = 1.5 Gal/Sq<br>15 Yr = 2.0 Gal/Sq<br>20 Yr = 2.5 Gal/Sq          | 10 Yr = 1.5 Gal/Sq<br>15 Yr = 2.0 Gal/Sq<br>20 Yr = 2.5 Gal/Sq          | 10 Yr = 1.5 Gal/Sq<br>15 Yr = 2.0 Gal/Sq<br>20 Yr = 2.5 Gal/Sq          |
|                                                                                                | 10 Yr = 24 WFT/23 DFT<br>15 Yr = 32 WFT/30 DFT<br>20 Yr = 40 WFT/38 DFT | 10 Yr = 24 WFT/23 DFT<br>15 Yr = 32 WFT/30 DFT<br>20 Yr = 40 WFT/38 DFT | 10 Yr = 24 WFT/23 DFT<br>15 Yr = 32 WFT/30 DFT<br>20 Yr = 40 WFT/38 DFT | 10 Yr = 24 WFT/23 DFT<br>15 Yr = 32 WFT/30 DFT<br>20 Yr = 40 WFT/38 DFT | 10 Yr = 24 WFT/23 DFT<br>15 Yr = 32 WFT/30 DFT<br>20 Yr = 40 WFT/38 DFT | 10 Yr = 24 WFT/23 DFT<br>15 Yr = 32 WFT/30 DFT<br>20 Yr = 40 WFT/38 DFT |
| <b>PolyBrite® 95 Series</b><br>Solvent-Based Silicone Coating <sup>3</sup>                     | 10 Yr = 2.0 Gal/Sq<br>15 Yr = 2.5 Gal/Sq<br>20 Yr = 3.0 Gal/Sq          | 10 Yr = 2.0 Gal/Sq<br>15 Yr = 2.5 Gal/Sq<br>20 Yr = 3.0 Gal/Sq          | 10 Yr = 2.0 Gal/Sq<br>15 Yr = 2.5 Gal/Sq<br>20 Yr = 3.0 Gal/Sq          | 10 Yr = 2.0 Gal/Sq<br>15 Yr = 2.5 Gal/Sq<br>20 Yr = 3.0 Gal/Sq          | 10 Yr = 2.0 Gal/Sq<br>15 Yr = 2.5 Gal/Sq<br>20 Yr = 3.0 Gal/Sq          | 10 Yr = 2.0 Gal/Sq<br>15 Yr = 2.5 Gal/Sq<br>20 Yr = 3.0 Gal/Sq          |
|                                                                                                | 10 Yr = 32 WFT/22 DFT<br>15 Yr = 40 WFT/27 DFT<br>20 Yr = 48 WFT/33 DFT | 10 Yr = 32 WFT/22 DFT<br>15 Yr = 40 WFT/27 DFT<br>20 Yr = 48 WFT/33 DFT | 10 Yr = 32 WFT/22 DFT<br>15 Yr = 40 WFT/27 DFT<br>20 Yr = 48 WFT/33 DFT | 10 Yr = 32 WFT/22 DFT<br>15 Yr = 40 WFT/27 DFT<br>20 Yr = 48 WFT/33 DFT | 10 Yr = 32 WFT/22 DFT<br>15 Yr = 40 WFT/27 DFT<br>20 Yr = 48 WFT/33 DFT | 10 Yr = 32 WFT/22 DFT<br>15 Yr = 40 WFT/27 DFT<br>20 Yr = 48 WFT/33 DFT |
| <b>PolyFlash® 1C</b> <sup>1,2</sup><br>1-Part Flashing Compound                                | 2.0 gal/sq.<br>32 WFT/26 DFT                                            | 2.0 gal/sq.<br>32 WFT/26 DFT                                            | 2.0 gal/sq.<br>32 WFT/26 DFT                                            | 2.0 gal/sq.<br>32 WFT/26 DFT                                            | 2.0 gal/sq.<br>32 WFT/26 DFT                                            | 2.0 gal/sq.<br>32 WFT/26 DFT                                            |
| 1 Gallon applied at 32 Wet Mils (26 Dry Mils) 6" wide will theoretically cover 100 lineal feet |                                                                         |                                                                         |                                                                         |                                                                         |                                                                         |                                                                         |
| <b>PolyBrite® 93</b> <sup>1,2</sup><br>Silicone Flashing Compound                              | 2.5 gal/sq.<br>40 WFT/39 DFT                                            | 250 - 350 fasteners per<br>gallon, approx.                              | 2.5 gal/sq.<br>40 WFT/39 DFT                                            | 2.5 gal/sq.<br>40 WFT/39 DFT                                            | 2.5 gal/sq.<br>40 WFT/39 DFT                                            | 2.5 gal/sq.<br>40 WFT/39 DFT                                            |
| 1 Gallon applied at 32 Wet Mils (26 Dry Mils) 6" wide will theoretically cover 100 lineal feet |                                                                         |                                                                         |                                                                         |                                                                         |                                                                         |                                                                         |

1 - The product is applied using the standard three-course method, with the listed quantity covering both below and above the fabric for each layer.

2 - Approx. 250-350 fasteners or 75-100 lf. at 4" wide per 1 Gallon

3 - Above coverages is for Labor & Material and NDL Warranties for Registered Contractors.

## Warranty Fees:

NDL - 10 Year \$.05 per square foot or \$500 Minimum.

NDL - 15 Year \$.07 per square foot or \$700 Minimum.

NDL - 20 Year \$.09 per square foot or \$900 Minimum.