



APP & SBS Low Slope Warranty Matrix for NDL Roof System and Labor & Material Warranties

Polyglass Product	10 Year	12 Year	15 Year	20 Year	25 Year ³ (Premio Pro Only)	30 Year ³ (Premio Pro Only)
SBS Membranes¹ - Heat Welded, Hot Applied, and Cold Process Systems	Minimum 1-ply fully bonded with sanded, coated, or granulated surfacing	Minimum 1-ply fully bonded with coated or granulated surfacing	Minimum 1-ply fully bonded base sheet with a fully bonded granulated cap sheet	Minimum 1-ply fully bonded base sheet with a fully bonded granulated cap sheet	Minimum 1-ply fully bonded base sheet with a minimum 2.5 mm thickness with a fully bonded cap sheet being Polyfresko® G SBS or any HP or TS Membranes or Minimum 2-ply of any fully bonded base & interply with a fully bonded cap sheet being Polyfresko® G SBS or any HP or TS Membranes	Minimum 2-ply fully bonded base & interply sheets with a fully bonded cap sheet being Polyfresko® G SBS or a granulated HP Membrane
APP Membranes - Heat Welded Systems	Minimum 1-ply fully bonded with sanded, coated, or granulated surfacing	Minimum 1-ply fully bonded with coated or granulated surfacing	Minimum 1-ply fully bonded base sheet with a fully bonded granulated cap sheet	Minimum 1-ply fully bonded base sheet with a fully bonded granulated cap sheet (except Polybond G)	Minimum 1-ply fully bonded base sheet with a minimum 2.5 mm thickness with a fully bonded cap sheet being Polyfresko® G or any granulated HP Membrane	Minimum 2-ply fully bonded base & interply sheets with cap sheet being Polyfresko® G or a granulated HP Membrane
SBS & APP Membranes - Full Self-Adhered Systems	Minimum 1-ply fully bonded base sheet with a fully bonded cap sheet having granulated surfacing	Minimum 1-ply fully bonded base sheet with a fully bonded cap sheet having granulated surfacing	Minimum 1-ply fully bonded base sheet (except Elastobase SA) with a fully bonded granulated cap sheet	Minimum 1-ply fully bonded of Elastoflex SA V Plus, or Elastoflex SA Base with a fully bonded SA cap sheet or Minimum 1-ply fully bonded any SA Base Sheet (Except Elastobase® SA) with a fully bonded Polyfresko® G SA or Polyfresko® G SBS SA cap sheet	Minimum 1-ply fully bonded of Elastoflex SA V Plus, or Elastoflex SA Base with a fully bonded Polyfresko® G SA or Polyfresko® G SBS SA cap sheet or Minimum 2-ply fully bonded any SA base & interply sheet (Except Elastobase® SA) with a fully bonded Polyfresko® G SA or Polyfresko® G SBS SA cap sheet	Minimum 2-ply of any fully bonded SA base & interply sheet (except Elastobase® SA) with a fully bonded Polyfresko® G SA or Polyfresko® G SBS SA cap sheet
SBS & APP Membranes - (Stick1 - Torch1)	Minimum 1-ply fully bonded SA base sheet with a heat welded granulated cap sheet	Minimum 1-ply fully bonded SA base sheet with a heat welded granulated cap sheet	Minimum 1-ply fully bonded SA base sheet (except Elastobase SA) with any SBS or APP heat welded granulated cap sheet	Minimum 1-ply fully bonded SA base sheet (except Elastobase® SA) with any SBS or APP heat welded granulated cap sheet	Minimum 1-ply fully bonded base sheet of Elastoflex SA V Plus, or Elastoflex SA Base with a heat welded cap sheet of Polyfresko® G, Polyfresko® G SBS, or any torch-applied SBS or APP granulated membrane classified as HP or TS	Minimum 2-ply fully bonded any SA base & interply sheet (except Elastobase® SA) with a heat welded cap sheet of Polyfresko® G, Polyfresko® G SBS, or any torch-applied SBS or APP membrane classified as HP
SBS & APP Membranes - Modifleece® Systems	Modifleece® base sheet adhered with LRF in spatter pattern with fully bonded granulated cap sheet	Modifleece® base sheet adhered with LRF in spatter pattern with fully bonded granulated cap sheet	Modifleece® base sheet adhered with LRF in spatter pattern with fully bonded granulated cap sheet	Modifleece® base sheet adhered with LRF in spatter pattern with fully bonded granulated cap sheet	Modifleece® base sheet adhered with LRF in spatter pattern with a fully bonded Polyfresko® G, Polyfresko® G SBS, Polyfresko® G SA, or Polyfresko® G SBS SA cap sheet, or any HP or TS cap membranes, heat welded	Modifleece® base sheet adhered with LRF in spatter pattern with a Minimum 1-ply of any fully bonded heat welded or SA interply sheet (except Elastobase® SA) with a fully bonded Polyfresko® G, Polyfresko® G SBS, Polyfresko® G SA, or Polyfresko® G SBS SA cap sheet, or any HP cap membranes, heat welded
SBS & APP Membranes - Velociflex Systems²	Minimum 1-ply mechanically attached base sheet with a fully bonded SA granulated cap sheet	Minimum 1-ply mechanically attached base sheet with a fully bonded SA granulated cap sheet	Minimum 1-ply mechanically attached base sheet with heat welded side laps with any SBS or APP granulated cap sheet	Minimum 1-ply mechanically attached base sheet with heat welded side laps with any SBS or APP granulated cap sheet	Minimum 1 ply mechanically attached base sheet with heat welded side laps with a heat welded cap sheet of Polyfresko® G, Polyfresko® G SBS, or any SBS or APP classified as HP or TS	Minimum 1-ply mechanically attached base sheet with heat welded side laps with 1-ply of any SBS or APP interply sheet heat welded with a cap sheet of Polyfresko® G, Polyfresko® G SBS, or any heat welded SBS or APP membrane classified as HP or TS

General Notations:

Warranty term availability is subject to contractor tier eligibility and applicable Polyglass warranty requirements.

Twenty-five (25) and thirty (30) year warranty terms are available to Premio Pro contractors only.

All generic products referenced (e.g., base ply) shall be Polyglass membranes

All FR and HP versions of listed products are acceptable for use.

“Fully bonded” does not imply 100% contact. Minor inconsistencies in adhesion may occur due to deck conditions or installation variables,

but are acceptable. All systems need to be applied over approved substrates.

LRF stands for Low Rise Foam. Refer to product data sheets for approved LRF products.

Labor & Materials Warranties are available for both residential and commercial projects. NDL Roof System Warranties are intended

for commercial projects only,

unless otherwise approved in writing by Polyglass Technical Services.

1 - Modibase is not included in this matrix. Please contact Polyglass Technical for further assistance.

2 - Velociflex Systems have specific base sheet requirements, fastening patterns, and a minimum width on side laps. Please review prior to installation.

Warranty Fees:

Labor & Material - No Fee

10 Year NDL RSW - \$0.05/ft²: \$300.00 minimum fee

12 Year NDL RSW - \$0.06/ft²: \$400.00 minimum fee

15 Year NDL RSW - \$0.10/ft²: \$600.00 minimum fee

20 Year NDL RSW - \$0.12/ft²: \$1,000.00 minimum fee

25 Year NDL RSW - \$0.15/ft²: \$1,300.00 minimum fee (Premio Pro Only)

30 Year NDL RSW - \$0.18/ft²: \$1,400.00 minimum fee (Premio Pro Only)